

FLOWING EXPERTISE

AUGUST 2022



PLUMBING AND
HYDRONICS
CATALOG



FLOWING EXPERTISE

With our heating and plumbing solutions, we have been redesigning the comfort of the spaces we live and work in for over 60 years. This is thanks to the flow of expertise, technology, experience and innovations that we have acquired over the years by constantly exchanging ideas with our customers and suppliers. A flow that pushes boundaries, allowing us to constantly set the benchmark. A flow that allows us to always look one step ahead into the future.



FLOW OF LIFE

A unique way of flowing. It is **continuous change**, a high degree of reliability in our work, and the ongoing pursuit of total quality, which is the result of small daily actions.



FUTURE

Innovation aimed at creating **new forms of comfort** for spaces, which motivates us to continue to grow and improve.



SUSTAINABILITY

Our focus on preserving **environmental, social and economic well-being** so that it can be passed on to future generations through our products and processes.



TECHNOLOGY

Our ability to do research, invest in processes and develop **state-of-the-art solutions** in an ever-evolving world of expertise.




MADE IN CALEFFI

A uniqueness consisting of many details, which is what we are known for worldwide. True **“Made in Italy”** quality, the hallmark of our company.




1	9	HYDRAULIC SEPARATORS
2	15	AIR AND DIRT SEPARATORS AND AIR VENTS
3	29	THERMOSTATIC RADIATOR VALVES
4	35	ZONE VALVES AND ZONE CONTROLS
5	43	DISTRIBUTION MANIFOLDS AND TEMPERATURE MIXING STATIONS
6A	53	MIXING VALVES FOR PLUMBING AND HYDRONICS
6B	65	BALANCING VALVES FOR PLUMBING AND HYDRONICS
6C	81	PRVS, BACKFLOW PREVENTERS
6D	91	PLUMBING MISCELLANEOUS COMPONENTS
7	97	FILLING UNITS AND BOILER TRIM KITS
8	103	FITTINGS AND MISCELLANEOUS COMPONENTS
9	115	RENEWABLES, SOLAR AND BIOMASS DEVICES
10	121	ENERGY METERS
11	126	INDEX

Hydronics Product Selector



Key	Part Number	Description	Pages #
1	549506A	SEP4™ hydraulic, air, dirt, mag separator	10
2	546328AM	DIRTMAG® PRO Magnetic Dirt Separator	24
3	508013A*	Hygroscopic air vent	17
4	551706A	DISCAL® air separator, rotating collar	19
5	221500*	Radiator valve	31
6	472000*	Remote wall sensor	30
7	200000*	Radiator valve control head	30
8	301040*	Radiator connection valves	32
9	656344*	TwisTop™ thermo-electric actuator	36 & 50
10	ZVR103	Z-one™ valve relay control	40
11	Z55P	Z-one™ valve assembly	37
12	6636E5A*	Manifold	47
13	6686E5S1A*	TwistFlow™ manifold	46
14	1725E1AHE*	Manifold mixing station	44
15	520510AX	TankMixer™ thermostatic mixing assembly	63
16	521619A*	MixCal™ thermostatic mixing valve	55
17	132662A	QuickSetter™ balancing valve	67
18	127361AF*	FlowCal™ automatic balancing valve	71
19	128556AF*	FlowCal™	74
20	128756000	Y-strainer	92
21	NA502640A	PLUMBVENT™ low lead automatic air vent	94
22	573002A	AutoFill™ combo ASSE 1012	100
23	574151A	AutoFill™ combo ASSE 1013	101
24	626600A*	Paddle flow switch	113
25	519600A*	Differential pressure bypass valve	112

Residential



Alternative
to 521201A
4-way
Scald protection
mixing valve

Key	Part Number	Description	Catalog Pages
9	132537AFC	QuickSetter+™ manual balancing valve	66
10	127356AF*	FlowCal™ automatic balancing valve	69
11	116151AC	ThermoSetter™ thermal balancing valve	76
12	533351HA	PresCal™ pressure reducing valve ASSE 1003	84
13	574050A	RPZ backflow preventer ASSE 1013	87
14	NA502640A	PLUMBVENT™ low lead automatic air vent	94
15	535991HA	PresCal™ pressure reducing valve ASSE 1003	82
16	NA10907	NPT y-strainer	93
17	128741000	FlowCal+™ union y-strainer	92


HIGH PERFORMANCE MULTI-FUNCTION HYDRAULIC SEPARATORS



The Caleffi **SEP4™** saves on system installation and maintenance costs with four high performance functions combined into one device: hydraulic separation, micro-bubble coalescing air separation, dirt separation and magnetic separation. **CALEFFI GUARANTEED.**



HYDRAULIC SEPARATORS



PRODUCTS INCLUDED IN SECTION

- 4-in-1 hydraulic separators
- Hydraulic separators
- Combination hydraulic separator and manifold
- Hydraulic separator accessories

4-IN-1 HYDRAULIC SEPARATORS



5495 SEP4™

Combination 1. air, 2. hydraulic and 3. dirt separation, plus 4. magnetic separation. Epoxy resin coated steel body. HDPE internal coalescing element, removable for cleaning. Includes mounting bracket. Thermowell tap: 1/2" straight female. Max. working pressure: 150 psi. Working temperature range: 32–212°F.



Code	Description	Lbs	USD
549596A	1" sweat union	15	881.00
549506A	1" NPT female union	15	916.00
549566A	1" press union	15	964.00
549597A	1¼" sweat union	19	1,075.00
549507A	1¼" NPT female union	19	1,111.00
549567A	1¼" press union	19	1,221.00
549598A	1½" sweat union	27	1,403.00
549508A	1½" NPT female union	27	1,453.00
549568A	1½" press union	27	1,586.00
549599A	2" sweat union	29	1,609.00
549509A	2" NPT female union	29	1,649.00
549569A	2" press union	29	1,852.00
549506US*	1" no tailpieces	13	751.00
549507US*	1¼" no tailpieces	16	876.00
549508US*	1½" no tailpieces	23	1,033.00
549509US*	2" no tailpieces	24	1,252.00

*See Separator fittings in Section 8.



NA549 SEP4™

Combination 1. air, 2. hydraulic, 3. dirt separation, plus 4. magnetic separation. Epoxy resin coated steel body. Stainless steel internal coalescing mesh. Pre-formed insulation on 2" – 4" sizes. One neodymium magnet assembly. Complete with: automatic air vent (code 501502A). air vent shut-off valve (code NA39589). 1" drain valve NA39753 (2" – 4" sizes) 1¼" drain valve NA39588 (5" – 6" sizes). ANSI 150 flange connections. Max. working pressure: 150 psi. Vessel temperature range: 32–220°F. Working temp. w/o insulation: 32–270°F. Particle separation capacity: to 5 µm (0.2 mil).



Code	Description	Lbs	USD
549552A	2" ANSI flange	76	5,852.00
549562A	2½" ANSI flange	82	6,237.00
549582A	3" ANSI flange	112	7,805.00
549510A	4" ANSI flange	120	8,741.00

Code	Description	Lbs	USD
NA549052AM	2" ANSI flange ASME & CRN	76	6,812.00
NA549062AM	2½" ANSI flange ASME & CRN	82	7,315.00
NA549082AM	3" ANSI flange ASME & CRN	112	9,053.00
NA549102AM	4" ANSI flange ASME & CRN	120	9,546.00
NA549120AM*	5" ANSI flange ASME & CRN	220	13,750.00
NA549150AM*	6" ANSI flange ASME & CRN	235	16,587.00

*Without insulation

NA prefix indicates ASME U-stamp tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors; CRN registered.



NA549 SEP4™ ASME

Combination 1. air, 2. hydraulic and 3. dirt separation, plus 4. magnetic separation. Three neodymium magnet assemblies. Complete with: automatic air vent (code 501502A). air vent shut-off valve (code NA39589). drain valve (code NA59600). ANSI 150 flange connections. Thermometer pockets (NPT): ½" inlet/outlet flanges, ¾" front center Max. working pressure: 150 psi. Vessel temperature range: 32–270°F. Particle separation capacity: to 5 µm (0.2 mil). CRN registered through 12". Consult factory for 14".



Code	Description	Lbs	USD
NA549200AM	8" ANSI flange ASME & CRN	530	28,709.00
NA549250AM	10" ANSI flange ASME & CRN	740	38,897.00
NA549300AM	12" ANSI flange ASME & CRN	1,110	51,187.00
NA549350AM	14" ANSI flange ASME	1,550	60,346.00



In the SEP4™ hydraulic separators ferrous impurities are captured by a concentrated magnetic field created by a stack of neodymium magnetic rods, rare-earth magnets positioned inside a brass dry-well which is below the flow stream. Non-magnetic dirt particles are separated by colliding with an internal element in the flow stream and settling to the bottom. The deep collection chamber keeps the dirt from re-entering the flow stream. The dirt and ferrous impurities are flushed out even while the system is still running, by removing the magnets and opening the purge valve.

Size	1"	1¼"	1½"	2"
GPM	11	18	26	37
Gallons	0.5	0.7	1.3	3.5

Size	2"	2½"	3"	4"	5"	6"	8"	10"	12"	14"
GPM	60	80	124	247	300	484	792	1330	1850	2500
Gallons	4.0	4.0	8.0	8.0	23	23	95	175	255	450

HYDRAULIC SEPARATORS



548 Hydro Separator

Hydraulic separator.
Epoxy resin coated steel body.
300 series stainless steel internal baffle.
Includes mounting bracket.
Thermowell tap: 1/2" straight female
Max. working pressure: 150 psi.
Working temperature range: 32—212°F.

Code	Description	Lbs	USD
548006A	1" NPT female union	13	602.00
548066A	1" press union	13	645.00
548096A	1" sweat union	13	571.00
548007A	1¼" NPT female union	17	722.00
548067A	1¼" press union	17	821.00
548097A	1¼" sweat union	17	689.00
548008A	1½" NPT female union	25	947.00
548068A	1½" press union	25	1,066.00
548098A	1½" sweat union	25	901.00
548009A	2" NPT female union	27	1,103.00
548069A	2" press union	27	1,346.00
548099A	2" sweat union	27	1,053.00
548006US*	1" no tailpieces	11	453.00
548007US*	1¼" no tailpieces	14	510.00
548008US*	1½" no tailpieces	21	566.00
548009US*	2" no tailpieces	22	623.00

*See Separator fittings in Section 8.



NA548 Hydro Separator ASME

Hydraulic separator.
Without insulation.
Complete with:
automatic air vent (code 501502A).
shut-off valve (code NA39589).
drain valve (code NA59600).
ANSI 150 flange connections.
Thermometer pockets (NPT):
½" inlet/outlet flanges, ¾" front center.
Max. working pressure: 150 psi.
Working temperature range: 32—270°F.
Baffle plates for all sizes: 304SST
ASME U-stamp tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors; CRN registered through 12". Consult factory for 14".

Code	Description	Lbs	USD
NA548200A	8" ANSI flange ASME & CRN	530	19,248.00
NA548250A	10" ANSI flange ASME & CRN	740	27,169.00
NA548300A	12" ANSI flange ASME & CRN	1,110	32,885.00
NA548350A	14" ANSI flange ASME	1,550	52,443.00



NA548 Hydro Separator

Hydraulic separator.
Epoxy resin coated steel body.
Pre-formed insulation on 2" — 4" sizes.
Complete with:
automatic air vent (code 501502A).
shut-off valve (code NA39589).
drain valve (code NA39588).
ANSI 150 flange connections.
Max. working pressure: 150 psi.
Vessel temperature range: 32—220°F.
Vessel temp. w/o insulation: 32—270°F.
Baffle plates for all sizes: 304 SS

Code	Description	Lbs	USD
548052A	2" ANSI flange	75	3,868.00
548062A	2½" ANSI flange	82	4,118.00
548082A	3" ANSI flange	112	5,155.00
548102A	4" ANSI flange	117	5,768.00

Code	Description	Lbs	USD
NA548052A	2" ANSI flange ASME & CRN	75	5,088.00
NA548062A	2½" ANSI flange ASME & CRN	82	5,470.00
NA548082A	3" ANSI flange ASME & CRN	112	6,621.00
NA548102A	4" ANSI flange ASME & CRN	117	7,000.00
NA548120A*	5" ANSI flange ASME & CRN	220	10,222.00
NA548150A*	6" ANSI flange ASME & CRN	231	12,404.00

NA prefix indicates ASME U-stamp tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors; CRN registered.

*Without insulation



NA549 HydroCal™ ASME

Combination 1. air, 2. hydraulic and 3. dirt separation.
Epoxy resin coated steel body.
Stainless steel internal coalescing mesh.
Pre-formed insulation on 2" — 4" sizes.
Complete with: automatic air vent, air vent shut-off valve, drain valve.
ANSI 150 flange connections.
Max. working pressure: 150 psi.
Vessel temperature range: 32—220°F.
Working temp. w/o insulation: 32—270°F.
Particle separation capacity: to 5 µm (0.2 mil).
CRN registered through 12".
Consult factory for 14".

Code	Description	Lbs	USD
NA549052A	2" ANSI flange ASME & CRN	73	6,614.00
NA549062A	2½" ANSI flange ASME & CRN	79	7,114.00
NA549082A	3" ANSI flange ASME & CRN	108	8,603.00
NA549102A	4" ANSI flange ASME & CRN	117	9,097.00
NA549120A*	5" ANSI flange ASME & CRN	190	13,283.00
NA549150A*	6" ANSI flange ASME & CRN	231	16,116.00
NA549200A*	8" ANSI flange ASME & CRN	520	26,039.00
NA549250A*	10" ANSI flange ASME & CRN	730	36,225.00
NA549300A*	12" ANSI flange ASME & CRN	1,100	48,517.00
NA549350A*	14" ANSI flange ASME	1,540	57,676.00

*Without insulation

COMBINATION HYDRAULIC SEPARATOR AND MANIFOLD

5599 HydroLink™

Hydraulic separator + distribution manifold. 2+0 with built-in mounting. Steel body with pre-formed insulation. Complete with automatic air vent (code 502043A) and drain valve (code 538402 FD).
 Max. working pressure: 100 psi.
 Working temperature range: 32—230°F.
 Outlet center dimension: 125 mm.
 Compatible with 165, 166, 167 series HydroMixer™.



Code	Description	Lbs	USD
559920A	1" FNPT primary, 1" MNPT secondary (2)	16	809.00

5599 HydroLink™

Hydraulic separator + distribution manifold. 2+2 with angle mounting brackets. Steel body with pre-formed insulation. Complete with automatic air vent (code 502043A) and drain valve (code 538402 FD).
 Max. working pressure: 100 psi.
 Working temperature range: 32—230°F.
 Outlet center dimension: 125 mm.
 Compatible with 165, 166, 167 series HydroMixer™.



Code	Description	Lbs	USD
559922A	1/4" FNPT primary, 1" MNPT secondary (4)	29	994.00

5599 HydroLink™

Hydraulic separator + distribution manifold. 2+1 with built-in mounting. Steel body with pre-formed insulation. Complete with automatic air vent (code 502043A) and drain valve (code 538402 FD).
 Max. working pressure: 100 psi.
 Working temperature range: 32—230°F.
 Outlet center dimension: 125 mm.
 Compatible with 165, 166, 167 series HydroMixer™.




Code	Description	Lbs	USD
559921A	1" FNPT primary, 1" MNPT secondary (3)	16	833.00

5599 HydroLink™

Hydraulic separator + distribution manifold. 3+1 with angle mounting brackets. Steel body with pre-formed insulation. Complete with automatic air vent (code 502043A) and drain valve (code 538402 FD).
 Max. working pressure: 100 psi.
 Working temperature range: 32—230°F.
 Outlet center dimension: 125 mm.
 Compatible with 165, 166, 167 series HydroMixer™.




Code	Description	Lbs	USD
559931A	1/4" FNPT primary, 1" MNPT secondary (4)	39	1,194.00



Maximum recommended flow rates at connections:

Branches	Primary	Secondary Total
2+0	9 gpm	22 gpm
2+1	9 gpm	22 gpm
2+2	11 gpm	26 gpm
3+1	11 gpm	26 gpm



HYDRAULIC SEPARATOR ACCESSORIES



**501
MAXCAL™**

Replacement air vent for Hydro Separator. Fits NA548 Series and NA549 Series. Max. working pressure: 230 psi. Max. discharge pressure: 90 psi. Max. working temperature: 250°F. Discharge top thread: 3/8" female.

Code	Description	Lbs	USD
501502A	3/4" FNPT	7.0	315.00



**5020
MINICAL™**

Replacement high capacity air vent for 5599 HydroLink™. Max. working pressure: 150 psi. Max discharge pressure: 32 psi. Max. working temperature: 250°F.

Code	Description	Lbs	USD
502043A	1/2" MNPT	0.6	23.80



**5023
VALCAL™**

Replacement high capacity air vent with service check valve fits Hydro Separator 548 series. Max. working pressure: 150 psi. Max. discharge pressure: 60 psi. Max. working temperature: 250°F.

Code	Description	Lbs	USD
502343A	1/2" MNPT	0.5	48.20



Support bracket for SEP4 and Hydro Separator.

Code	Description	Lbs	USD
NA10778	for 1" and 1 1/4" union	2.0	27.90
NA10796	for 1-1/2" union	2.5	29.10
NA10797	for 2" union	4.0	30.30



Replacement drain valve fits Hydro Separator 548 series and HydroLink™ 559 series. 3/4" garden hose thread with cap. Max. working pressure: 150 psi. Max. working temperature: 250°F.

Code	Description	Lbs	USD
538402 FD	1/2" NPT x 3/4" GHT	0.3	15.10



Drain ball valves fit HydroCal™, Hydro Separators, DISCAL®, DISCALDIRT® and DIRTICAL®. Brass body. Max. working pressure: 150 psi. Max. working temperature: 365°F.

Code	Description	Lbs	USD
NA39589	3/4" FNPT w/T-handle, air vent isolate	0.8	31.30
NA39753	1" FNPT w/Lever, drain	0.7	42.60
NA39588	1 1/4" FNPT w/Lever, drain	1.0	71.70
NA59600	2" FNPT w/Lever, drain	4.0	151.00



Temperature pocket well fits 1", 1 1/4", 1 1/2" & 2" 548 / 5495 Hydro Separators. 1 3/4" pocket length. Inside thread: 20 x1.0 mm.

Code	Description	Lbs	USD
694045	1/2" straight thread	0.2	19.20
R20011	Sealing washer	0.1	1.60
NA10426	Sensor holding grommet	0.1	4.40
NA10425	Kit containing above 3 items	0.4	25.70



Magnetic/drywell assembly for SEP4™.

Code	Description	Lbs	USD
F0000435	Fits 2" and 2 1/2"	0.3	137.00
49684A	Fits 3" — 6"	0.3	309.00
F0000349	Fits 8" to 14"	0.3	583.00



Insulation jacket kit for SEP4 and Hydro Separator.

Code	Description	Lbs	USD
NA10801	for 1" union 5495	0.5	48.50
NA10802	for 1 1/4" union 5495	0.5	53.30
NA10803	for 1 1/2" union 5495	0.6	72.80
NA10804	for 2" union 5495	0.6	82.40
NA10805	for 1" union 548	0.5	31.50
NA10806	for 1 1/4" union 548	0.5	36.40
NA10807	for 1 1/2" union 548	0.6	44.90
NA10808	for 2" union 548	0.6	52.20

THE GOLD STANDARD FOR HEALTHY HYDRONIC SYSTEM FLUIDS



The **DISCAL**® air separator and **DIRTMAG PRO**® dirt separator duo ensures maximum protection and efficiency in hydronic systems. The DISCAL high efficiency air separator features a large, low-flow zone, coalescing element and automatic air vent to minimize corrosion formation. The DIRTMAG's magnetic technology and particle mesh removes both ferrous and non-ferrous debris helping to keep expensive heat exchangers and ECM circulators running smoothly. **CALEFFI GUARANTEED.**



AUTOMATIC AND MANUAL AIR VENTS



5026 ROBOCAL™

Automatic air vent.
Brass body.
Max. working pressure: 150 psi.
Max. discharge pressure: 90 psi.

Code	Description	Lbs	USD
502610A	1/8" MNPT	0.6	15.00
502620A	1/4" MNPT	0.6	15.90
502420	1/4" straight thread	NEW 1.0	21.00
502630	3/8" straight thread	1.0	21.00
502640	1/2" straight thread	1.0	22.70



5027 ROBOCAL™

Automatic air vent with service check valve.
Brass body.
Max. working pressure: 150 psi.
Max. discharge pressure: 90 psi.

Code	Description	Lbs	USD
502710A	1/8" MNPT	0.6	20.90
502720A	1/4" MNPT	0.6	22.10



NA5027 ROBOCAL™

Automatic air vent with service check valve.
Brass body.
Max. working pressure: 150 psi.
Max. discharge pressure: 90 psi.



Code	Description	Lbs	USD
NA502740A	1/2" MNPT, hygroscopic anti-drip cap	0.6	28.70

MINICAL™ and VALCAL™

These float type automatic air vents are designed to vent released air from the water while being heated. They are used on manifolds or pipes in sealed heating systems.


MINICAL is a standard size air vent that will discharge up to 1.75 SCFM.

VALCAL is a high capacity larger size air vent that will discharge up to 2.5 SCFM.



Some MINICAL and VALCAL models are equipped with a hygroscopic safety cap. Cellulose fiber discs in the cap serve as a redundant seal. Their volume increases by 50% when wet, sealing the discharge vent.

Some MINICAL and VALCAL models are equipped with a service check valve which facilitates maintenance operations by shutting off the water flow when the air vent is removed and also allows an easy replacement of the air vent without purging the system.



5020 MINICAL™

Automatic air vent.
Brass body.
Max. working pressure: 150 psi.
Max. discharge pressure: 32 psi.
Max. discharge rate: 1.75 SCFM.
Max. working temperature: 250°F.

Code	Description	Lbs	USD
502015A	1/8" MNPT	0.4	16.90
502040A	1/2" MNPT	0.4	16.90



5021 MINICAL™

Automatic air vent with service check valve.
Brass body.
Max. working pressure: 150 psi.
Max. discharge pressure: 32 psi.
Max. discharge rate: 1.75 SCFM.
Max. working temperature: 230°F.

Code	Description	Lbs	USD
502115A	1/8" MNPT	0.4	22.70
502113A	1/8" MNPT, hygroscopic anti-drip cap	0.4	26.10



5020 MINICAL™

Automatic air vent.
Brass body.
Hygroscopic safety air vent cap.
Max. working pressure: 150 psi.
Max discharge pressure: 32 psi.
Max. discharge rate: 1.75 SCFM.
Max. working temperature: 250°F.

Code	Description	Lbs	USD
502043A	1/2" MNPT	0.6	23.80



5022 VALCAL™

High discharge automatic air vent.
Hygroscopic safety air vent cap.
Max. working pressure: 150 psi.
Max. discharge pressure: 60 psi.
Max. discharge rate: 2.5 SCFM.
Max. working temperature: 250°F.

Code	Description	Lbs	USD
502243A	1/2" MNPT	0.5	40.70



5023 VALCAL™


High discharge vent with service check.
Hygroscopic safety air vent cap.
Max. working pressure: 150 psi.
Max. discharge pressure: 60 psi.
Max. discharge rate: 2.5 SCFM.
Max. working temperature: 230°F.

Code	Description	Lbs	USD
502343A	1/2" MNPT	0.5	48.20

AUTOMATIC AND MANUAL AIR VENTS

MAXCAL™

Extra high capacity air vent is ideal for use in large piping systems and can also be installed in horizontal piping. The valve body and cover are made of forged brass while the filter, valve stem, float, and spring are all made of stainless steel to prevent the formation of rust.



**501
MAXCAL™**

Automatic air vent for heating and air conditioning. Brass body and cover, stainless steel internal components. Extra high discharge capacity. Max. working pressure: 230 psi. Max. discharge pressure: 90 psi. Max. discharge rate: 9 SCFM. Working temperature range: -4 – 250°F. Discharge top thread: 3/8" female.

Code	Description	Lbs	USD
501502A	3/4" FNPT	7	315.00

**551
DISCALAIR®**


High discharge automatic air vent. Brass body. Stainless steel float guide pin and linkage. Max. working pressure: 150 psi. Max. discharge pressure: 150 psi. Max. discharge rate: 4.5 SCFM. Max. working temperature: 230°F.



Code	Description	Lbs	USD
551004A	1/2" FNPT and 3/4" MNPT	0.8	97.40

Function

DISCALAIR® automatic air vents release air that forms in the hydraulic circuits of heating and air conditioning systems with pressures to 150 psi. The venting air discharge capacity is capable of expelling over 4 standard cubic feet per minute (SCFM). The circulation of fully de-aerated water or glycol-water mediums enables the equipment to operate under optimum conditions, free from noise, corrosion, localized overheating, or mechanical damage.




**5080
HYGROCAL™**

Automatic hygroscopic air vent for hydronic heating system and low pressure steam. Manual operation by rotating knob. Chrome plated brass body. Max. working pressure: 150 psi. Max. working temperature: 212°F. Low pressure steam: 15 psi. **(Priced each, sold in quantities of 25)**

Code	Description	Lbs	USD
508013A	1/8" MNPT	0.1	8.10

Automatic radiator air vent valve is designed to remove any air trapped inside the heat emitters both during the filling of the system and in normal operation. The automatic air discharge happens when the hygroscopic cellulose fiber discs are dry. As air is vented and water contacts the hygroscopic discs, they increase their volume by 50% which causes the discharge vent to close.



5081

Replacement hygroscopic cartridge fits hygroscopic air vent 5080 series. **(Priced each, sold in quantities of 25)**



Code	Description	Lbs	USD
508100A	Cartridge	0.1	7.10

337

Manual air vent with metal seal and adjustable outlet. Brass body. Max. working pressure: 150 psi. Max. working temperature: 212°F.



Code	Description	Lbs	USD
337221A	1/4" MNPT	0.1	10.20



Service check valve for removal of air vent or expansion tank without purging system. Fits automatic air vents 502 series. Max. working pressure: 150 psi. Max. working temperature: 230°F.

Code	Description	Lbs	USD
59474A	1/8" MNPT x FNPT	0.1	12.40
59804A	1/4" MNPT x FNPT	0.1	13.10
561402A	1/2" MNPT x FNPT	0.2	15.10

AIR SEPARATORS



551 DISCAL®

Air separator.
Brass body.
Stainless steel float guide pin and linkage.
Glass reinforced nylon internal element.
1/2" NPT female bottom thread.
Max. working pressure: 150 psi.
Working temperature range: 32—250°F.

Code	Description	Lbs	USD
551005A	3/4" FNPT	3.7	209.00
551028A	1" sweat	3.7	215.00
551006A	1" FNPT	3.7	226.00
551066A	1" integral press	3.8	257.00
551035A	1 1/4" sweat	3.7	313.00
551007A	1 1/4" FNPT	4.9	330.00
551067A	1 1/4" integral press	5.0	395.00
551041A	1 1/2" sweat	4.9	407.00
551008A	1 1/2" FNPT	4.9	428.00
551068A	1 1/2" integral press	5.1	510.00
551054A	2" sweat	5.5	499.00
551009A	2" FNPT	5.5	523.00
551069A	2" integral press	5.5	624.00



551 DISCAL® Service check

Air separator with 1/2" service check valve (code 561402A) to mount expansion tank on bottom thread.
Brass body.
Stainless steel float guide pin and linkage.
Glass reinforced nylon internal element.
Max. working pressure: 150 psi.
Working temperature range: 32—250°F.

Code	Description	Lbs	USD
551005AC	3/4" FNPT	3.8	218.00
551028AC	1" sweat	3.8	223.00
551006AC	1" FNPT	3.8	234.00
551066AC	1" integral press	3.9	264.00
551035AC	1 1/4" sweat	3.8	321.00
551007AC	1 1/4" FNPT	5.0	336.00
551067AC	1 1/4" integral press	5.1	404.00
551041AC	1 1/2" sweat	5.0	417.00
551008AC	1 1/2" FNPT	5.0	437.00
551068AC	1 1/2" integral press	5.2	519.00
551054AC	2" sweat	5.6	506.00
551009AC	2" FNPT	5.6	531.00
551069AC	2" integral press	5.6	632.00

ACCESSORIES



Insulation shell fits DISCAL® 551 series.

Code	Description	Lbs	USD
CBN551005	Fits 3/4" and 1" 551 series	0.1	57.40
CBN551007	Fits 1 1/4" and 1 1/2" 551 series	0.1	61.50
CBN551009	Fits 2" 551 series	0.1	67.30


*Will not fit the 3/4" compact DISCAL®; codes 551003A and 551022A.



Service check valve for easy replacement of expansion tank when connected to bottom of DISCAL®.

Code	Description	Lbs	USD
561402A	1/2" MNPT x 1/2" FNPT	0.2	15.10

Size	MAXIMUM FLOW RATE				
	3/4"	1"	1 1/4"	1 1/2"	2"
GPM	6	10	15	22	39
Cv	19	32	56	73	81



AIR SEPARATORS

5517 DISCAL® Rotating collar



Air separator with rotating collar for horizontal or vertical pipes.
 Brass body.
 Stainless steel float guide pin and linkage.
 Stainless steel mesh internal element.
 Max. working pressure: 150 psi.
 Working temperature range: 32–250°F.

551 DISCAL® Compact




Air separator.
 Brass body.
 Stainless steel float guide pin and linkage.
 Stainless steel mesh internal element.
 ½" NPT bottom thread.
 Max. working pressure: 150 psi.
 Working temperature range: 32–250°F.

Code	Description	Lbs	USD
551705A	¾" NPT male union	4.9	266.00
551765A	¾" press union	4.9	280.00
551795A	¾" sweat union	4.9	263.00
551706A	1" NPT male union	4.9	284.00
551766A	1" press union	4.9	313.00
551796A	1" sweat union	4.9	279.00
551716*	body only, order unions separately	4.4	243.00


*See fitting selection table in Section 8.

Code	Description	Lbs	USD
551003A	¾" FNPT	2.0	140.00
551003AC	¾" FNPT, service check valve	2.1	147.00
551022A	¾" sweat	2.0	135.00
551022AC	¾" sweat, service check valve	2.1	143.00

Construction details DISCAL® Compact



Construction details DISCAL® Rotating collar



	MAXIMUM FLOW RATE		
Size	¾" compact	¾" vertical	1" vertical
GPM	6	6	10
Cv	12	19	19

Air separation efficiency

DISCAL® air separators continuously remove entrained air in hydronic systems with high separation efficiency. The amount of air removed from a system varies depending on fluid velocity and temperature. As illustrated on the graph, at the 4.0 feet per second fluid velocity, all the air artificially introduced into the system is gradually eliminated during normal system operation by the DISCAL air separator. In conditions where the fluid velocity is slower or the temperature of the fluid is higher, the amount of air separated is even faster.

AIR SEPARATORS



551 DISCAL®


Air separator.
Epoxy resin coated steel body.
Stainless steel float guide pin and linkage.
Stainless steel mesh internal element.
ANSI 150 flange connections.
1" NPT male bottom drain connection.
Complete with male bottom drain valve (NA39753).
½" NPT male side drain connection.
Complete with side drain valve (538402FD).
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.

Code	Description	Lbs	USD
551050A	2" ANSI flange	34	3,009.00
551050AT	2" MNPT	30	2,861.00
551060A	2½" ANSI flange	35	3,215.00
551060AT	2½" MNPT	31	3,069.00
551080A	3" ANSI flange	62	4,257.00
551100A	4" ANSI flange	67	4,762.00
551150A	6" ANSI flange	117	9,338.00

Air separator construction

DISCAL® air separators are constructed to allow maintenance and cleaning operations to be carried out without having to remove the separator body from the pipe work. All DISCAL air separators have a bottom connection drain valve. All internal air release control components are fully accessible. The automatic air release valve, located at the top of the separator, has a long chamber for the movement of the float. This feature prevents any debris present in the water from reaching the sealing seat.

Flanged models include a side drain vent to release large amounts of air when filling the system and to remove any debris present above the water level.



MAXIMUM FLOW RATE

Size	2"	2½"	3"	4"	5"	6"	8"	10"	12"
GPM	100	155	220	400	615	880	1,570	2,450	3,525
Cv	87	174	208	324	520	832	1,109	1,387	1,664



NA551 DISCAL® ASME/CRN

Air separator.
Epoxy resin coated steel body.
Stainless steel float guide pin and linkage.
Stainless steel mesh internal element.
ANSI 150 flange connections.
1" NPT male bottom drain connection.
Complete with drain valve (NA39753).
½" NPT male side drain connection.
Complete with side drain valve (538402FD).
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
ASME and CRN registered.

Code	Description	Lbs	USD
NA551050A	2" ANSI flange ASME & CRN	34	3,769.00
NA551060A	2½" ANSI flange ASME & CRN	35	4,029.00
NA551080A	3" ANSI flange ASME & CRN	62	5,333.00
NA551100A	4" ANSI flange ASME & CRN	67	5,968.00
NA551120A	5" ANSI flange ASME & CRN	106	6,864.00
NA551150A	6" ANSI flange ASME & CRN	117	11,189.00

NA prefix indicates ASME tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors; CRN registered.

NA551 DISCAL® ASME



Air separator.
Epoxy resin coated steel body.
Stainless steel float guide pin and linkage.
Stainless steel mesh internal element.
ANSI 150 flange connections.
2" NPT male bottom drain connection.
Complete with drain valve (NA59600).
½" NPT male side drain connection.
Complete with side drain valve (538402FD).
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
ASME and CRN registered.

Code	Description	Lbs	USD
NA551200A	8" ANSI flange ASME & CRN	371	18,311.00
NA551250A	10" ANSI flange ASME & CRN	617	27,462.00
NA551300A	12" ANSI flange ASME & CRN	871	35,703.00

NA prefix indicates ASME tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors; CRN registered.



Replacement drain ball valve.
Fits DISCAL® series.
Brass body.
Lever.
Max. working pressure: 150 psi.
Max. working temperature: 365°F.

Code	Description	Lbs	USD
NA39753	1" FNPT with lever	0.7	42.60
NA59600	2" FNPT with lever	3.5	151.00

DIRT SEPARATORS

The dirt separating action performed by the DIRTCAL® is based on using the internal element with concentric diamond pattern mesh surfaces instead of a mechanical filter. The element offers little resistance to the medium flow while ensuring dirt separation. This occurs due to the particles colliding with the concentric diamond pattern mesh surfaces and then settling to the bottom, and not by filtration; which, over time, gets continuously clogged. By contrast, the DIRTCAL low-velocity zone dirt separator efficiently removes the particles to as small as 5 µm (0.2 mil). The dirt collection chamber at the bottom of the DIRTCAL is at the optimal distance from the inlet and outlet connections to ensure that the collected dirt particles are not affected by the swirling flow through the mesh element. The dirt can then be removed through the bottom drain port even with the system running, by opening the drain valve. Low head losses and performance are maintained over time.




5465 DIRTCAL®

Dirt separator.
Epoxy resin coated steel body.
1" threaded NPT bottom drain connection
Complete with drain valve (code NA39753).
¾" NPT male top thread with brass cap.
ANSI 150 flange connections.
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
Particle separation capacity: to 5 µm (0.2 mil).

Code	Description	Lbs	USD
546550A	2" ANSI flange	29	1,931.00
546510A	4" ANSI flange	54	2,874.00

Dirt separation comparison



NA5465 DIRTCAL® ASME/CRN

Dirt separator.
Epoxy resin coated steel body.
1" threaded NPT bottom drain connection
Complete with drain valve (code NA39753).
¾" NPT male top thread with brass cap.
ANSI 150 flange connections.
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
Particle separation capacity: to 5 µm (0.2 mil).
ASME and CRN registered.

Code	Description	Lbs	USD
NA546550A	2" ANSI flange ASME & CRN	38	3,095.00
NA546560A	2½" ANSI flange ASME & CRN	38	3,290.00
NA546580A	3" ANSI flange ASME & CRN	55	4,283.00
NA546510A	4" ANSI flange ASME & CRN	55	4,689.00
NA546512A	5" ANSI flange ASME & CRN	138	7,066.00
NA546515A	6" ANSI flange ASME & CRN	148	9,065.00

ASME U-stamp tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors CRN registered.



NA5465 DIRTCAL® ASME/CRN

Dirt separator.
Epoxy resin coated steel body.
2" threaded NPT bottom drain connection.
Complete with drain valve (code NA59600).
¾" NPT male top thread with brass cap.
ANSI 150 flange connections.
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
Particle separation capacity: to 5 µm (0.2 mil).
ASME registered. CRN registered thru 12".
Consult factory for 14".

Code	Description	Lbs	USD
NA546520A	8" ANSI flange ASME & CRN	335	18,533.00
NA546525A	10" ANSI flange ASME & CRN	620	28,571.00
NA546530A	12" ANSI flange ASME & CRN	870	35,386.00
NA546535A	14" ANSI flange ASME	1,000	44,488.00

ASME U-stamp tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors. CRN registered 8", 10", 12". Consult factory for 14" status.

MAXIMUM FLOW RATE						
Size	2"	2½"	3"	4"	5"	6"
GPM	89	150	227	355	816	904
Cv	88	176	211	328	520	842

MAXIMUM FLOW RATE				
Size	8"	10"	12"	14"
GPM	1,570	2,450	3,525	4,800
Cv	1,055	1,400	1,755	2,075

AIR AND DIRT SEPARATORS



5461 DISCALDIRTMAG™

Air & Dirt separator with magnet.
 Brass body.
 Stainless steel float guide pin and linkage.
 Glass reinforced nylon internal element.
 Max. working pressure: 150 psi.
 Working temperature range: 32—250°F.
 Particle separation capacity: to 5 µm (0.2 mil).
 Ferrous impurities separation efficiency: 100%.

Code	Description	Lbs	USD
546196A	1" sweat	8.5	445.00
546166A	1" press	8.5	477.00
546116A	1" MNPT	8.5	465.00
546197A	1¼" sweat	8.5	531.00
546167A	1¼" press	8.5	601.00



5461 DISCALDIRTMAG™

Air & Dirt separator with magnet.
 Epoxy resin coated steel body.
 Stainless steel float guide pin and linkage.
 Stainless steel mesh internal element.
 Complete with union connections.
 Max. working pressure: 150 psi.
 Working temperature range: 32 — 230°F
 Particle separation capacity: to 5 µm (0.2 mil).
 Ferrous impurities separation efficiency: 100%.

Code	Description	Lbs	USD
546198A	1½" sweat union	22	1,376.00
546108A	1½" NPT female union	22	1,419.00
546168A	1½" press union	22	1,572.00
546199A	2" sweat union	23	1,443.00
546109A	2" NPT female union	23	1,497.00
546169A	2" press union	23	1,754.00

The **DISCALDIRTMAG™** air and dirt separator with magnet uses a patented external magnet ring for separation of ferrous impurities. The impurities are retained in the body of the dirt separator by the strong magnetic field created. The outer ring is removable from the body to allow the flushing of sludge.



546 DISCALDIRT®

Air & Dirt separator.
 Epoxy resin coated steel body.
 Stainless steel float guide pin and linkage.
 Stainless steel mesh internal element.
 1" NPT threaded bottom drain connection.
 Complete with side drain valve (538402 FD).
 ANSI 150 flange connections.
 Complete with drain valve (NA39753)
 Max. working pressure: 150 psi.
 Vessel temperature range: 32—270°F.
 Particle separation capacity: to 5 µm (0.2 mil).

Code	Description	Lbs	USD
546050A	2" ANSI flange	40	3,821.00
546060A	2½" ANSI flange	42	4,027.00
546080A	3" ANSI flange	73	5,187.00
546100A	4" ANSI flange	78	5,685.00
546120A	5" ANSI flange	181	8,573.00



546 DISCALDIRT®

Air & Dirt separator.
 Brass body.
 Stainless steel float guide pin and linkage.
 Glass reinforced nylon internal element.
 Max. working pressure: 150 psi.
 Working temperature range: 32 — 250°F.
 Particle separation capacity: to 5 µm (0.2 mil).

Code	Description	Lbs	USD
546096A	1" sweat	8.3	362.00
546016A	1" MNPT	8.3	380.00
546097A	1¼" sweat	8.3	432.00



Insulation shell for DISCALDIRT® & DISCALDIRTMAG™.

Code	Description	Lbs	USD
CBN546002	Fits 1", 1¼" brass 546 only	0.1	90.00
CBN546118	Fits 1½" steel 5461 only	0.1	113.00
CBN546119	Fits 2" steel 5461 only	0.1	129.00

MAXIMUM FLOW RATE				
Size	1"	1¼"	1½"	2"
GPM	10	15	22	39
Cv	32	40	50	79

AIR AND DIRT SEPARATORS

NA546
DISCALDIRT®
ASME/CRN



Air & Dirt separator.
Epoxy resin coated steel body.
Stainless steel float guide pin and linkage.
Stainless steel mesh internal element.
1" (2–6" sizes) and 2" (8–14" sizes)
threaded NPT bottom drain connection.
ANSI 150 flange connections.
Complete with drain valve NA39753
(2–6" sizes), NA59600 (8–14" sizes).
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
ASME registered. CRN registered thru 12".
Consult factory for 14".

NA546M
DISCALDIRTMAG™
ASME/CRN




Air & Dirt separator with magnets.
Epoxy resin coated steel body.
Stainless steel float guide pin and linkage.
Stainless steel mesh internal element.
ANSI 150 flange connections.
1" (2–6" sizes) and 2" (8–14" sizes)
threaded NPT bottom drain connection.
Complete with drain valve NA39753
(2–6" sizes), NA59600 (8–14" sizes).
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
Particle separation capacity: to 5 µm (0.2 mil).
Ferrous impurities separation efficiency: up
to 100%.
ASME registered. CRN registered thru 12".
Consult factory for 14".

Code	Description	Lbs	USD
NA546050T	2" Threaded ASME & CRN	28	3,659.00
NA546060A	2½" ANSI flange ASME & CRN	42	4,921.00
NA546080A	3" ANSI flange ASME & CRN	73	6,337.00
NA546100A	4" ANSI flange ASME & CRN	78	6,949.00
NA546120A	5" ANSI flange ASME & CRN	181	10,023.00
NA546150A	6" ANSI flange ASME & CRN	188	12,783.00
NA546200A	8" ANSI flange ASME & CRN	355	23,746.00
NA546250A	10" ANSI flange ASME & CRN	555	36,510.00
NA546300A	12" ANSI flange ASME & CRN	825	45,654.00
NA546350A	14" ANSI flange ASME	950	57,729.00

ASME U-stamp tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors; CRN registered, 2" – 12"; consult factory for 14".

Low head losses and high performance are maintained over time. The dirt separating action performed by the DISCALDIRT® air and dirt separator is based on using the internal element with concentric diamond pattern mesh surfaces instead of an ordinary filter. The element offers little resistance to the medium flow while ensuring dirt separation.



Code	Description	Lbs	USD
NA546050TM*	2" Threaded ASME & CRN	31	4,228.00
NA546060AM*	2½" ANSI flange ASME & CRN	45	5,528.00
NA546080AM*	3" ANSI flange ASME & CRN	76	7,193.00
NA546100AM*	4" ANSI flange ASME & CRN	81	7,821.00
NA546120AM*	5" ANSI flange ASME & CRN	184	11,486.00
NA546150AM*	6" ANSI flange ASME & CRN	191	13,860.00
NA546200AM**	8" ANSI flange ASME & CRN	365	27,191.00
NA546250AM**	10" ANSI flange ASME & CRN	565	39,260.00
NA546300AM**	12" ANSI flange ASME & CRN	835	49,748.00
NA546350AM**	14" ANSI flange ASME	960	62,176.00

*With one magnet

**With three magnets

ASME U-stamp tagged and registered with the National Board of Boiler and Pressure Vessel Inspectors. CRN registered, 2" – 12"; consult factory for 14".



In the DISCALDIRTMAG™ air and dirt separator with magnets, ferrous impurities are captured by a concentrated magnetic field created by a stack of neodymium rare-earth magnets positioned inside a brass dry-well which is below the flow stream. Non-magnetic dirt particles are separated by colliding with an internal element in the flow stream and settling to the bottom. The deep collection chamber keeps the dirt from re-entering the flow stream. The dirt and ferrous impurities are flushed out while the system is operating, by removing the magnets and opening the purge valve.

Size	MAXIMUM FLOW RATE									
	2"	2½"	3"	4"	5"	6"	8"	10"	12"	14"
GPM	100	155	220	400	615	880	1,570	2,450	3,525	4,800
Cv	87	174	208	324	520	832	1,109	1,387	1,664	1,967

MAGNETIC DIRT SEPARATORS



**5463M
DIRTMAG PRO®**


Dirt separator with dual magnetic fields.
Internal magnet in drywell.
External clip-on magnet.
Brass body.
Max. working pressure: 150 psi.
Working temperature range: 32-250°F.
Particle separation capacity: to 5um (0.2 mil).
Ferrous impurities separation efficiency: 100%.



Code	Description	Lbs	USD
546328AM	1" sweat	4.7	266.00
546306AM	1" FNPT	4.7	279.00
546366AM	1" press	5.0	303.00
546335AM	1¼" sweat	4.7	387.00
546307AM	1¼" FNPT	5.8	406.00
546367AM	1¼" press	6.1	464.00
546341AM	1½" sweat	5.4	505.00
546308AM	1½" FNPT	6.7	531.00
546368AM	1½" press	7.0	605.00
546354AM	2" sweat	6.0	615.00
546309AM	2" FNPT	6.7	638.00
546369AM	2" press	7.0	738.00


Construction design

The DIRTMAG® PRO incorporates patented technology and features dual magnetic fields that increase ferrous debris removal efficiency by 40%. The concentric pattern collision media inside the low-velocity zone efficiently separates non-ferrous debris. All debris is quickly purged from system via the blow down valve. No disassembly or scraping of magnetite from wetted magnets is required, which means clean hands, fast, and easy servicing.




Double the protection

Captures two forms of debris that can damage or shorten the life of heat exchangers, circulators and valves: ferrous debris such as magnetite, and non-ferrous debris such as copper shavings, solder, lime-scale fragments, silica and pipe compound. Two powerful neodymium rare-earth magnetic fields attract and capture ferrous oxide impurities and allow simple blowdown - no disassembly required.



Fast and easy clean hands purging:

Stop circulation, pull out the magnetic pull rod from drywell on top, unclip the external barrel magnetic collar and open the purge valve to simply release the captured magnetic impurities and purge all dirt.



Size	MAXIMUM FLOW RATE			
	1"	1¼"	1½"	2"
GPM	14	21	31	54
Cv	32	45	69	104

MAGNETIC DIRT SEPARATORS



Insulation shell fits DIRTMAG® 5463 series. Labels included for field installation to externally identify product use.



Replacement drain valve fits DIRTMAG® 5463 series, DISCALDIRT® 546 series and DISCALDIRTMAG™ 5461 series. Brass body. Max. working pressure: 150 psi. Max. working temperature: 250°F.

Code	Description	Lbs	USD
CBN546205	Fits ¾" & 1" DIRTMAG®	0.1	54.60
CBN546207	Fits 1¼" & 1½" DIRTMAG®	0.1	58.80
CBN546209	Fits 2" DIRTMAG®	0.1	64.10

Code	Description	Lbs	USD
538402 FD	½" MNPT x ¾" GHT	0.3	15.10



NA5453 DIRTMAG®

Dirt separator with magnet. Brass mounting housing. Composite PA66G30 body. Max. working pressure: 45 psi. Working temperature range: 32—195°F. Particle separation capacity: to 5 µm (0.2 mil). Ferrous impurities separation efficiency: 100%. Drain valve with hose connection. Top dosing point port. Dosing capacity: 12 fluid oz. Manual screw air vent.

Construction design

The dirt separator with magnet combines the action of the internal element and magnet. The impurities in the water strike the internal element and are separated, dropping into the bottom of the body where they are collected. Ferrous impurities are also trapped inside the dirt separator body by two strong magnets contained within the removable outer ring collar. The collected impurities are discharged by removing the external ring magnet and opening the drain valve.

Code	Description	Lbs	USD
NA545305	¾" NPT male union	4.5	208.00
NA545365	¾" press union	4.5	226.00
NA545395	¾" sweat union	4.5	207.00
NA545306	1" NPT male union	4.5	240.00
NA545366	1" press union	4.7	270.00
NA545396	1" sweat union	4.5	229.00
NA545355	¾" NPT female union, isolation valves	5.5	250.00
NA545356	1" NPT female union, isolation valves	5.5	291.00
NA545376	1" press union, isolation valves	5.5	397.00



The special coupling between the locking nut and the mounting base allows the DIRTMAG® dirt separator to be rotated for installation to either vertical or horizontal pipes, while maintaining the same operating performance.

MAXIMUM FLOW RATE		
Size	¾"	1"
GPM	10	10
Cv w/ ball valve	9	9
Cv w/o ball valve	12	12

MAGNETIC DIRT SEPARATORS

Ferrous and non-ferrous impurities in hydronic systems can deposit onto heat exchanger surfaces and accumulate in pump cavities causing reduced thermal efficiency and premature wear. The small and often microscopic magnetic particles, called magnetite, form when iron or steel corrodes. Highly abrasive, the extremely fine particles are difficult to remove by traditional means. DIRTMAG® separators offer highly efficient separation of typical dirt as well as magnetite. The magnetite is captured by a concentrated magnetic field created by a stack of neodymium rare-earth magnets positioned inside a brass dry-well which is below the flow stream. Non-magnetic dirt particles are separated by colliding with an internal element in the flow stream, settling to the bottom. The deep collection chamber keeps the dirt from re-entering the flow stream.



To purge the debris, the flexible magnetic stack is removed from the brass dry-well and, even while the system is still running, the drain valve is opened. Aided by the system pressure, the dirt and magnetite flushes out quickly and effectively. DIRTMAG magnetic dirt separators accomplish 2½ times the ferrous impurities removal performance of standard dirt separators, delivering up to 100% elimination efficiency.



MAXIMUM FLOW RATE						
Size	2"	2½"	3"	4"	5"	6"
GPM	89	150	227	355	816	904
Cv	88	176	211	328	520	842

MAXIMUM FLOW RATE				
Size	8"	10"	12"	14"
GPM	1,570	2,450	3,525	4,800
Cv	1,055	1,400	1,755	2,075



5465M DIRTMAG®

Magnetic dirt separator with one magnet assembly.
Epoxy resin coated steel body.
Complete with drain valve (code NA39753).
¼" NPT male top thread with brass cap.
ANSI 150 flange connections.
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
Particle separation capacity: to 5 µm (0.2 mil).
Ferrous impurities separation efficiency: 100%.

Code	Description	Lbs	USD
546550AM	2" ANSI flange	41	2,492.00
546560AM	2½" ANSI flange	41	2,683.00
546580AM	3" ANSI flange	58	3,627.00
546510AM	4" ANSI flange	58	4,012.00



NA5465M DIRTMAG® ASME/CRN

Magnetic dirt separator with one magnet assembly.
Epoxy resin coated steel body.
Complete with drain valve (code NA39753).
¼" NPT male top thread with brass cap.
ANSI 150 flange connections.
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
Particle separation capacity: to 5 µm (0.2 mil).
Ferrous impurities separation efficiency: 100%.
ASME and CRN registered.

Code	Description	Lbs	USD
NA546550AM	2" ANSI flange ASME & CRN	41	3,534.00
NA546560AM	2½" ANSI flange ASME & CRN	41	3,731.00
NA546580AM	3" ANSI flange ASME & CRN	58	4,921.00
NA546510AM	4" ANSI flange ASME & CRN	58	5,327.00
NA546512AM	5" ANSI flange ASME & CRN	141	7,733.00
NA546515AM	6" ANSI flange ASME & CRN	151	9,732.00



NA5465M DIRTMAG® ASME/CRN

Magnetic dirt separator with three magnets assembly.
Epoxy resin coated steel body.
Complete with drain valve (code NA59600).
¼" NPT male top thread with brass cap.
ANSI 150 flange connections.
Max. working pressure: 150 psi.
Vessel temperature range: 32–270°F.
Particle separation capacity: to 5 µm (0.2 mil).
Ferrous impurities separation efficiency: 100%.
ASME registered. CRN registered thru 12".
Consult factory for 14".

Code	Description	Lbs	USD
NA546520AM	8" ANSI flange ASME & CRN	345	21,152.00
NA546525AM	10" ANSI flange ASME & CRN	630	31,188.00
NA546530AM	12" ANSI flange ASME & CRN	880	38,003.00
NA546535AM	14" ANSI flange ASME	1,010	47,106.00

ACCESSORIES FOR AIR AND DIRT SEPARATORS



Hygroscopic air vent cap fits DISCAL 551, and DISCALDIRT® 546 series, and MINICAL™ 502 series.

Code	Description	Lbs	USD
R59681	Vent cap	0.1	18.80



Anti-suction air vent cap fits DISCAL® 551, DISCALDIRT 546 series and MINICAL™ 502 series.

Code	Description	Lbs	USD
562100	Vent cap	0.1	19.70



Replacement air vent cap fits DISCAL 551 and DISCALDIRT 546 series.

Code	Description	Lbs	USD
R59119	Vent cap	0.1	12.50



Replacement plastic cap fits MINICAL 5020 and 5021 series.

Code	Description	Lbs	USD
R56214	Vent cap	0.1	2.10



Replacement plastic air vent cap fits 5026 and 5027 series.

Code	Description	Lbs	USD
R56142	Vent cap	0.1	2.00



Magnetic/drywell assembly for DISCALDIRTMAG and DIRTMAG.

Code	Description	Lbs	USD
49684A	Fit 2" and 2½"	3.0	309.00
49685A	Fit 3" to 6"	3.0	446.00
F0000349	Fit 8" to 14"	3.0	583.00



DIRTCAL to DIRTMAG Retrofit kit for 3/4" to 2" 5462 brass DIRTCAL.

Code	Description	Lbs	USD
F41661A	Retrofit kit	2.0	112.00



Replacement clip-on magnets for DIRTMAG.

Code	Description	Lbs	USD
R39949	Magnetic band	0.2	37.60



Replacement air vent assembly fits DISCAL brass 551 series (except Compact and Rotating Collar version), brass 546, brass and steel 5461 series and SEP4 5495 series.

Code	Description	Lbs	USD
59829	Air vent assembly for brass DISCAL®	2.0	122.00



Replacement air vent assembly fits steel 551, NA551 steel DISCAL and 546 steel series DISCALDIRT and DISCALDIRTMAG.

Code	Description	Lbs	USD
59756	Air vent assembly for steel DISCAL®	3.0	135.00



Replacement cover and float subassembly. Vent cap sold separately.

Code	Description	Lbs	USD
F39807	Cover and float for brass DISCAL®	0.4	59.10
F0001470	Cover and float for steel DISCAL®	0.5	71.40



Drain ball valve. Fits DIRTCAL 5465 and NA5465 series. Fits steel separators in section 2. Max. working pressure: 150 psi. Max. working temperature: 365°F.

Code	Description	Lbs	USD
NA39753	1" FNPT with lever	0.7	42.60
NA59600	2" FNPT with lever	3.5	151.00



Vent cap adapter fits all air separators and air vents except 5026 and 5027 series.

Code	Description	Lbs	USD
NA10204	¼" MNPT	0.1	21.40



Replacement coalescing element for brass separators (except 551 Compact and 5517 Rotating collar).

Code	Description	Lbs	USD
F0001179	For sizes ¾" to 1¼" (sweat)	0.2	19.70
F59917	For sizes 1¼" (NPT, press) to 2"	0.2	19.70



Replacement GHT cap for DIRTMAG (shown attached to 538 drain valve, not included).

Code	Description	Lbs	USD
R49418	cap with teather	0.1	17.00

INTERACTIVE EXCELLENCE IN EDUCATION




idronics[™] is a complimentary educational journal series for hydronic, plumbing and renewable energy professionals to aid them in system design, component application and selection. The popular and frequently referenced publication is written by engineers and oriented towards innovative design techniques with a commitment to continuous education of North American professionals. Beginning with the 27th edition and in cadence with edition releases, Caleffi will provide **digital access to the journal**. Watch for the collection to GROW! **CALEFFI GUARANTEED.**

Digital *idronics*[™]
idronics.caleffi.com

For more information
marketingadmin@caleffi.com

THERMOSTATIC RADIATOR VALVES



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions
[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

- Thermostatic control heads
- Accessories for thermostatic control heads
- Thermo-electric actuator
- NPT thermostatic radiator valve bodies
- European style towel warmer radiator valves
- Connection valves for panel radiator
- Connection fittings
- Thermo-electric radiator valve bodies

THERMOSTATIC CONTROL HEADS



200

Thermostatic control head fits radiator valves. Set point locking mechanism. Range stop adjustment. Built-in sensor with liquid-filled element. Fits valve 220, 221, 338 and 339 series. Graduated scale from * to 5 corresponding to a temperature scale adjustment range of 45–82°F (7–28°C).

Code	Description	Lbs	USD
200000	Built-in sensor	0.5	58.40



472

Thermostatic control head with remote adjusting knob, liquid-filled element. Fits valves 220, 221, 338, 339 & 676 series (direct coupling). Temperature range: 43–82°F (6–28°C). Capillary length: 78 in. (2 m).

Code	Description	Lbs	USD
472000	Remote wall sensor	1.0	198.00



201

Thermostatic control head fits radiator valves. With remote sensor. Fits valve 220, 221, 338 and 339 series. Graduated scale from * to 5 corresponding to a temperature scale adjustment range of 45–82°F (7–28°C). Capillary length: 78" (2 m).

Code	Description	Lbs	USD
201000	Remote sensor	1.0	104.00



203

Thermostatic control head fits radiator valves; with contact probe. Built-in sensor with liquid-filled element. Fits valve 220, 221, 338 and 339 series. The pre-set scale corresponds to adjustment temperature range of 68–122°F (20–50°C). Capillary length: 78" (2 m).

Code	Description	Lbs	USD
203502	Remote sensor probe	0.5	197.00

ACCESSORIES



4490

Manual knob for thermostatic radiator valves. Fits valves 220 and 221 series.

Code	Description	Lbs	USD
449010	Manual knob	0.1	12.20


THERMO-ELECTRIC ACTUATOR



6564

Thermo-electric actuator for electric control of radiator valves. Fits valves 220, 221, 338 and 339 series. Low current draw. Power supply: 24 V AC/DC. Initial current draw: ≤ 250 mA. Power consumption: 3 W, 6 VA. 31.5" wire lead connection.

Code	Description	Lbs	USD
656404	24 V AC/DC	0.4	80.40
656414	24 V AC/DC with microswitch	0.4	102.00




Key features

The thermostatic control head is filled with a non compressible liquid bellows (1). Plus, the radiator valve body has an extra strong valve stem compression spring (2). The non compressible liquid provides the force required to compress the strong valve stem spring. When the temperature decreases, the liquid bellows contracts, which allows the valve stem spring to lift the valve plug from valve seat after long periods of non-movement. This ensures that after a long off-season, when the actuator operates for the first time, the spring reliably lifts the valve seat without sticking. In addition, the 200000 control head features an easy-to-use locking mechanism that prevents unauthorized temperature set point changes and a range stop adjustment that limits the maximum temperature setting to save energy and over-heating.

Function

The control mechanism of the thermostatic radiator valve is a proportional temperature controller, composed of a liquid filled bellows. With increasing temperature the liquid expands which, causes the bellows to expand. When the temperature decreases the opposite occurs; the bellows contracts allowing the spring to return it to the original position. By connection to the valve stem, these movements adjust the heat transfer medium to the radiator.

*Head shown vertical for illustration only, it should be installed horizontally.



NPT THERMOSTATIC RADIATOR VALVE BODIES



220

Angled radiator valve body. Order thermo-electric actuators or thermostatic control heads separately for field installation.
Chrome plated.
Max. working pressure: 150 psi (10 bar).
Temperature range: 40–212°F (5–100°C).

Code	Description	Cv	Lbs	USD
220400A	½" FNPT in, ½" NPT male union out	2.7	0.3	57.30
220500A	¾" FNPT in, ¾" NPT male union out	3.7	0.3	62.70



221

Straight radiator valve body. Order thermo-electric actuators or thermostatic control heads separately for field installation.
Chrome plated.
Max. working pressure: 150 psi (10 bar).
Temperature range: 40–212°F (5–100°C).

Code	Description	Cv	Lbs	USD
221400A	½" FNPT in, ½" NPT male union out	1.7	0.3	57.30
221500A	¾" FNPT in, ¾" NPT male union out	2.5	0.3	62.70



Replacement internal valve assembly fits radiator valves.

Code	Description	Lbs	USD
F36073	½" and ¾"	0.1	8.00



Universal radiator tool for installing ½ and ¾" tail pieces.

Code	Description	Lbs	USD
387127	Radiator tool	1.0	84.00

EUROPEAN STYLE TOWEL WARMER RADIATOR VALVES



338

Angled radiator valve body. Convertible from standard manual operation to automatic control with thermostatic control heads.
Chrome plated.
Fits copper, single and multilayer PEX pipes.
Max. working pressure: 150 psi (10 bar).
Temperature range: 40–212°F (5–100°C).

Code	Radiator Connection	Pipe Connection	Cv	Lbs	USD
338452	½" straight	¾" conical	3.1	0.5	60.30



342

Angled isolation and balancing valve. Chrome plated.
Fits copper, single and multilayer PEX pipes.
Max. working pressure: 150 psi (10 bar).
Temperature range: 40–212°F (5–100°C).

Code	Radiator Connection	Pipe Connection	Cv	Lbs	USD
342452	½" straight	¾" conical	4.6	0.5	39.60



339

Straight radiator valve body. Convertible from standard manual operation to automatic control with thermostatic control heads.
Chrome plated.
Fits copper, single and multilayer PEX pipes.
Max. working pressure: 150 psi (10 bar).
Temperature range: 40–212°F (5–100°C).

Code	Radiator Connection	Pipe Connection	Cv	Lbs	USD
339452	½" straight	¾" conical	2.0	0.5	65.00



343


Straight isolation and balancing valve. Chrome plated.
Fits copper, single and multilayer PEX pipes.
Max. working pressure: 150 psi (10 bar).
Temperature range: 40–212°F (5–100°C).

Code	Radiator Connection	Pipe Connection	Cv	Lbs	USD
343452	½" straight	¾" conical	2.5	0.5	41.60

Intended for use in metric radiators such as European towel warmers and panel radiators.

CONNECTION VALVES FOR PANEL RADIATORS

Caleffi panel radiator valves are designed to be connected to the bottom of panel radiators. They come in two versions: for two-pipe and one-pipe systems. Both are available straight (pipes exiting the floor) and angled (pipes exiting the wall). The two-pipe version is equipped with two ball shut-off valves. The one-pipe, in addition to the shut-off valves, is equipped with an adjustable by-pass which diverts from 30% to 50% of the flow rate towards the radiator, and a flow check valve device (1) prevents thermo-syphoning upward into radiator from by-passing flow.



3010

Valve for panel radiators that have built-in thermostatic valve unit.
Two-pipe straight version (floor connections) fits 1/2" female radiator connections.
Max. working pressure: 150 psi (10 bar).
Max. working temperature: 212°F (100°C).

Code	Radiator Connection	Pipe Connection	Lbs	USD
301040	1/2" straight	3/4" conical	1.0	48.30



3011

Valve for panel radiators that have built-in thermostatic valve unit.
Two-pipe valve angled version (wall connections) fits 1/2" female radiator connections.
Max. working pressure: 150 psi (10 bar).
Max. working temperature: 212°F (100°C).

Code	Radiator Connection	Pipe Connection	Lbs	USD
301140	1/2" straight	3/4" conical	1.0	48.30



3012

Valve for panel radiators that have built-in thermostatic valve unit.
One-pipe straight version (floor connections) fits 1/2" female radiator connections.
With adjustable by-pass.
Balance knob.
Max. working pressure: 150 psi (10 bar).
Max. working temperature: 212°F (100°C).

Code	Radiator Connection	Pipe Connection	Lbs	USD
301241	1/2" straight	3/4" conical	1.0	84.50



3013

Valve for panel radiators that have built-in thermostatic valve unit.
One-pipe angled version (wall connections) fits 1/2" female radiator connections.
With adjustable by-pass.
Balance knob.
Max. working pressure: 150 psi (10 bar).
Max. working temperature: 212°F (100°C).

Code	Radiator Connection	Pipe Connection	Lbs	USD
301341	1/2" straight	3/4" conical	1.0	84.50



4497

Wall-covering plate.
Fits dual panel radiator valves 301.
With wall connections.
In white ABS.
Outlet center distance: 40–50 mm.

Code	Description	Lbs	USD
449740	Plate	0.1	4.30

CONNECTION FITTINGS



681
Universal
PEX fittings

681 series fittings are compatible with any ASTM F876 single layer PEX.
Max. working pressure: 150 psi.
Working temperature for ASTM F876 PEX piping: 41 – 180°F.
Chrome plated nut.


Code	Description	Lbs	USD
681503A	3/8" nominal PEX	0.2	10.30
681524	1/2" nominal PEX	0.2	10.30
681555	5/8" nominal PEX	0.2	10.10



682
Universal
PEX-AL-PEX fittings

682 series fittings are compatible with any ASTM F1281 multilayer PEX-AL-PEX pipe.
Max. working pressure: 150 psi.
Working temperature for ASTM F1281 PEX-AL-PEX piping: 41 – 200°F with tubing rated 200°F.

Code	Description	Lbs	USD
682540A	1/2" PEX-AL-PEX	0.2	10.10



940

Radiator adapter for directly connecting a panel radiator with PEX, PEX-AL-PEX, sweat, NPT or compression fittings.
Package of 2 each, priced per package.



Code	Description	Lbs	USD
940451	1/2" M straight x 3/4" M conical (2 ea.)	0.1	18.50

Wrench for tightening PEX fitting to TRV.



Code	Description	Lbs	USD
387100	26 mm x 30 mm	1.5	46.40



437

Compression fitting, fits 1/2" hard copper.
With o-ring seal.
Max. working pressure: 150 psi.
Working temperature range: 41 – 250°F.
Chrome plated.
For connecting copper to valve 301, 338, 339, 342 and 343 series.

Code	Description	Lbs	USD
437516	1/2" compression	0.1	8.30



NA102

Sweat connection fitting fits 1/2" copper.
Max. working pressure: 150 psi.
Working temperature range: 41 – 250°F.
Chrome plated nut.
For connecting copper to valve 301, 338, 339, 342 and 343 series.

Code	Description	Lbs	USD
NA10262	1/2" sweat	0.2	11.00



NA103

NPT connection fitting.
Max. working pressure: 150 psi.
Working temperature range: 41 – 250°F.
Chrome plated nut.
For connecting copper to valve 301, 338, 339, 342 and 343 series.

Code	Description	Lbs	USD
NA10313	1/2" NPT male	0.2	11.80


ZONING DONE RIGHT INDUSTRY EXCLUSIVE 5-YEAR WARRANTY



The extremely reliable **Z-one™ motorized zone valve** offers quick installation and easy service in a wide variety of applications. When installed with a **Z-one™ Relay** control, featuring universal compatibility and versatility, both qualify for our industry exclusive **five-year warranty. CALEFFI GUARANTEED.**



ZONE VALVES AND ZONE CONTROLS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions
[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

- Thermo-electric zone valves
- Motorized zone controls
- Pump zone controls
- Valve zone controls
- Motorized ball zone valves, high-flow, high-close off

THERMO-ELECTRIC ZONE VALVES

6767 TwisTop+™ High Performance



Complete with 656354 actuator.
 Pressure balanced body.
 40% more flow, 75% more close-off
 Spring return. Normally closed.
 Pressure balanced body.
 Brass valve body and trim.
 Max. body pressure: 150 psi.
 Max. Temperature: 200°F.
 Power supply: 24 V AC/DC.
 Initial current draw: ≤ 250 mA.
 Power consumption:
 holding: 3 W
 inrush: 6 VA
 Rating of micro-switch contacts: 5 A (24 V).
 31.5" wire lead connection.

6762 TwisTop™ Zone valve



Two-way thermo-electric zone valve.
 Complete with TwisTop™ (code 656354)
 actuator. Spring return. Normally closed.
 Brass valve body and trim.
 Max. body pressure: 150 psi.
 Max. Temperature: 200°F.
 Power supply: 24 V AC/DC.
 Initial current draw: ≤ 250 mA.
 Power consumption:
 holding: 3 W
 inrush: 6 VA
 Rating of micro-switch contacts: 5 A (24 V).
 31.5" wire lead connection.

Code	Description	Cv	ΔP	Lbs	USD
676756A	¾" press union	5.6	35 psi	2.2	217.00
676759A	¾" sweat union	5.6	35 psi	2.2	211.00
676758A	¾" PEX expansion union	5.6	35 psi	2.2	211.00
676766A	1" press union	5.6	35 psi	2.2	247.00
676769A	1" sweat union	5.6	35 psi	2.2	236.00
676768A	1" PEX expansion union	5.6	35 psi	2.2	236.00
676500A	body only, close-off 35 psid	5.6		1.0	54.30

Code	Description	Cv	ΔP	Lbs	USD
676256A	¾" press union	4.0	20 psi	1.4	198.00
676259A	¾" sweat union	4.0	20 psi	1.4	192.00
676258A	¾" PEX expansion union	4.0	20 psi	1.4	192.00
676266A	1" press union	4.0	20 psi	1.4	228.00
676269A	1" sweat union	4.0	20 psi	1.4	219.00
676268A	1" PEX expansion union	4.0	20 psi	1.4	219.00
676000A	body only, close-off 20 psid	4.3		0.5	27.40

6564



Thermo-electric actuator fits on 676 two-way zone valve bodies.
 Low current draw.
 Protection class (installed in all positions):
 NEMA 3 (IP54)
 Power supply: 24 V AC/DC.
 Initial current draw: ≤ 250 mA.
 Power consumption:
 holding: 3 W
 inrush: 6 VA
 Rating of micro-switch contacts: 5 A (24 V).
 31.5" wire lead connection.

6563 TwisTop™




TwisTop™ thermo-electric actuator fits on 676 two-way valve.
 Twist the top to manually open and close micro-switch.
 Power supply: 24 V AC/DC.
 Initial current draw: ≤ 250 mA.
 Power consumption:
 holding: 3 W
 inrush: 6 VA
 Rating of micro-switch contacts: 5 A (24 V).
 31.5" wire lead connection.
 U.S. Patent 7,617,989 B2.

Code	Description	Lbs	USD
656404	24 V AC/DC	0.4	80.40
656414	24 V AC/DC with micro-switch	0.4	102.00


Code	Description	Lbs	USD
656344	24 V AC/DC	0.4	108.00
656354	24 V AC/DC with micro-switch	0.4	127.00

Construction design

The zone valve, code 676500A, has a special valve plug that can work at high differential pressures. As shown in the figure, the thrust towards the opening is counterbalanced by the force created by the pressure acting on the internal surface of the valve plug. This feature reduces the thrust needed to close the valve plug.



Up to 12 actuators per 40 VA transformer.



MOTORIZED ZONE VALVES

Z4
Z-one 2-way



Two-way zone valve. Spring return.
Normally closed actuator: Z111000.
Auxiliary micro-switch.
Max. body pressure: 300 psi.
Temperature range: 32°–240°F.
Suitable fluids: water, 50% max. glycol,
15 psi max. steam.
Power supply: 24 V AC.
Power consumption: 5 W, 7 VA.
Rating of auxiliary micro-switch contacts:
0.0 A min, 0.4 A max 24 V (24 V only).
18" wire lead connection.
UL873, cULus Listed & CE.
UL 1995 sec. 18 air plenums and ducts.
U.S. Patent 7,048,251.



Z5
Z-one 2-way



Two-way zone valve. Spring return.
Normally closed actuator: Z151000.
Auxiliary micro-switch.
Max. body pressure: 300 psi.
Temperature range: 32°–240°F.
Suitable fluids: water, 50% max. glycol,
15 psi max. steam.
Power supply: 24 V AC.
Power consumption: 5 W, 7 VA.
Rating of auxiliary micro-switch contacts:
0.0 A min, 0.4 A max 24 V (24 V only).
Screw terminal connection.
UL873, cULus Listed & CE.
UL 1995 sec. 18 air plenums and ducts.
U.S. Patent 7,048,251.



Code	Description	Cv	Δ P	Lbs	USD
Z40	Inverted flare	3.5	30 psi	2.2	164.00
Z40F	¾" Inv flare*	3.5	30 psi	2.2	185.00
Z42	½" SAE flare	3.5	30 psi	2.2	177.00
Z44	½" sweat	2.5	50 psi	2.1	160.00
Z45	¾" sweat	7.5	20 psi	2.2	173.00
Z46	1" sweat	7.5	20 psi	2.3	216.00
Z47	1¼" sweat	7.5	20 psi	2.3	251.00

* Two ¾" sweat fittings (NA10006) included.

Code	Description	Cv	Δ P	Lbs	USD
Z50	Inverted flare	3.5	30 psi	2.2	168.00
Z50F	¾" Inv flare*	3.5	30 psi	2.2	189.00
Z54	½" sweat	2.5	50 psi	2.1	164.00
Z55	¾" sweat	7.5	20 psi	2.2	177.00
Z56	1" sweat	7.5	20 psi	2.3	219.00
Z57	1¼" sweat	7.5	20 psi	2.3	255.00

* Two ¾" sweat fittings (NA10006) included.

Z-one 2-way Unions



Two-way zone valve. Spring return.
Auxiliary micro-switch.
Max. body pressure: 300 psi.
Overall length: 5-⁵/₈"
Temperature range: 32–240°F.
Suitable fluids: water, 50% max. glycol,
15 psi max. steam.
Power supply: 24 V AC.
Power consumption: 5 W, 7 VA.
Rating of auxiliary micro-switch contacts:
0.0 A min, 0.4 A max 24 V (24 V only).
UL873, cULus Listed & CE.
UL 1995 sec. 18 air plenums and ducts.
U.S. Patent 7,048,251.




Code	Description	Cv	Δ P	Lbs	USD
Z44P	½" press unions*	3.5	30 psi	2.2	219.00
Z54P	½" press unions**	3.5	30 psi	2.2	223.00
Z45P	¾" press unions*	7.5	20 psi	2.2	223.00
Z55P	¾" press unions**	7.5	20 psi	2.2	227.00
Z45PL	¾" press unions*	7.5	20 psi	2.3	245.00
Z55PL	¾" press unions**	7.5	20 psi	2.3	249.00
Z46P	1" press unions*	7.5	20 psi	2.4	252.00
Z56P	1" press unions**	7.5	20 psi	2.4	257.00
Z55S	¾" sweat unions	7.5	20 psi	2.2	216.00

*18" wire lead connection.

**Screw terminal connection.

PL (1) extra long press fitting for retrofit
Includes press fittings.

Construction design



Inverted flare sweat adaptors fits Z40, Z50 and inverted flare valve body.

Code	Description	Lbs	USD
NA10005	½" sweat	0.3	8.30
NA10006	¾" sweat	0.3	10.50
NA10007	1" sweat	0.4	17.40
NA61241	Retrofit extension kit	0.2	8.50

MOTORIZED ZONE VALVES



Z1

Z1 Normally closed actuators fit on Z2 and Z3 valves. Normally open actuators fit on Z2 valves only. Easy pushbutton attachment 7/8" knockout for 1/2" conduit connector. Power: 24 and 120 VAC. Power consumption: 5 W, 7 VA. Conduit connector size: 1/2". Rating of auxiliary switch contacts: 24 VAC: 0.0 A min, 0.4 A max (24 V). 120 and Z11900 VAC: 0.25 A min, 5.0 A max (230 V). UL873, cULus Listed & CE. UL 1995 sec.18 air plenums and ducts. U.S. Patent 7,048,251.

Normally closed

Code	Description	Lbs	USD
Z111000	24 V, micro-switch, 18" wires	1.1	113.00
Z111900	24 V, high current switch, 18" wires	1.1	113.00
Z116000	120 V, micro-switch, 6" wires	1.1	113.00
Z151000	24 V, micro-switch, terminal blocks	1.1	117.00
Z161000	24 V, terminal blocks	1.1	107.00
Z121000	24 V, 18" wires	1.1	105.00
Z126000	120 V, 6" wires	1.1	105.00

Normally open

Code	Description	Lbs	USD
Z131000	24 V, micro-switch, 18" wires	1.1	124.00
Z136000	120 V, micro-switch, 6" wires	1.1	124.00
Z141000	24 V, 18" wires	1.1	114.00
Z146000	120 V, 6" wires	1.1	114.00


Function

The Z-one™ valve is a truly universal zone valve that can be used in a wide range of commercial and residential applications; from fan coils to baseboard, radiant to high rise, the Z-one is the professional's valve of choice. The Z-one can be used in both chilled or hot water and low pressure steam applications. With Delta P close off pressures of up to 75 PSI, the Z-one outperforms all other zone valves. The Z-one is available in sizes from 1/2" to 1 1/4" sweat or NPT connections on valve body, with removable actuator available in 24 to 120 voltages.

Some models of Z-one actuators contain an auxiliary micro-switch to operate other devices. The 24 V actuators use a sealed reed switch, which has been produced specifically for use with relays, boiler contacts (TT) and DDC systems. It requires no minimum current load. The 120 V actuators for applications requiring greater than 400 mA, use a conventional micro-switch with silver contacts. The auxiliary switch is activated when the valve is 60% open or when the actuator is manually opened.


• Manual opening (Normally closed actuator only)

The valve can be opened manually by moving the lever for opening it. When the power is restored the manual control is automatically overridden. The auxiliary switch in 24 V actuators is tripped when the unit is put into manual open position. This helps during start up to check if the wiring is correct without firing the valve electrically with the thermostat.




• Auxiliary micro-switch

The actuator contains an auxiliary microswitch to operate other devices. The 24 V actuators use a sealed reed switch, which has been produced specifically for use with relays, boiler contacts (TT) and DDC systems. It requires no minimum current load. The 120 V actuators use a conventional micro-switch with silver contacts. The auxiliary micro-switch is activated when the valve is 60% open or when the actuator is manually opened.



Construction details



MOTORIZED ZONE VALVES

Z2
2-way



Two-way on/off two position valve. Straight through flow pattern. Brass body. Stainless steel stem. EPDM rubber seals and paddle. Max. working pressure: 300 psi. Max temperature: 240°F.

Code	Description	Cv	Δ P	Lbs	USD
Z200041	Inverted flare	1.0	75 psi	1.1	49.90
Z200042	Inverted flare	2.5	50 psi	1.1	49.90
Z200043	Inverted flare	3.5	30 psi	1.1	49.90
Z200053	½" SAE Flare	3.5	30 psi	1.1	63.90
Z200411	½" FNPT	1.0	75 psi	1.1	49.90
Z207411	½" FNPT LL	1.0	75 psi	1.1	68.10
Z200412	½" FNPT	2.5	50 psi	1.1	49.90
Z200413	½" FNPT	3.5	30 psi	1.1	49.90
Z200431	½" sweat	1.0	75 psi	1.0	45.70
Z200432	½" sweat	2.5	50 psi	1.0	45.70
Z207433	½" sweat LL	3.5	30 psi	1.0	63.90
Z200512	¾" FNPT	2.5	50 psi	1.2	68.10
Z200513	¾" FNPT	3.5	30 psi	1.2	68.10
Z200515	¾" FNPT	5.0	25 psi	1.2	68.10
Z200517	¾" FNPT	7.5	20 psi	1.2	68.10
Z200532	¾" sweat	2.5	50 psi	1.1	60.30
Z207533*	¾" sweat LL	3.5	30 psi	1.1	78.40
Z200535	¾" sweat	5.0	25 psi	1.1	60.30
Z200537	¾" sweat	7.5	20 psi	1.1	60.30
Z207537*	¾" sweat LL	7.5	20 psi	1.1	78.40
Z200617	1" FNPT	7.5	20 psi	1.3	108.00
Z200635	1" sweat	5.0	25 psi	1.2	102.00
Z200637	1" sweat	7.5	20 psi	1.2	102.00
Z200737	1¼" sweat	7.5	20 psi	1.3	137.00

LL Low-lead brass body.

NEW



Isolation ball valve. Low lead MxF union union fits between valve body and tailpiece.

Code	Description	Lbs	USD
290030	1" M x 1" F union ball valve	1.0	46.20
NA10815	Stem extension for 290030	0.2	26.30



Z3
3-way



Three-way on/off two position valve. Diverting flow pattern. Brass body. Stainless steel stem. EPDM rubber seals and paddle. Max. working pressure: 300 psi. Max temperature: 240°F.

Code	Description	Cv	Δ P	Lbs	USD
Z300053	½" SAE Flare	3.5	30 psi	1.1	79.80
Z300411	½" FNPT	1.0	75 psi	1.1	66.50
Z300412	½" FNPT	2.5	50 psi	1.1	66.50
Z300413	½" FNPT	3.5	30 psi	1.1	66.50
Z300431	½" sweat	1.0	75 psi	1.0	62.40
Z300432	½" sweat	2.5	50 psi	1.0	62.40
Z307433*	½" sweat LL	3.5	30 psi	1.0	80.40
Z300512	¾" FNPT	2.5	50 psi	1.2	83.10
Z300513	¾" FNPT	3.5	30 psi	1.2	83.10
Z300515	¾" FNPT	5.0	25 psi	1.2	83.10
Z300517	¾" FNPT	7.5	20 psi	1.2	83.10
Z300532	¾" sweat	2.5	50 psi	1.1	77.10
Z300533	¾" sweat	3.5	30 psi	1.1	77.10
Z300535	¾" sweat	5.0	25 psi	1.1	77.10
Z307537*	¾" sweat LL	7.5	20 psi	1.1	95.30
Z300617	1" FNPT	7.5	20 psi	1.3	125.00
Z300635	1" sweat	5.0	25 psi	1.2	116.00
Z300637	1" sweat	7.5	20 psi	1.2	116.00
Z300737	1¼" sweat	7.5	20 psi	1.3	141.00

***LL** Low-lead brass body.

2-way male union valve body. Select fittings in Section 8 Table.



Code	Description	Cv	Δ P	Lbs	USD
Z200683	1" male union body	3.5	30 psi	1.1	68.10
Z200687	1" male union body	7.5	20 psi	1.1	68.10

3-way male union valve body. Select fittings in Section 8 Table.



Code	Description	Cv	Δ P	Lbs	USD
Z300687	1" male union body	7.5	20 psi	1.2	86.60

Two-way and three-way zone valve body repair kit. Includes valve stem paddle with O-rings, C clip and one bottom cap O-ring.



Code	Description	Lbs	USD
F69293	Fits all ½" & ¾" sweat Z2, Z3	0.4	17.20
F69294	Fits all ¾" NPT and all 1", 1¼" Z2, Z3	0.4	17.20

PUMP ZONE CONTROLS



ETL Intertek 4009064
 Certified to CSA C22-2 No.24
 Conforms to UL Standard 873

ZSR
Z-one Relay

The ZSR series is multi-zone pump and boiler operating control for multiple zone hydronic heating systems. The ZSR series interfaces with low voltage thermostats or any other low voltage controllers having a switching action. The ZSR series controls up to 3, 4, 5 or 6 heating circulator pumps, depending on model selected, a primary pump, and has LED indicators to provide functional status and easy system troubleshooting. In addition, a primary pump system circulator is switched on whenever any zone calls for heat.

Power supply: 120 VAC, 50/60 Hz
 Transformer voltage: 24 VAC
 Maximum transformer load: 12 VA (ZSR101/103/104), 20 VA (ZSR106)
 Electrical switch rating: 10A (ZSR101), 20A (ZSR103/4/6) max combined
 Electrical switch rating pump output: 120 VAC, 5A each
 Dry contact rating: AUX, XX, ZONE1 E/S: 120 VAC max, 2A each
 Replaceable fuses: Type 2AG, 5A slow blow

ZSR Z-ONE RELAY FUSES

Code	Description	Lbs	USD
NA10342	Spare fuse (package of 5)	0.1	11.60

Code	Description	Lbs	USD
ZSR101	Single zone relay	1.0	114.00
ZSR103	3 zone pump control	2.0	270.00
ZSR104	4 zone pump control	2.0	316.00
ZSR106	6 zone pump control	2.0	386.00

VALVE ZONE CONTROLS



ETL Intertek 4009064
 Certified to CSA C22-2 No.24
 Conforms to UL Standard 873

ZVR
Z-one Relay

The ZVR series is a multi-zone valve relay and boiler operating control for multiple zone hydronic heating systems. The ZVR series interfaces with low voltage thermostats or any other low voltage controllers having a switching action. The ZVR series controls up to 3, 4, 5 or 6 zones, depending on model selected. In addition, a system circulator pump and secondary pump is turned on whenever any zone calls for heat. LED indicators provide functional status and easy system troubleshooting. The ZVR series is a perfect match with Caleffi's Z-one™ motorized zone valves.

Power supply: 120 VAC, 50/60 Hz
 Transformer voltage: 24 VAC
 Maximum transformer load: 40 VA (ZVR103/4), 80 VA (ZVR106)
 Electrical switch rating: 20A Max Combined
 Electrical switch rating pumps: 120 VAC, 5A each
 Dry contact rating: AUX, XX, ZONE1 E/S:120 VAC, 2A each
 Resettable Fuse: automatic
 High Capacity 40 VA Transformer standard for 3 and 4 zone models- expandable to 80 VA, and 80 VA for the 6 zone model

Code	Description	Lbs	USD
ZVR103	3 zone valve control	2.0	205.00
ZVR104	4 zone valve control	2.0	243.00
ZVR106	6 zone valve control	2.0	316.00
NA10343	Expansion transformer	0.1	66.20

MOTORIZED BALL ZONE VALVES HIGH-FLOW, HIGH CLOSE-OFF





6442
2-way Straight

Two-way motorized ball zone valve. Straight.
Max. ΔP close-off pressure: 150 psi.
Temperature range: 20°–230°F.
Power supply: 24 VAC.
Power consumption: 4 VA.
Rating of micro-switch contacts: 5 A (24 V).
3-wire control.
36" wire lead connection.

Code	Description	Cv	Lbs	USD
644250A	¾" NPT male union	13	2.3	318.00
644256A	¾" press union	13	2.4	318.00
644259A	¾" sweat union	13	2.3	312.00
644260A	1" NPT male union	13	2.3	344.00
644266A	1" press union	13	2.4	347.00
644269A	1" sweat union	13	2.3	337.00
NA644200*	body, with no fittings	13	1.0	276.00

*See fitting selection table in Section 8.




6443..3BY
3-way By-pass



Three-way motorized ball zone valve. By-pass.
Max. ΔP close-off pressure: 150 psi.
Temperature range: 20°–230°F.
Power supply: 24 VAC.
Power consumption: 4 VA.
Rating of micro-switch contacts: 5 A (24 V).
3-wire control.
2.1 Cv in by-pass mode.
36" wire lead connection.

Code	Description	Cv	Lbs	USD
644350A 3BY	¾" NPT male union	12	2.5	343.00
644356A 3BY	¾" press union	12	2.6	361.00
644359A 3BY	¾" sweat union	12	2.5	353.00
644360A 3BY	1" NPT male union	12	2.5	399.00
644366A 3BY	1" press union	12	2.6	405.00
644369A 3BY	1" sweat union	12	2.5	390.00
NA644300 3BY*	body, no fittings	12	1.2	299.00

*See fitting selection table in Section 8.



6440
24 V 3-wire control



Actuator fits 6442 and 6443 series.
Power supply: 24 VAC.
Power consumption: 4 VA.
Rating of micro-switch contacts: 5 A (24 V).
Operating time: 40 s (90° rotation).
Length of supply cable: 36".

Code	Description	Lbs	USD
644004	24 VAC	1.0	187.00

6443
3-way Diverting



Three-way motorized ball zone valve. Diverting.
Max. ΔP close-off pressure: 150 psi.
Temperature range: 20°–230°F.
Power supply: 24 VAC.
Power consumption: 4 VA.
Rating of micro-switch contacts: 5 A (24 V).
3-wire control.
36" wire lead connection.

Code	Description	Cv	Lbs	USD
644350A	¾" NPT male union	4.5	2.5	343.00
644356A	¾" press union	4.5	2.6	361.00
644359A	¾" sweat union	4.5	2.5	353.00
644360A	1" NPT male union	4.5	2.5	399.00
644366A	1" press union	4.5	2.6	405.00
644369A	1" sweat union	4.5	2.5	390.00
NA644300*	body, no fittings	4.5	1.2	299.00

*See fitting selection table in Section 8.

WEBINAR SERIES EXCELLENCE IN EDUCATION




You are invited to join us for our monthly webinar series, Coffee with Caleffi™. The complimentary technical training webinars are intended for contractors, designers, engineers, and wholesalers. A Certificate of Attendance is emailed to attendees following the webinar for continuing education consideration. Register by scanning the QR code below. Missed a webinar? No problem! Our webinars are available 24/7 on YouTube for your convenience. **CALEFFI GUARANTEED.**

Coffee with Caleffi™
bit.ly/CWC-SCHEDULE

For more information
marketingadmin@caleffi.com

DISTRIBUTION MANIFOLDS AND TEMPERATURE MIXING STATIONS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions

[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

- Thermostatic manifold mixing stations
- Low temperature manifold mixing stations
- Brass distribution manifolds
- Distribution manifolds
- Pump and valve temperature mixing units
- Fittings for distribution manifolds and mixing stations
- Boxes for distribution manifolds
- Thermo electric actuators for manifolds and valves

THERMOSTATIC MANIFOLD MIXING STATIONS

**172
Low temperature manifold mixing station three speed pump**

Pre-assembled thermostatic manifold mixing station consisting of a supply distribution manifold complete with built-in sight flow gauges and adjustable balancing valves. Return manifold with built-in shutoff valves is suitable for thermo-electric actuators. Complete with built-in sensor to keep flow temperature at constant set value.

Includes Grundfos UPS 15–58 three-speed pump.

¾" F NPT supply/return ball valves.

Max. working pressure: 150 psi.


Control temperature range: 80°–130°F.

Primary inlet max. temperature: 195°F.

Outlet center distance: 2 in.

PT Gauge: (40-240°F, 10-110°C) (0-10 bar; 1-140 psi)

Models with "...IN" suffix are built inverted (tubing connections going upward).



Code	Description	UPS Pump	No.	Outlets	Lbs	USD
1725C1A	¾"	15-58	3	¾" M	20	1,235.00
1725C1A IN	¾"	15-58	3	¾" M	20	1,235.00
1725D1A	¾"	15-58	4	¾" M	21	1,316.00
1725D1A IN	¾"	15-58	4	¾" M	21	1,316.00
1725E1A	¾"	15-58	5	¾" M	23	1,394.00
1725E1A IN	¾"	15-58	5	¾" M	23	1,394.00
1725F1A	¾"	15-58	6	¾" M	25	1,475.00
1725F1A IN	¾"	15-58	6	¾" M	25	1,475.00
1725G1A	¾"	15-58	7	¾" M	27	1,555.00
1725G1A IN	¾"	15-58	7	¾" M	27	1,555.00
1725H1A	¾"	15-58	8	¾" M	28	1,635.00
1725H1A IN	¾"	15-58	8	¾" M	28	1,635.00
1725I1A	¾"	15-58	9	¾" M	29	1,714.00
1725I1A IN	¾"	15-58	9	¾" M	29	1,714.00
1725L1A	¾"	15-58	10	¾" M	31	1,792.00
1725L1A IN	¾"	15-58	10	¾" M	31	1,792.00
1725M1A	¾"	15-58	11	¾" M	33	1,872.00
1725M1A IN	¾"	15-58	11	¾" M	33	1,872.00
1725N1A	¾"	15-58	12	¾" M	34	1,953.00
1725N1A IN	¾"	15-58	12	¾" M	34	1,953.00
1725O1A	¾"	15-58	13	¾" M	36	2,032.00
1725O1A IN	¾"	15-58	13	¾" M	36	2,032.00

**172
Low temperature manifold mixing station high efficiency pump**

Pre-assembled thermostatic manifold mixing station consisting of a supply distribution manifold complete with built-in sight flow gauges and adjustable balancing valves. Return manifold with built-in shutoff valves is suitable for thermo-electric actuators. Complete with built-in sensor to keep flow temperature at constant set value.

Includes Grundfos Alpha 25-55U pump.

¾" F NPT supply/return ball valves.

Max. working pressure: 150 psi.

Control temperature range: 80°–130°F.

Primary inlet max. temperature: 195°F.

Outlet center distance: 2 in.

PT Gauge: (40-240°F, 10-110°C) (0-10 bar; 1-140 psi)

Models with "...IN" suffix are built inverted (tubing connections going upward).



Code	Description	Alpha Pump	No.	Outlets	Lbs	USD
1725C1AHE	¾"	25-55U	3	¾" M	20	1,483.00
1725C1AHE IN	¾"	25-55U	3	¾" M	20	1,483.00
1725D1AHE	¾"	25-55U	4	¾" M	21	1,561.00
1725D1AHE IN	¾"	25-55U	4	¾" M	21	1,561.00
1725E1AHE	¾"	25-55U	5	¾" M	23	1,641.00
1725E1AHE IN	¾"	25-55U	5	¾" M	23	1,641.00
1725F1AHE	¾"	25-55U	6	¾" M	25	1,720.00
1725F1AHE IN	¾"	25-55U	6	¾" M	25	1,720.00
1725G1AHE	¾"	25-55U	7	¾" M	27	1,802.00
1725G1AHE IN	¾"	25-55U	7	¾" M	27	1,802.00
1725H1AHE	¾"	25-55U	8	¾" M	28	1,880.00
1725H1AHE IN	¾"	25-55U	8	¾" M	28	1,880.00
1725I1AHE	¾"	25-55U	9	¾" M	29	1,960.00
1725I1AHE IN	¾"	25-55U	9	¾" M	29	1,960.00
1725L1AHE	¾"	25-55U	10	¾" M	31	2,041.00
1725L1AHE IN	¾"	25-55U	10	¾" M	31	2,041.00
1725M1AHE	¾"	25-55U	11	¾" M	33	2,120.00
1725M1AHE IN	¾"	25-55U	11	¾" M	33	2,120.00
1725N1AHE	¾"	25-55U	12	¾" M	34	2,200.00
1725N1AHE IN	¾"	25-55U	12	¾" M	34	2,200.00
1725O1AHE	¾"	25-55U	13	¾" M	36	2,279.00
1725O1AHE IN	¾"	25-55U	13	¾" M	36	2,279.00

THERMOSTATIC MANIFOLD MIXING STATIONS

Characteristic components / hydraulic diagram

Item	Description	Symbol
1	Circulation pump UPS 15-58 pictured	
2	Top elbow with supply temperature and pressure gauge	
3	Purge valve	
4	Supply temperature and pressure gauge	
5	Return temperature gauge	
6	Primary circuit shut-off valves	
7	Primary circuit hydraulic separator with check valve	
8	Thermostatic three-way mixing valve with built-in sensor	

Supply manifold equipped with flow meters and balancing valves.

Return manifold equipped with shut-off valves.


End fittings with automatic air vent with hygroscopic cap and drain cock.

Function

The 172 series manifold mixing station is designed for use in manifold-based hydronic distribution systems. The manifold mixing station incorporates a thermostatic actuator with built-in sensor which keeps the flow temperature at a constant set value for use in low temperature systems such as floor radiant panels. (7) A removable, primary circuit hydraulic separator with check valve is also supplied. The hydraulic separator is essential when there is a primary circuit circulation pump and when radiator circuits or fan coils are controlled by

thermostatic or thermo-electric valves. When connecting to a Caleffi HYDROLINK™ or hydraulic separator without a primary pump, the hydraulic separator can be removed and the manifold mixing station can be connected directly. The 172 station, like the TWISTFLOW™ Series 668S1 distribution manifolds, can be configured with 3 to 13 circuit outlets offering similar benefits with built-in sight flow meters/adjustable balancing valves and optional TWISTOP™ thermo-electric zone actuators.

LOW TEMPERATURE MANIFOLD MIXING STATIONS




Thermostatic mixing station kit

For field assembly to a Caleffi radiant manifold assembly. Grundfos UPS 15–58 three-speed pump or Alpha 25-55U. 1" NPT male adapters included to connect to manifold. 3/4" NPT female riser connections. Includes built-in hydraulic separator.

Code	Description	Lbs	USD
NA17256HE	Thermostatic mixing, Alpha 25-55U	4.1	1,198.00
NA17256	Thermostatic mixing, UPS 15-58U	4.1	940.00
NA16002	Alpha 25-55U replacement pump	2.3	515.00
NA10038	UPS 15-58U replacement pump	2.3	253.00
F19153	Replacement mixing valve	1.6	286.00

BRASS DISTRIBUTION MANIFOLDS



**668S1
TwistFlow™ assembly**

Pre-assembled radiant manifold consisting of return distribution manifold complete with built-in shut-off valves suitable for thermo-electric actuator and supply distribution manifold complete with built-in sight flow meters and balancing valves with 2" gauges 30—210°F scale.

1" or 1¼" NPT inlet ball valves.

Temperature gauges.

Max. working pressure: 150 psi.

Max. working temperature: 180°F.

Max. peak temperature: 200°F.

Loop Cv: 1.23 (combined supply & return ports).

Flow meter scale: ¼ — 2 gpm.


Outlet center distance: 2".

Models with "...IN" suffix are built inverted (tubing connections going upward).

Code	Description	No.	Outlets	Lbs	USD
6686C5S1A	1"	3	¾" M	17	571.00
6686C5S1A IN	1"	3	¾" M	17	571.00
6686D5S1A	1"	4	¾" M	18	653.00
6686D5S1A IN	1"	4	¾" M	18	653.00
6686E5S1A	1"	5	¾" M	19	735.00
6686E5S1A IN	1"	5	¾" M	19	735.00
6686F5S1A	1"	6	¾" M	21	819.00
6686F5S1A IN	1"	6	¾" M	21	819.00
6686G5S1A	1"	7	¾" M	23	901.00
6686G5S1A IN	1"	7	¾" M	23	901.00
6686H5S1A	1"	8	¾" M	24	986.00
6686H5S1A IN	1"	8	¾" M	24	986.00
6686I5S1A	1"	9	¾" M	26	1,067.00
6686I5S1A IN	1"	9	¾" M	26	1,067.00
6686L5S1A	1"	10	¾" M	28	1,150.00
6686L5S1A IN	1"	10	¾" M	28	1,150.00
6686M5S1A	1"	11	¾" M	29	1,233.00
6686M5S1A IN	1"	11	¾" M	29	1,233.00
6686N5S1A	1"	12	¾" M	31	1,316.00
6686N5S1A IN	1"	12	¾" M	31	1,316.00
6686O5S1A	1"	13	¾" M	33	1,399.00
6686O5S1A IN	1"	13	¾" M	33	1,399.00

Code	Description	No.	Outlets	Lbs	USD
6687C5S1A	1¼"	3	¾" M	17	604.00
6687C5S1A IN	1¼"	3	¾" M	17	604.00
6687D5S1A	1¼"	4	¾" M	18	688.00
6687D5S1A IN	1¼"	4	¾" M	18	688.00
6687E5S1A	1¼"	5	¾" M	19	771.00
6687E5S1A IN	1¼"	5	¾" M	19	771.00
6687F5S1A	1¼"	6	¾" M	21	853.00
6687F5S1A IN	1¼"	6	¾" M	21	853.00
6687G5S1A	1¼"	7	¾" M	23	935.00
6687G5S1A IN	1¼"	7	¾" M	23	935.00
6687H5S1A	1¼"	8	¾" M	24	1,019.00
6687H5S1A IN	1¼"	8	¾" M	24	1,019.00
6687I5S1A	1¼"	9	¾" M	26	1,103.00
6687I5S1A IN	1¼"	9	¾" M	26	1,103.00
6687L5S1A	1¼"	10	¾" M	28	1,184.00
6687L5S1A IN	1¼"	10	¾" M	28	1,184.00
6687M5S1A	1¼"	11	¾" M	29	1,266.00
6687M5S1A IN	1¼"	11	¾" M	29	1,266.00
6687N5S1A	1¼"	12	¾" M	31	1,349.00
6687N5S1A IN	1¼"	12	¾" M	31	1,349.00
6687O5S1A	1¼"	13	¾" M	33	1,432.00
6687O5S1A IN	1¼"	13	¾" M	33	1,432.00

Manifolds and accessories



1. Thermo-electric actuator 6564 series.
2. Thermo-electric actuator with manual open handle, 6563 series.
3. Self-adjusting Universal PEX fitting, 680, 682 series.
4. Inspection wall box, 659 series.
5. Differential by-pass kit, code 668000.

DISTRIBUTION MANIFOLDS



663
Pre-assembled distribution assembly

Pre-assembled distribution assembly consisting of return distribution manifold complete with built-in shut-off valves suitable for thermo-electric actuator and supply distribution manifold complete with manually-adjustable balancing valves.

1" or 1 1/4" NPT inlet ball valves.

Loop Cv: 2.3 (combined supply & return ports).

Max. working pressure: 150 psi.

Max. temperature: 210°F.


Outlet center distance: 2".

Models with "...IN" suffix are built inverted (tubing connections going upward).

Code	Description	No.	Outlets	Lbs	USD
6636C5A	1"	3	3/4" M	17	466.00
6636C5A IN	1"	3	3/4" M	17	466.00
6636D5A	1"	4	3/4" M	18	539.00
6636D5A IN	1"	4	3/4" M	18	539.00
6636E5A	1"	5	3/4" M	19	611.00
6636E5A IN	1"	5	3/4" M	19	611.00
6636F5A	1"	6	3/4" M	21	685.00
6636F5A IN	1"	6	3/4" M	21	685.00
6636G5A	1"	7	3/4" M	23	756.00
6636G5A IN	1"	7	3/4" M	23	756.00
6636H5A	1"	8	3/4" M	24	830.00
6636H5A IN	1"	8	3/4" M	24	830.00
6636I5A	1"	9	3/4" M	26	901.00
6636I5A IN	1"	9	3/4" M	26	901.00
6636L5A	1"	10	3/4" M	28	974.00
6636L5A IN	1"	10	3/4" M	28	974.00
6636M5A	1"	11	3/4" M	29	1,046.00
6636M5A IN	1"	11	3/4" M	29	1,046.00
6636N5A	1"	12	3/4" M	31	1,118.00
6636N5A IN	1"	12	3/4" M	31	1,118.00
6636O5A	1"	13	3/4" M	33	1,191.00
6636O5A IN	1"	13	3/4" M	33	1,191.00
6636P5A	1"	14	3/4" M	35	1,435.00
6636P5A IN	1"	14	3/4" M	35	1,435.00

Code	Description	No.	Outlets	Lbs	USD
6637C5A	1 1/4"	3	3/4" M	17	497.00
6637C5A IN	1 1/4"	3	3/4" M	17	497.00
6637D5A	1 1/4"	4	3/4" M	18	570.00
6637D5A IN	1 1/4"	4	3/4" M	18	570.00
6637E5A	1 1/4"	5	3/4" M	19	642.00
6637E5A IN	1 1/4"	5	3/4" M	19	642.00
6637F5A	1 1/4"	6	3/4" M	21	714.00
6637F5A IN	1 1/4"	6	3/4" M	21	714.00
6637G5A	1 1/4"	7	3/4" M	23	786.00
6637G5A IN	1 1/4"	7	3/4" M	23	786.00
6637H5A	1 1/4"	8	3/4" M	24	860.00
6637H5A IN	1 1/4"	8	3/4" M	24	860.00
6637I5A	1 1/4"	9	3/4" M	26	930.00
6637I5A IN	1 1/4"	9	3/4" M	26	930.00
6637L5A	1 1/4"	10	3/4" M	28	1,004.00
6637L5A IN	1 1/4"	10	3/4" M	28	1,004.00
6637M5A	1 1/4"	11	3/4" M	29	1,075.00
6637M5A IN	1 1/4"	11	3/4" M	29	1,075.00
6637N5A	1 1/4"	12	3/4" M	31	1,150.00
6637N5A IN	1 1/4"	12	3/4" M	31	1,150.00
6637O5A	1 1/4"	13	3/4" M	33	1,222.00
6637O5A IN	1 1/4"	13	3/4" M	33	1,222.00
6637P5A	1 1/4"	14	3/4" M	35	1,399.00
6637P5A IN	1 1/4"	14	3/4" M	35	1,399.00

Construction



1. Supply manifold.
2. Return manifold complete with shut-off valves that can be used with thermo-electric actuators.
3. Pair of shut-off ball valves (complete with port for optional temperature gauge only for 1 1/4" version).
4. End fittings consisting of a 3-way end fitting, automatic air vent valve and drain cock.
5. Pair of mounting brackets for use with series 659 boxes or direct wall installation.
6. Thermo-electric actuator, series 6564 or 6563.
7. Flow meter, code NA669

PUMP AND VALVE TEMPERATURE MIXING UNITS

165 HydroMixer™



Injection pump mixing unit with insulation. Grundfos UPS 15-58 three speed pump. Grundfos Alpha 25-55U pump. Temperature gauges. Shut-off ball valves. Compatible with 5599 Hydrolink series. Male union connections (select top and bottom fitting sets below). Max working pressure: 145 psi. Max. working temperature: 212°F. Power supply: 115 V 50/60 Hz.

Code	Description	Lbs	USD
165600A	Dual line with 15-58 pump on right	21	1,111.00
165610A	Dual line with 15-58 pump on left	21	1,111.00
165602A	Dual line with Alpha pump on right	21	1,356.00
165612A	Dual line with Alpha pump on left	21	1,356.00

166 HydroMixer™



Thermostatic adjustable temperature mixing unit with insulation. Grundfos UPS 15-58 three speed pump. Grundfos Alpha 25-55U pump. Temperature gauges. Shut-off ball valves. Compatible with 5599 Hydrolink series. Male union connections (select top and bottom fitting sets below). Max working pressure: 145 psi. Adjustable range: 80–125°F. Power supply: 115 V 50/60 Hz.

Code	Description	Lbs	USD
166600A	Dual line with 15-58 pump on right	22	1,356.00
166610A	Dual line with 15-58 pump on left	22	1,356.00
166602A	Dual line with Alpha pump on right	22	1,603.00
166612A	Dual line with Alpha pump on left	22	1,603.00

Wall bracket fits 165, 166 and 167 series.



Code	Description	Lbs	USD
165001	Wall bracket	0.1	62.10

Optional differential pressure bypass valve fits 165, 166 and 167 series.



Code	Description	Lbs	USD
519006	Differential pressure by-pass valve	1.0	69.50

167 HydroMixer™



Motorized temperature mixing unit with insulation. Three-point floating 24 VAC actuator for use with separately-sourced outdoor reset controller. Grundfos UPS 15-58 three speed pump. Grundfos Alpha 25-55U pump. Temperature gauges. Shut-off ball valves. Compatible with 5599 Hydrolink series. Male union connections (select top and bottom fitting sets below). Max working pressure: 145 psi. Primary inlet temperature range: 40-212°F. Power supply: 115 V 50/60 Hz. Valve actuator: 24 V AC

Code	Description	Lbs	USD
167600A	Dual line with 15-58 pump on right	23	1,603.00
167610A	Dual line with 15-58 pump on left	23	1,603.00
167602A	Dual line with Alpha pump on right	23	1,849.00
167612A	Dual line with Alpha pump on left	23	1,849.00



Top outlet fitting set fits 165, 166, 167 series. Includes (2) 1 1/4" union nuts, (2) tail pieces and (2) washers. Will not fit bottom inlet thread.

Code	Description	Lbs	USD
NA16069	1" sweat union outlet fittings	1.0	63.70



Bottom Inlet fitting set fits 165, 166, 167 series. Includes (2) 1 1/2" union nuts, (2) tail pieces and (2) washers. Will not fit top outlet thread.

Code	Description	Lbs	USD
NA16169	1" sweat union inlet fittings	1.0	64.50



Top outlet fitting set fits 165, 166, 167 series. Includes (2) 1 1/4" union nuts, (2) tail pieces and (2) washers. Will not fit bottom inlet thread.

Code	Description	Lbs	USD
NA16060	1" NPT female union outlet fittings	1.0	72.30



Bottom Inlet fitting set fits 165, 166, 167 series. Includes (2) 1 1/2" union nuts, (2) tail pieces and (2) washers. Will not fit top outlet thread.

Code	Description	Lbs	USD
NA16160	1" NPT female union inlet fittings	1.0	73.00

FITTINGS FOR DISTRIBUTION MANIFOLDS AND MIXING STATIONS



(680504A shown)

**680
Universal
PEX fittings**

680 series fittings are compatible with any ASTM F876 single layer PEX.
Max. working pressure: 150 psi.
Working temperature range for ASTM F876 PEX piping: 40–180°F.

Code	Description	Compression ring	Lbs	USD
680507	5/16" nominal PEX	Blue	0.2	9.90
680503A	3/8" nominal PEX	Black	0.2	9.90
680504A	1/2" nominal PEX	Blue	0.2	9.90
680555A	5/8" nominal PEX	Black	0.2	9.90
680505A	3/4" nominal PEX	Brass	0.2	9.90



(682530A shown)

**682
Universal
PEX-AL-PEX fittings**

682 series fittings are compatible with any ASTM F1281 multilayer PEX-AL-PEX pipe.
Max. working pressure: 150 psi.
Working temperature range for ASTM F1281 PEX-AL-PEX piping: 40–200°F with tubing rated 200°F.

Code	Description	Lbs	USD
682530A	3/8" nominal PEX-AL-PEX	0.2	10.10
682540A	1/2" nominal PEX-AL-PEX	0.2	10.10
682545A	5/8" nominal PEX-AL-PEX	0.2	10.70
682550A	3/4" nominal PEX-AL-PEX	0.2	19.10



Double nipple for coupling PEX fittings.

Code	Description	Lbs	USD
942550	3/4" x 3/4" thread	0.1	12.20



Wrench for tightening PEX fitting to manifolds.

Code	Description	Lbs	USD
387100	26 mm x 30 mm	1.5	46.40



NA102

Sweat connection fitting fits 1/2" copper.
Max. working pressure: 150 psi.
Working temperature range: 41–250°F.
Chrome plated nut.
Does not work with 668S1 and 172 series.

Code	Description	Lbs	USD
NA10262	1/2" sweat	0.2	11.00



NA103

NPT connection fitting.
Max. working pressure: 150 psi.
Working temperature range: 41–250°F.
Chrome plated nut.
Does not work with 668S1 and 172 series.

Code	Description	Lbs	USD
NA10313	1/2" NPT male	0.2	11.80



386

Cap to plug unused manifold outlets on 592, 663 and 668S1 series.

Code	Description	Lbs	USD
386500	3/4" straight thread	0.2	9.90

BOXES FOR DISTRIBUTION MANIFOLDS



**659
Manifold cabinet**

Housing wall box fits 663 and 668S1 series manifolds.
Adjustable depth: 4 3/8" – 5 1/2".
Powder coated painted 18 gauge sheet metal.
With push-fit clamp.

Code	Description	H	Max Outlets	Lbs	USD
659044	16" width	20"	3	17	330.00
659064	24" width	20"	6	23	361.00
659084	32" width	20"	10	30	425.00
659104	40" width	20"	13	37	487.00
659124	48" width"	20"	17	44	552.00

Rough opening dimensions

THERMO ELECTRIC ACTUATORS FOR MANIFOLDS AND VALVES



**6563
TwisTop™**

TwisTop™ thermo-electric actuator. Twist the top to manually open. Power supply: 24 V AC/DC. Initial current draw: ≤ 250 mA. Power consumption: 3 W. Rating of micro-switch contacts: 5 A (24 V). 31.5" wire lead connection. US Patent 7,617,989 B2.




6564

Low current draw thermo-electric actuator. Hermetically sealed for upside down installation. Pop-up feature. Power supply: 24 V AC/DC. Initial current draw: ≤ 250 mA. Power consumption: 3 W. Rating of micro-switch contacts: 5 A (24 V). 31.5" wire lead connection.


Code	Description	Lbs	USD
656344	24 V AC/DC	0.4	108.00
656354	24 V AC/DC with micro-switch	0.4	127.00
656354R	24 V AC/DC with micro-switch REHAU	0.4	140.00

Code	Description	Lbs	USD
656404	24 V AC/DC	0.4	80.40
656414	24 V AC/DC with micro-switch	0.4	102.00


Simply twist to manually open actuator (and activate micro switch on 656354). When power is applied, it returns to Auto position.




Green ring indicates valve is open.



Construction details



Up to 12 actuators per 40 VA transformer.



ACCESSORIES



Replacement balance/flow meter fits 668S1 series manifold.
Flow meter scale: ¼ — 2 gpm.

Code	Description	Lbs	USD
F69600	Fits 668S1 supply manifold	0.2	28.50



Replacement shut-off valve fits 668S1 series manifold.

Code	Description	Lbs	USD
F69590	Fits 668S1 return manifold	0.3	22.70



Replacement balancing valve fits 668 series manifold.

Code	Description	Lbs	USD
F69184	Fits 668 supply manifold	0.2	19.70



Replacement shut-off valve fits 668 & 663 series manifold.

Code	Description	Lbs	USD
69122 CST	Fits 668 & 663 return manifold	0.3	12.60



Replacement balancing valve for 663 series manifold.

Code	Description	Lbs	USD
R69176	Fits 663 supply manifold	0.3	19.40



NA669

Flow meter fits manifolds.
Max. temperature: 180°F (669050).
Max. temperature: 210°F (NA669 series).
¾" straight male x ¾" straight female connections.

Code	Description	Lbs	USD
NA669150	¼ — 1 GPM High Temp.	0.3	33.50
NA669250	½ — 2 GPM High Temp.	0.3	33.50



White replacement knob fits 663 and 668S1 series manifolds.

Code	Description	Lbs	USD
449000	Knob	0.5	9.90

5020



Replacement air vent fits radiant manifolds.
Brass body.
Hygroscopic safety air vent cap.
Max. working pressure: 150 psi.
Max discharge pressure: 32 psi.
Max. working temperature: 250°F.

Code	Description	Lbs	USD
502043 CST	½" straight thread	0.6	23.80




Plastic replacement/test cap fits 5020 series.

Code	Description	Lbs	USD
R56214	Vent cap	0.1	2.10

675



Snap-on thermometer directly to PEX, PEX-AL-PEX and copper piping.
Box of 10 comes with 1 syringe of thermo conductive paste.



Code	Description	Lbs	USD
675900A	¾" & 5/8" PEX & ½" copper	0.2	10.50
R69413	Syringe of thermo conductive paste	0.1	7.40



688

Temperature gauge with well pocket fitting for inserting into manifold ball valves.
Working Temperature range: 30—210°F.
Face dial diameter: 2".

Code	Description	Lbs	USD
R39591	Replacement gauge	0.1	25.70
688003A	Gauge with pocket well	0.2	39.30
NA10498	Replacement pocket well, low lead	0.1	3.90
F67037	O-ring fits NA10498	0.1	0.80


CUTTING-EDGE INNOVATION IN TEMPERATURE MIXING



Caleffi mixing valves lead the way. From 3/8" under-sink scald protection valves to 3" flanged digital master mixing valves, we have a full offering for residential and commercial applications. **Over 50 years of innovation and global experience** assure high quality and proven reliability. A wide selection of double union connection types work with copper, iron, steel and non-metallic pipes. The valves comply with the necessary standards and codes for the U.S. and Canada. **CALEFFI GUARANTEED.**



MIXING VALVES FOR PLUMBING AND HYDRONICS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions
[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

- Thermostatic mixing valves for plumbing and hydronics
- High flow thermostatic mixing valves for plumbing and hydronics
- Scald protection thermostatic mixing valves for plumbing
- Electronic mixing valve for plumbing
- Thermostatic mixing valve kits for domestic water heaters

THERMOSTATIC MIXING VALVES FOR PLUMBING AND HYDRONICS



521 MixCal™ sweat

Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body. Locking set point knob. Max. working pressure: 200 psi. Max. inlet temperature: 200°F. Adjustable range: 85–150°F. Min. flow for optimum performance: 1.0 gpm. (0 gpm with recirculation) Max flow for optimum performance: 14 gpm.

Code	Description	Cv	Lbs	USD
521409A	1/2" sweat union	3	2.4	194.00
521409AC	1/2" sweat union, check valves	3	2.4	215.00
521509A	3/4" sweat union	3	2.4	203.00
521509AC	3/4" sweat union, check valves	3	2.4	233.00
521609A	1" sweat union	3	2.4	242.00
521609AC	1" sweat union, check valves	3	2.4	270.00



521 MixCal™ NPT

Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body. Locking set point knob. Max. working pressure: 200 psi. Max. inlet temperature: 200°F. Adjustable range: 85–150°F. Min. flow for optimum performance: 1.0 gpm. (0 gpm with recirculation) Max flow for optimum performance: 14 gpm.

Code	Description	Cv	Lbs	USD
521400A	1/2" NPT male union	3	2.4	203.00
521400AC	1/2" NPT male union, check valves	3	2.4	223.00
521500A	3/4" NPT male union	3	2.4	212.00
521500AC	3/4" NPT male union, check valves	3	2.4	242.00
521600A	1" NPT male union	3	2.4	251.00
521600AC	1" NPT male union, check valves	3	2.4	280.00



521 MixCal™ press

Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body. Locking set point knob. Max. working pressure: 200 psi. Max. inlet temperature: 200°F. Adjustable range: 85–150°F. Min. flow for optimum performance: 1.0 gpm. (0 gpm with recirculation) Max flow for optimum performance: 14 gpm.

Code	Description	Cv	Lbs	USD
521406A	1/2" Press union	3	2.4	207.00
521406AC	1/2" Press union, check valves	3	2.5	227.00
521506A	3/4" Press union	3	2.4	212.00
521506AC	3/4" Press union, check valves	3	2.5	263.00
521606A	1" Press union	3	2.6	256.00
521606AC	1" Press union, check valves	3	3.1	279.00



521 MixCal™ PEX

Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body. Locking set point knob. Max. working pressure: 200 psi. Max. inlet temperature: 200°F. Adjustable range: 85–150°F. Min. flow for optimum performance: 1.0 gpm. (0 gpm with recirculation) Max flow for optimum performance 14 gpm. PEX crimp: ASTM F1807 PEX expansion: ASTM F1960

Code	Description	Cv	Lbs	USD
521407A	1/2" PEX crimp union	3	2.4	194.00
521407AC	1/2" PEX crimp union, check valves	3	2.9	215.00
521408A	1/2" PEX expansion union	3	2.4	194.00
521408AC	1/2" PEX expansion union, check valves	3	2.9	215.00
521507A	3/4" PEX crimp union	3	2.4	203.00
521507AC	3/4" PEX crimp union, check valves	3	2.9	233.00
521508A	3/4" PEX expansion union	3	2.4	203.00
521508AC	3/4" PEX expansion union, check valves	3	2.9	233.00
521607A	1" PEX crimp union	3	2.4	242.00
521607AC	1" PEX crimp union, check valves	3	2.9	270.00
521608A	1" PEX expansion union	3	2.4	242.00
521608AC	1" PEX expansion union, check valves	3	2.9	270.00

Meets requirements of NSF/ANSI 372-2011. Complies with ASSE 1017, CSA B125.3, UPC, IPC, Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

THERMOSTATIC MIXING VALVES FOR PLUMBING AND HYDRONICS



521 MixCal™ sweat

Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body, with gauge. Locking set point knob. Max. working pressure: 200 psi. Max. inlet temperature: 200°F. Adjustable range: 85 – 150°F. Min. flow for optimum performance: 1.0 gpm. (0 gpm with recirculation) Max flow for optimum performance: 14 gpm. Optional Gauge scale: 30–210°F.

Code	Description	Cv	Lbs	USD
521419A	1/2" sweat union	3	2.9	231.00
521419AC	1/2" sweat union, check valves	3	2.9	250.00
521519A	3/4" sweat union	3	2.9	239.00
521519AC	3/4" sweat union, check valves	3	2.9	268.00
521619A	1" sweat union	3	2.9	279.00
521619AC	1" sweat union, check valves	3	2.9	308.00



521 MixCal™ NPT

Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body with gauge. Locking set point knob. Max. working pressure: 200 psi. Max. inlet temperature: 200°F. Adjustable range: 85 – 150°F. Min. flow for optimum performance: 1.0 gpm. (0 gpm with recirculation) Max flow for optimum performance: 14 gpm. Optional Gauge scale: 30–210°F.

Code	Description	Cv	Lbs	USD
521410A	1/2" NPT male union	3	2.9	239.00
521410AC	1/2" NPT male union, check valves	3	2.9	258.00
521510A	3/4" NPT male union	3	2.9	249.00
521510AC	3/4" NPT male union, check valves	3	2.9	276.00
521610A	1" NPT male union	3	2.9	289.00
521610AC	1" NPT male union, check valves	3	2.9	316.00



521 MixCal™ press

Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body with gauge. Locking set point knob. Max. working pressure: 200 psi. Max. inlet temperature: 200°F. Adjustable range: 85 – 150°F. Min. flow for optimum performance: 1.0 gpm. (0 gpm with recirculation) Max flow for optimum performance: 14 gpm. Optional Gauge scale: 30–210°F.

Code	Description	Cv	Lbs	USD
521416A	1/2" Press union	3	2.9	243.00
521416AC	1/2" Press union, check valves NEW	3	3.0	261.00
521516A	3/4" Press union	3	2.9	249.00
521516AC	3/4" Press union, check valves	3	3.0	298.00
521616A	1" Press union	3	3.1	293.00
521616AC	1" Press union, check valves	3	3.5	315.00



521 MixCal™ PEX

Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body with gauge. Locking set point knob. Max. working pressure: 200 psi. Max. inlet temperature: 200°F. Adjustable range: 85 – 150°F. Min. flow for optimum performance: 1.0 gpm. (0 gpm with recirculation) Max flow for optimum performance: 14 gpm. Optional Gauge scale: 30–210°F. PEX crimp: ASTM F1807. PEX expansion: ASTM F1960.

Code	Description	Cv	Lbs	USD
521417A	1/2" PEX crimp union	3	2.5	231.00
521417AC	1/2" PEX crimp union, checks	3	2.9	250.00
521418A	1/2" PEX expansion union	3	2.5	231.00
521418AC	1/2" PEX expansion union, checks	3	2.9	250.00
521517A	3/4" PEX crimp union	3	2.5	239.00
521517AC	3/4" PEX crimp union, checks	3	2.9	268.00
521518A	3/4" PEX expansion union	3	2.5	239.00
521518AC	3/4" PEX expansion union, checks	3	2.9	268.00
521617A	1" PEX crimp union	3	2.5	279.00
521617AC	1" PEX crimp union, checks	3	2.9	308.00
521618A	1" PEX expansion union	3	2.5	279.00
521618AC	1" PEX expansion union, checks	3	2.9	308.00

Meets requirements of NSF/ANSI 372-2011. Complies with ASSE 1017, CSA B125.3, UPC, IPC, Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

THERMOSTATIC MIXING VALVES FOR PLUMBING AND HYDRONICS



Point of distribution mixed temperature gauge adaptor fits 1" male union thread mixing valves.
Removable gauge fits into pocket well.
Dual scale: 30–210°F (0 – 100°C).
Gauge accuracy: ± 6°F.
Gauge dial: 2" diameter.
Certified: Low-lead brass.

Code	Description	Lbs	USD
NA10328	½" sweat with gauge	0.4	57.60
NA10056	¾" sweat with gauge	0.4	63.30
NA10058	1" sweat with gauge	0.4	69.50
NA10358	1" union thread with gauge	0.4	36.20
688003A	Replacement gauge with pocket well	0.5	39.30
R39591	Replacement gauge	0.1	25.70
NA10498	Pocket well, plated	0.1	3.90

ACCESSORIES



Replacement check valves for 521 (AC models).

Code	Description	Lbs	USD
NA10405	Repl. check for 521 PEX, press fittings	0.1	2.40
R39204	Repl. check for 521 sweat, NPT fittings	0.1	3.40



Conical inlet filter for 521 mixing valves.

Code	Description	Lbs	USD
F52429	Conical filter for 521 mixing valve	0.1	4.90




521 MixCal™ Body

Replacement body (1/2", 3/4", 1" valve).
See fitting selection table in Section 8.

Code	Description	Cv	Lbs	USD
521101A	1" union body	3	1.9	149.00

Construction details



HIGH FLOW THERMOSTATIC MIXING VALVES FOR PLUMBING AND HYDRONICS



5231 MixCal+™ Body

Replacement body includes nuts and washers.
See fitting selection table in Section 8.

Code	Description	Min - Max Flow (gpm)	Cv	Lbs	USD
523179A	For 1" and 1¼" sizes	4.4 to 40	7.6	5.0	1,096.00
523199A	For 1½" and 2" sizes	8.8 to 70	14.2	14.2	1,569.00



5231 MixCal+™ Sweat

Adjustable thermostatic mixing valve for domestic water systems and radiant hydronic systems.
DZR low lead brass body.
Max. working pressure: 200 psi.
Max. inlet temperature: 195°F.
Adjustable range: 95–150°F.
Gauge scale: 30–210°F.
Gauge accuracy: ± 6°F.
Gauge dial: 2" diameter.

Code	Description	Min - Max Flow (gpm)	Cv	Lbs	USD
523177A	1¼" sweat union	4.4 to 40	7.6	9.0	1,371.00

Meets requirements of NSF/ANSI 372-2011. Complies with ASSE 1017, CSA B125.3, UPC, IPC, Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

HIGH FLOW THERMOSTATIC MIXING VALVES FOR PLUMBING AND HYDRONICS



5231 MixCal+™ sweat

Adjustable thermostatic mixing valve for domestic water systems and radiant hydronic systems.
DZR low lead brass body.
Max. working pressure: 200 psi.
Max. inlet temperature: 195°F.
Adjustable range: 95—150°F.

Code	Description	Min - Max Flow (gpm)	Cv	Lbs	USD
523168A	1" sweat union	4.4 to 40	7	7	1,220.00
523178A	1¼" sweat union	4.4 to 40	7.6	7	1,275.00
523188A	1½" sweat union	8.8 to 70	13	17	1,916.00
523198A	2" sweat union	8.8 to 70	14	18	2,014.00



Point of distribution mixed temperature gauge adaptor fits MixCal+™ High Flow 5231 series mixing valves.
Removable gauge fits into pocket well.
Dual scale: 30—210°F (0—100°C).
Gauge accuracy: ± 6°F.
Gauge dial: 2" diameter.
Certified: Low-lead brass.

Code	Description	Lbs	USD
NA10315	1¼" sweat	0.5	140.00
NA10476	1" and 1¼" male x female union	3.0	160.00
NA10461	1½" and 2" male x female union	4.0	275.00
688003A	Replacement gauge with pocket well	0.2	39.30
R39591	Replacement gauge	0.1	25.70



5231 MixCal+™ NPT

Adjustable thermostatic mixing valve for domestic water systems and radiant hydronic systems.
DZR low lead brass body.
Max. working pressure: 200 psi.
Max. inlet temperature: 195°F.
Adjustable range: 95—150°F.

Code	Description	Min - Max Flow (gpm)	Cv	Lbs	USD
523160A	1" NPT male union	4.4 to 40	7	7	1,233.00
523170A	1¼" NPT male union	4.4 to 40	7.6	7	1,332.00
523180A	1½" NPT male union	8.8 to 70	13	17	1,964.00
523190A	2" NPT male union	8.8 to 70	14	18	2,065.00



Inlet check valve assembly for installing on inlet union tail pieces of 5231 mixing valves.
Stainless steel body. No Lead. Ordered separately, field installed. Assembly examples shown below.



523177A shown with (2) NA10366 523178A shown with (2) NA10366


Code	Description	Lbs	USD
NA10366	Check valve assembly 1" and 1¼"	1.0	100.00
NA10367	Check valve assembly 1½" & 2"	1.5	221.00



5231 MixCal+™ press

Adjustable thermostatic mixing valve for domestic water systems and radiant hydronic systems.
DZR low lead brass body.
Max. working pressure: 200 psi.
Max. inlet temperature: 195°F.
Adjustable range: 95—150°F.

Code	Description	Min - Max Flow (gpm)	Cv	Lbs	USD
523166A	1" press union	4.4 to 40	7	7	1,298.00
523176A	1¼" press union	4.4 to 40	7.6	7	1,358.00
523186A	1½" press union	8.8 to 70	13	17	2,087.00
523196A	2" press union	8.8 to 70	14.2	18	2,321.00



THERMOSTATIC MIXING VALVES FOR PLUMBING AND HYDRONICS



520 AngleMix™ sweat

Body is DZR low lead brass with gauge.
 Adjustment temperature range: 95°F — 150°F.
 Max. body pressure rating (static): 150 psi.
 Max. working pressure (dynamic): 75 psi.
 Max. inlet temperature: 195°F.
 Gauge scale: 30—210°F.
 Flow (1/2" and 3/4" valves) 0.5 to 9 GPM.
 Flow (1" valves) 1 to 16 GPM.



520 AngleMix™ press

Body is DZR low lead brass with gauge.
 Adjustment temperature range: 95°F — 150°F.
 Max. body pressure rating (static): 150 psi.
 Max. working pressure (dynamic): 75 psi.
 Max. inlet temperature: 195°F.
 Gauge scale: 30—210°F.
 Flow (1/2" and 3/4" valves) 0.5 to 9 GPM.
 Flow (1" valves) 1 to 16 GPM.



Code	Description	Cv	Lbs	USD
520419A	1/2" sweat union	2	1.7	231.00
520419AC	1/2" sweat union, checks	2	1.8	250.00
520519A	3/4" sweat union	2	2	249.00
520519AC	3/4" sweat union, checks	2	2.1	276.00
520619A	1" sweat union	3.5	3.7	334.00
520619AC	1" sweat union, check valves	3.5	3.8	361.00

Code	Description	Cv	Lbs	USD
520416A	1/2" press union	2	1.8	243.00
520416AC	1/2" press union, check valves NEW	2	1.8	260.00
520516A	3/4" press union	2	2	239.00
520516AC	3/4" press union, check valves	2	2.1	298.00
520616A	1" press union	3.5	3.7	348.00
520616AC	1" press union, check valves	3.5	3.9	377.00



520 AngleMix™ NPT

Body is DZR low lead brass with gauge.
 Adjustment temperature range: 95°F — 150°F.
 Max. body pressure rating (static): 150 psi.
 Max. working pressure (dynamic): 75 psi.
 Max. inlet temperature: 195°F.
 Gauge scale: 30—210°F.
 Flow (1/2" and 3/4" valves) 0.5 to 9 GPM.
 Flow (1" valves) 1 to 16 GPM.



Code	Description	Cv	Lbs	USD
520410A	1/2" NPT male union	2	1.7	239.00
520410AC	1/2" NPT male union, checks	2	1.8	258.00
520510A	3/4" NPT male union	2	2	249.00
520510AC	3/4" NPT male union, checks	2	2.1	276.00
520610A	1" NPT male union	3.5	3.9	343.00
520610AC	1" NPT male union, check valves	3.5	4	371.00

Construction details


Anti-scale materials The material used in the construction of the Caleffi AngleMix 520 series thermostatic mixing valve reduces jamming caused by lime deposits. All the working parts such as shutter, seats and slide guides are made of a special anti-scale polymer material, with a low friction coefficient, assuring long term performance.



520 AngleMix™ Body

Replacement body.
 See fitting selection table in Section 8.

Code	Description	Cv	Lbs	USD
520051A	1" union body (1/2", 3/4" valves)	2	2	149.00
520061A	1 1/4" union body (1" valves)	3.5	4	208.00



Meets requirements of NSF/ANSI 372-2011. Complies with ASSE 1017, CSA B125.3, UPC, IPC, Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

SCALD PROTECTION THERMOSTATIC MIXING VALVES FOR PLUMBING



5212 SinkMixer™
4-way Scald Protection Point-of-use

Thermostatic mixing valve for under sink and under counter applications where the user must be protected from the danger of scalding caused by excessively hot water. Temperature adjustment range: 95–120°F. Cold inlet temperature: Min. 39°F; Max. 85°F. Hot inlet temperature: Min. 120°F; Max. 195°F. Min flow for optimum performance 0.35 gpm. Max flow for optimum performance 2.3 gpm. Complies with NSF/ANSI/CAN 61.



SinkMixer™ Replacement check valve/filter kit. Includes two checks and two filters.

Code	Description	Lbs	USD
F0001270	Replacement check valve/filter kit	0.1	6.60



SinkMixer™ 5-pack plug/nut fitting kit. The cold outlet port plug is for single-pipe, mixed-water fixtures.

Code	Description	Lbs	USD
NA10741	5-pack plug/nut fitting kit	0.2	16.60


Code	Description	Cv	Lbs	USD
521201A	3/8" compression	0.52	1	110.00
521201AP	3/8" compression, plug/fittings	0.52	1.1	112.00




5213 TubMixer™
High Flow Scald Protection

Adjustable thermostatic high-flow point-of-use mixing valve for Roman Tubs and other high flow fixtures. Locking set point knob. Complete with check valves on both hot and cold inlets. Low-lead brass body. Max. working pressure: 150 psi. Max. inlet temperature: 185°F. Adjustable range: 85–120°F. Temperature control: ±3°F. Min. flow for optimum performance: 0.5 gpm. Max flow for optimum performance: 9 gpm. Cv = 2

Construction details SinkMixer™



Application diagram TubMixer™



Code	Description	Lbs	USD
521333A	3/8" compression union	2	132.00
521347A	1/2" PEX crimp union	2	132.00
521348A	1/2" PEX expansion union	2	132.00
521342A	1/2" NPT male union	2	132.00
521349A	1/2" sweat union	2	132.00
521357A	3/4" PEX crimp union	2	139.00
521358A	3/4" PEX expansion union	2	139.00
521352A	3/4" NPT male union	2	139.00
521359A	3/4" sweat union	2	139.00
521367A	1" PEX crimp union	2	215.00
521368A	1" PEX expansion union	2	215.00
521362A	1" NPT male union	2	223.00
521369A	1" sweat union	2	215.00
521301A*	Replacement body, no fittings	1.5	119.00

*See fitting selection table in Section 8.

Meets requirements of NSF/ANSI 372-2011. Complies with ASSE 1070, CSA B125.3, UPC, IPC, Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

ELECTRONIC MIXING VALVE FOR PLUMBING



6000 LEGIOMIX® sweat

Electronic mixing valve with optional selectable programs for thermal disinfection of hot water recirculation system to kill Legionella bacteria.

Power: 24 VAC +/- 10% - 50/60 Hz - 6 VA. 115/24 VAC transformer included.
Adjustment temperature range: 70 — 185°F.
Disinfection temperature range: 100 — 185°F.
Max body pressure rating (static): 230 psi.
Max operating pressure: 150 psi.
Max. inlet temperature: 212°F.
Protection class: IP 54 (controller).



Code	Description	Cv	Lbs	USD
600059A	¾" sweat union	9.7	5.1	2,738.00
600069A 001	1" sweat union, ¾" body	9.7	5.3	2,885.00
600069A	1" sweat union	21	7.3	3,030.00
600079A	1¼" sweat union	24	8.2	3,082.00
600089A	1½" sweat union	34	21	3,498.00
600099A	2" sweat union	48	22	3,588.00



6000 LEGIOMIX® NPT

Electronic mixing valve with optional selectable programs for thermal disinfection of hot water recirculation system to kill Legionella bacteria.

Power: 24 VAC +/- 10% - 50/60 Hz - 6 VA. 115/24 VAC transformer included.
Adjustment temperature range: 70 — 185°F.
Disinfection temperature range: 100 — 185°F.
Max body pressure rating (static): 230 psi.
Max operating pressure: 150 psi.
Max. inlet temperature: 212°F.
Protection class: IP 54 (controller).



Code	Description	Cv	Lbs	USD
600054A	¾" NPT male union	9.7	5.1	2,767.00
600064A 001	1" NPT male union, ¾" body	9.7	5.3	2,905.00
600064A	1" NPT male union	21	7.3	3,041.00
600074A	1-1/4" NPT male union	24	8.2	3,136.00
600084A	1½" NPT male union	34	21	3,541.00
600094A	2" NPT male union	48	22	3,637.00

Meets requirements of NSF/ANSI 372-2011 and complies with ASSE 1017, CSA B125.3, UPC, IPC, Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes. Meets requirements of CSA Z317.1 Special Requirements For Plumbing Installations In Health Care Facilities.



6000 LEGIOMIX® press

Electronic mixing valve with optional selectable programs for thermal disinfection of hot water recirculation system to kill Legionella bacteria.

Power: 24 VAC +/- 10% - 50/60 Hz - 6 VA. 115/24 VAC transformer included.
Adjustment temperature range: 70 — 185°F.
Disinfection temperature range: 100 — 185°F.
Max body pressure rating (static): 230 psi.
Max operating pressure: 150 psi.
Max. inlet temperature: 212°F.
Protection class: IP 54 (controller).



Code	Description	Cv	Lbs	USD
600056A	¾" press union	9.7	5.1	2,885.00
600066A 001	1" press union, ¾" body	9.7	5.2	2,994.00
600066A	1" press union	21	7.3	3,104.00
600076A	1¼" press union	24	8.2	3,157.00
600086A	1½" press union	34	21	3,657.00
600096A	2" press union	48	22	3,873.00



6000 LEGIOMIX® flange

Electronic mixing valve with optional selectable programs for thermal disinfection of hot water recirculation system to kill Legionella bacteria.

Power: 24 VAC +/- 10% - 50/60 Hz - 6 VA. 115/24 VAC transformer included.
Adjustment temperature range: 70 — 185°F.
Disinfection temperature range: 100 — 185°F.
Max body pressure rating (static): 230 psi.
Max operating pressure: 150 psi.
Max. inlet temperature: 212°F.
Protection class: IP 54 (controller).

Code	Description	Cv	Lbs	USD
600060A	2½" ANSI 150 flanges	105	30	13,070.00
600080A	3" ANSI 150 flanges	120	42	13,835.00

The LEGIOMIX® includes:
three-way ball valve
3-wire floating control actuator controller/user interface with DIN rail mounting bracket
mixed outlet temperature sensor/probe
return temperature sensor/probe
mixed outlet temperature gauge

Size	Recommended Flow Rates (gpm/lpm)						
	¾"	1"	1¼"	1½"	2"	2½"	3"
Minimum flow*	2.2 / 8.3	3.1 / 11.7	4.4 / 16.6	6.6 / 25	8.8 / 33.3	17.0 / 64	22.0 / 83.3
Design flow**	27 / 102	58 / 220	66 / 250	93 / 352	131 / 495	288 / 1,090	329 / 1,245
Flow at 20 psid	43 / 172	94 / 356	107 / 405	152 / 575	215 / 814	470 / 1,780	537 / 2,033
Cv	9.7	21	24	34	48	105	120

*To ensure stable operation and ± 3° F accuracy. Minimum flow rate is 0 gpm when recirculation flow rate is greater than or equal to the valve size minimum flow rating.
**Suggested maximum flow rate for optimum modulating control (at 7.5 psid pressure drop).

ACCESSORIES AND REPLACEMENT



Replacement mixed temp sensor.

Code	Description	Lbs	USD
F69807	Fits 1" and 1¼" valve	1.0	64.40



Replacement mixed temp sensor.

Code	Description	Lbs	USD
F69804	Fits 1½" and 2" valve	1.0	91.60



Replacement recirculation sensor.

Code	Description	Lbs	USD
F69591	Replacement recirculation sensor	1.0	81.70



Replacement controller.

Code	Description	Lbs	USD
F000962	Replacement controller	1.5	1,835.00



Replacement actuator.

Code	Description	Lbs	USD
645114	Replacement actuator	1.0	459.00



Replacement transformer.

Code	Description	Lbs	USD
NA10703	Foot-mount transformer 50 VA	3	69.50
NA10759	Plug-in transformer 20 VA	1	39.40

NEW



LEGIOMIX® parts bag assembly.

Code	Description	Lbs	USD
R0001397	Bag assembly	0.2	84.00



Replacement temp gauge.

Code	Description	Lbs	USD
R19101	Replacement temp gauge	0.3	22.30



Modbus-to-BACnet gateway
Converts LEGIOMIX® controller Modbus (RS-485 serial) output communication to BACnet IP or MSTP communication.

Code	Description	Lbs	USD
755052	Modbus-to-BACnet gateway	1.2	1,949.00



Inlet check valve assembly for installing on 6000 Series valve body (if required). Stainless steel body. No Lead. Ordered separately, field installed. 2 required per valve.

Code	Description	Lbs	USD
NA10366	Check valve assembly 1" and 1¼"	1.0	95.00
NA10367	Check valve assembly 1½" & 2"	1.5	210.00



Replacement body includes gauge adapter assembly.
See fitting selection table in Section 8.

Code	Description	Lbs	USD
NA10758	Body, gauge adapter (¾" valve)	3.5	470.00
NA10615	Body, gauge adapter (1", 1¼" valves)	5.1	530.00
NA10616	Body, gauge adapter (1½", 2" valves)	10.5	777.00

Replacement controller battery.



Code	Description	Lbs	USD
F69888	Replacement controller battery	0.1	46.10

ELECTRONIC MIXING VALVE FOR PLUMBING




6000 LEGIOMIX® Station

Electronic mixing valve pre-packaged in a convenient wall mount configuration. 100% factory tested for plug-and-play in a packaged wall mount configuration.

Station assembly includes pre-piped 3-way mixing valve with union connections, serviceable check valves, a recirculation connection and isolation valves for fast and simple installation, all mounted on welded, powder-coat painted steel strut. The LEGIOMIX® controller/user interface with DIN rail mounting bracket is pre-mounted and pre-wired and includes a return water temperature sensor. Simply wall mount the assembly, hook up the hot and cold water supplies, the mixed outlet and the recirculation circuit. Plug in 120/24 VAC transformer with 20 ft cable included.

Code	Description	Cv	Lbs	USD
600066AS	1" copper wall-mount station	7.8	130	9,633.00
600076AS	1¼" copper wall-mount station	9	148	10,946.00
600086AS	1½" copper wall-mount station	20	219	13,853.00
600096AS	2" copper wall-mount station	38	248	15,724.00
600060AS	2½" copper wall-mount station	43	250	17,983.00

Construction details



THERMOSTATIC MIXING VALVE KIT FOR DOMESTIC WATER HEATERS



520 TankMixer™

Adjustment temperature range: 95°F - 150°F.
 Max. working pressure (static): 150 psi.
 Max. working pressure (dynamic): 75 psi.
 Max. inlet temperature: 195°F.
 Minimum flow for optimum performance: 0.5 GPM (0 GPM with recirculation).
 Max flow for optimum performance: 9 gpm.
 Tank: 3/4" NPT female union connections.
 System: 3/4" NPT M, press or sweat union connections.



520 TankMixer™ with gauge

Adjustment temperature range: 95°F - 150°F.
 Max. working pressure (static): 150 psi.
 Max. working pressure (dynamic): 75 psi.
 Max. inlet temperature: 195°F.
 Gauge scale: 30—210°F.
 Gauge accuracy: ± 6°F.
 Gauge dial: 2" diameter.
 Minimum flow for optimum performance: 0.5 GPM (0 GPM with recirculation).
 Max flow for optimum performance: 9 gpm.
 Tank: 3/4" NPT female union connections.
 System: 3/4" NPT M, press or sweat union connections.

Code	Description	Cv	Lbs	USD
520500AX	3/4" NPT male union system connections	2	2.4	279.00
520506AX	3/4" press union system connections	2	2.4	318.00
520509AX	3/4" sweat union system connections	2	2.4	269.00

Code	Description	Cv	Lbs	USD
520510AX	3/4" NPT male union system connections	2	2.9	318.00
520516AX	3/4" press union system connections	2	2.9	358.00
520519AX	3/4" sweat union system connections	2	2.9	309.00




520 TankMixer™ Body


Replacement body.
 See fitting section table in Section 8.

Code	Description	Cv	Lbs	USD
520051A	1" male union connection	2	2.0	149.00

Construction details



Application diagram



Meets requirements of NSF/ANSI 372-2011. Certified to ASSE 1017, CSA B125.3, UPC, IPC, Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

SET IT AND FORGET IT


NO BALANCING TOOLS REQUIRED



The **ThermoSetter™** thermal balancing valve maintains precise temperature in recirculation return piping using state-of-the-art modulating control. **Setup is simple** and safe with an easy-to-read, lockable temperature adjustment dial. The integral drywell is versatile, suitable for a local slide-in temperature gauge or remote sensor bulb. Models with bypass cartridges are available for projects that are designed for **thermal disinfection to control Legionella bacteria. CALEFFI GUARANTEED.**



BALANCING VALVES FOR PLUMBING AND HYDRONICS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions

[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

- Static balancing valve with built-in flowmeter for plumbing
- Static balancing valve with built-in flowmeter for hydronics
- Dynamic balancing valves for plumbing and hydronics
- Static balancing valves, fixed orifice, for plumbing and hydronics
- Static balancing valves, variable orifice, for plumbing and hydronics
- Thermal balancing valves for plumbing
- Dynamic balancing valves for hydronics
- Y-strainer with ball valve for hydronics
- Drain valves and pt ports

STATIC BALANCING VALVES WITH BUILT-IN FLOWMETER FOR PLUMBING



132 QuickSetter+™ sweat

Balancing valve with flow meter.
Direct reading of flow rate.
DZR low-lead brass.
Inlet flow check valve.



Code	Description	Flow scale (gpm)	Lbs	USD
132439AFC	½" sweat union	0.5–1.75	1.8	257.00
132539AFC	¾" sweat union	0.5–1.75	2.0	268.00
132639AFC	1" sweat union	0.5–1.75	2.4	296.00
132459AFC	½" sweat union	2.0–7.0	1.8	257.00
132559AFC	¾" sweat union	2.0–7.0	2.0	268.00
132659AFC	1" sweat union	2.0–7.0	2.4	296.00



132 QuickSetter+™ press

Balancing valve with flow meter.
Direct reading of flow rate.
DZR low-lead brass.
Inlet flow check valve.
Dual scale: 30 – 210°F (0 – 100°C).
Gauge accuracy: ± 6°F.



Code	Description	Flow scale (gpm)	Lbs	USD
132438AFC	½" sweat union	0.5–1.75	2.4	295.00
132538AFC	¾" sweat union	0.5–1.75	2.2	307.00
132638AFC	1" sweat union	0.5–1.75	2.8	332.00
132458AFC	½" sweat union	2.0–7.0	2.4	295.00
132558AFC	¾" sweat union	2.0–7.0	2.2	307.00
132658AFC	1" sweat union	2.0–7.0	2.8	332.00



132 QuickSetter+™ press

Balancing valve with flow meter.
Direct reading of flow rate.
DZR low-lead brass.
Inlet flow check valve.



Code	Description	Flow scale (gpm)	Lbs	USD
132436AFC	½" press union	NEW 0.5–1.75	1.8	296.00
132536AFC	¾" press union	0.5–1.75	1.8	308.00
132636AFC	1" press union	0.5–1.75	2.2	341.00
132456AFC	½" press union	NEW 2.0–7.0	1.8	296.00
132556AFC	¾" press union	2.0–7.0	1.8	308.00
132656AFC	1" press union	2.0–7.0	2.2	341.00



132 QuickSetter+™ PEX

Balancing valve with flow meter.
Direct reading of flow rate.
DZR low-lead brass.
Inlet flow check valve.
Dual scale: 30 – 210°F (0 – 100°C).
Gauge accuracy: ± 6°F.



Code	Description	Flow scale (gpm)	Lbs	USD
132437AFC	½" press union	NEW 0.5–1.75	1.8	339.00
132537AFC	¾" press union	0.5–1.75	2.2	353.00
132637AFC	1" press union	0.5–1.75	2.6	381.00
132457AFC	½" press union	NEW 2.0–7.0	1.8	339.00
132557AFC	¾" press union	2.0–7.0	2.2	353.00
132657AFC	1" press union	2.0–7.0	2.6	381.00



132 QuickSetter+™ PEX

Balancing valve with flow meter.
Direct reading of flow rate.
DZR low-lead brass.
Inlet flow check valve.
PEX crimp: ASTM F1807
PEX expansion: ASTM F1960



Code	Description	Flow scale (gpm)	Lbs	USD
132434AFC	½" PEX crimp union	0.5–1.75	1.8	257.00
132432AFC	½" PEX expansion union	0.5–1.75	1.8	257.00
132534AFC	¾" PEX crimp union	0.5–1.75	2.0	268.00
132532AFC	¾" PEX expansion union	0.5–1.75	2.0	268.00
132634AFC	1" PEX crimp union	0.5–1.75	2.2	310.00
132632AFC	1" PEX expansion union	0.5–1.75	2.2	310.00
132454AFC	½" PEX crimp union	2.0–7.0	1.8	257.00
132452AFC	½" PEX expansion union	2.0–7.0	1.8	257.00
132554AFC	¾" PEX crimp union	2.0–7.0	2.0	268.00
132552AFC	¾" PEX expansion union	2.0–7.0	2.0	268.00
132654AFC	1" PEX crimp union	2.0–7.0	2.2	310.00
132652AFC	1" PEX expansion union	2.0–7.0	2.2	310.00



132 QuickSetter+™ PEX

Balancing valve with flow meter.
Direct reading of flow rate.
DZR low-lead brass.
Inlet flow check valve.
PEX crimp: ASTM F1807
PEX expansion: ASTM F1960




Code	Description	Flow scale (gpm)	Lbs	USD
132435AFC	½" PEX crimp union	0.5–1.75	2.2	295.00
132433AFC	½" PEX expansion union	0.5–1.75	2.2	295.00
132535AFC	¾" PEX crimp union	0.5–1.75	2.4	307.00
132533AFC	¾" PEX expansion union	0.5–1.75	2.4	307.00
132635AFC	1" PEX crimp union	0.5–1.75	2.6	347.00
132633AFC	1" PEX expansion union	0.5–1.75	2.6	347.00
132455AFC	½" PEX crimp union	2.0–7.0	2.2	295.00
132453AFC	½" PEX expansion union	2.0–7.0	2.2	295.00
132555AFC	¾" PEX crimp union	2.0–7.0	2.4	307.00
132553AFC	¾" PEX expansion union	2.0–7.0	2.4	307.00
132655AFC	1" PEX crimp union	2.0–7.0	2.6	347.00
132653AFC	1" PEX expansion union	2.0–7.0	2.6	347.00


Complies with NSF/ANSI 372-2000, low lead laws, for use in accordance with the U.S. and Canadian plumbing codes.

STATIC BALANCING VALVES WITH BUILT-IN FLOWMETER

Construction details for QuickSetter+™



Construction details for QuickSetter™



Connection size	Flow rate (gpm)	Fully open Cv
1/2"	0.5 - 1.75	1.0
3/4"	0.5 - 1.75	1.0
1"	0.5 - 1.75	1.0
1/2"	2.0 - 7.0	6.3
3/4"	2.0 - 7.0	6.3
1"	2.0 - 7.0	6.3

Connection size	Flow rate (gpm)	Fully open Cv
1/2"	0.5 - 1.75	3.0
3/4"	2.0 - 7.0	6.3
1"	3.0 - 10.0	8.3
1 1/4"	5.0 - 19.0	15.2
1 1/2"	8.0 - 32.0	32.3
2"	12.0 - 50.0	53.7

STATIC BALANCING VALVES WITH BUILT-IN FLOWMETER FOR HYDRONICS



132 QuickSetter™ press

Balancing valve with flow meter.
Direct reading of flow rate.
No sight gauge clouding or scaling.
Brass valve body and flow meter.
Max. working pressure: 150 psi.
Temperature range: 14–230°F.
Max. percentage of glycol: 50%.
Insulation jacket included for both press and FNPT.

Code	Description	Flow scale (gpm)	Lbs	USD
132436A	1/2" press	0.5 - 1.75	2.2	219.00
132556A	3/4" press	2.0–7.1	2.0	247.00
132666A	1" press	3.0–10.0	2.4	289.00
132776A	1 1/4" press	5.0–19.0	2.8	383.00
132886A	1 1/2" press	8.0–32.0	3.4	455.00
132996A	2" press	12.0–50.0	4.4	557.00



132 QuickSetter™

Balancing valve with flow meter.
Direct reading of flow rate.
No sight gauge clouding or scaling.
Brass valve body and flow meter.
Max. working pressure: 150 psi.
Temperature range: 14–230°F.
Max. percentage of glycol: 50%.
Insulation jacket included for both press and FNPT.


Code	Description	Flow scale (gpm)	Lbs	USD
132432A	1/2" FNPT	0.5–1.75	2.0	204.00
132552A	3/4" FNPT	2.0–7.0	1.8	219.00
132662A	1" FNPT	3.0–10.0	2.4	256.00
132772A	1 1/4" FNPT	5.0–19.0	2.8	341.00
132882A	1 1/2" FNPT	8.0–32.0	3.4	404.00
132992A	2" FNPT	12.0–50.0	4.4	494.00

STATIC BALANCING VALVES WITH BUILT-IN FLOWMETER FOR HYDRONICS



132 QuickSetter™ flange

Balancing valve with flow meter.
Direct reading of flow rate.
ANSI 125 flanged cast iron body.
Brass flow meter.
Max. working pressure: 150 psi.
Temperature range: 14–230°F.
Max. percentage of glycol: 50%.



The 132 series balancing valve accurately sets the flow rate of heating and cooling transfer fluid. The flow meter is housed in a bypass circuit on the valve body and can be shut off during normal operation. The flow meter permits fast and easy circuit balancing without added differential pressure gauges and reference charts.

Code	Description	Flow scale (gpm)	Lbs	USD
132060A	2½" ANSI flange	30–105	35	1,219.00
132080A	3" ANSI flange	38–148	62	1,626.00
132100A	4" ANSI flange	55–210	67	2,482.00

ACCESSORIES



Isolation ball valve.
Low lead MxF union fits between valve body and tailpiece.

Code	Description	Lbs	USD
290030	Isolation ball valve 1" M x 1" F union	1	46.20
NA10815	Stem extension for 290030 NEW	0.2	26.30



Replacement flow meter.

Code	Description	Lbs	USD
F0000940	Replacement flowmeter 0.5 to 1.75 GPM	0.2	113.00
F0000941	Replacement flowmeter 2.0 to 7.0 GPM	0.2	113.00
F0000942	Replacement flowmeter 3.0 to 10 GPM	0.2	113.00
F0000943	Replacement flowmeter 5.0 to 19 GPM	0.2	119.00
F0000944	Replacement flowmeter 8.0 to 32 GPM	0.2	119.00
F0000945	Replacement flowmeter 12 to 50 GPM	0.2	119.00
F0000946	Replacement flowmeter 30 to 105GPM	0.2	125.00
F0000947	Replacement flowmeter 38 to 148 GPM	0.2	125.00
F0000948	Replacement flowmeter 55 to 210 GPM	0.2	125.00
F19346	Replacement by-pass valve stem* *With operating ring	0.2	41.30



NA108
NPT full port ball valves with extended operator handle for insulated or bare pipes. For use with hot or cold water piping in plumbing or hydronic applications. High strength forged low lead brass. Blowout-proof stem with dual o-ring seals. Pressure rating 600 WOG. Temperature rating -4°F to 366°F.

Code	Description	Lbs	USD
NA10824	½" FNPT ball valve low lead	0.4	37.30
NA10825	¾" FNPT ball valve low lead	0.6	45.70
NA10826	1" FNPT ball valve low lead	1	59.30
NA10827	1¼" FNPT ball valve low lead	1.6	98.70
NA10828	1½" FNPT ball valve low lead	1.9	125.00
NA10829	2" FNPT ball valve low lead	3	305.00



QuickSetter™ Insulation sleeve for valve and fitting on each end.

Code	Description	Lbs	USD
F0000926	For models with temperature gauge	0.1	41.20
112001	For models without temperature gauge	0.1	40.60



Low lead brass pipe nipples. For connecting NA108 ball valve to other FNPT valves such as 130, 132, 142, 116 series

Code	Description	Lbs	USD
NA10834	½" NPT nipple	0.1	4.70
NA10835	¾" NPT nipple	0.1	7.40
NA10836	1" NPT nipple	0.1	11.60
NA10837	1¼" NPT nipple	0.3	20.00
NA10838	1½" NPT nipple	0.3	21.00
NA10839	2" NPT nipple	0.5	30.50



QuickSetter+™ replacement body. See fitting section table in Section 8.

Code	Description	Lbs	USD
132637	0.5 - 1.75 GPM	1	204.00
132657	2.0 - 7.0 GPM	1	215.00

DYNAMIC BALANCING VALVES FOR PLUMBING AND HYDRONICS



127 FlowCal™ sweat

Compact automatic recirculation balancing valves.
 Patented anti-scale, low noise polymer.
 Max. working pressure: 230 psi.
 Temperature range: 32—212°F.
 Max. percentage of glycol: 50%
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: ±10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127349AF ***	½" sweat union	0.8	105.00
127359AF ***	¾" sweat union	0.8	110.25
127369AF ***	1" sweat union	1.0	127.05



127 FlowCal™ NPT

Compact automatic recirculation balancing valves.
 Patented anti-scale, low noise polymer.
 Max. working pressure: 230 psi.
 Temperature range: 32—212°F.
 Max. percentage of glycol: 50%
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: ±10%.
 Select desired flow rate on **page 70** to complete full part number..

Code	Description	Lbs	USD
127341AF ***	½" NPT male union	1.0	111.30
127351AF ***	¾" NPT male union	1.0	115.50
127361AF ***	1" NPT male union	1.2	131.25



127 FlowCal™ press

Compact automatic recirculation balancing valves.
 Patented anti-scale, low noise polymer.
 Max. working pressure: 230 psi.
 Temperature range: 32—212°F.
 Max. percentage of glycol: 50%
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: ±10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127346AF ***	½" press union	NEW 0.9	122.85
127356AF ***	¾" press union	1.0	135.45
127366AF ***	1" press union	1.3	165.90



127 FlowCal™ PEX

Compact automatic recirculation balancing valves.
 Patented anti-scale, low noise polymer.
 Max. working pressure: 230 psi.
 Temperature range: 32—212°F.
 Max. percentage of glycol: 50%
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: ±10%.
 PEX crimp: ASTM F1807
 PEX expansion: ASTM F1960
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127344AF ***	½" PEX crimp union	1.0	105.00
127342AF ***	½" PEX expansion union	1.0	105.00
127354AF ***	¾" PEX crimp union	1.0	110.25
127352AF ***	¾" PEX expansion union	1.0	110.25
127364AF ***	1" PEX crimp union	1.3	127.05
127362AF ***	1" PEX expansion union	1.3	127.05



127 FlowCal™ body

Compact automatic recirculation balancing valves.
 Patented anti-scale, low noise polymer.
 Max. working pressure: 230 psi.
 Temperature range: 32—212°F.
 Max. percentage of glycol: 50%
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: ±10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127000A ***	127 body + *** GPM cartridge, no fittings	1.0	79.80

NEW



Union isolation ball valve
 Low lead MxF union fits between valve body and tailpiece.

Code	Description	Lbs	USD
290030	1" M x 1" F union ball valve	1	46.20
NA10815	Stem extension for 290030	0.2	26.30

Complies with NSF/ANSI 372-2011, low lead laws, for use in accordance with the U.S. and Canadian plumbing codes. US Patent 7,246,635 B2.

DYNAMIC BALANCING VALVES FOR PLUMBING AND HYDRONICS



127 FlowCal+™ sweat

Compact automatic recirculation balancing valves. Patented anti-scale, low noise polymer. FlowCal™ cartridge. Inlet flow check valve. Max. working pressure: 230 psi. Temperature range: 32–212°F. Max. percentage of glycol: 50%. Flow rate range: 0.35 to 10 GPM. Flow accuracy: ±10%. Dual scale: 30 – 210°F (0 – 100°C). Gauge accuracy: ± 6°F. Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127148AFC ***	1/2" sweat union	1.0	151.20
127158AFC ***	3/4" sweat union	1.0	164.85
127168AFC ***	1" sweat union	1.2	192.15



127 FlowCal+™ PEX

Compact automatic recirculation balancing valves. Patented anti-scale, low noise polymer. FlowCal™ cartridge. Inlet flow check valve. Max. working pressure: 230 psi. Temperature range: 32–212°F. Max. percentage of glycol: 50%. Flow rate range: 0.35 to 10 GPM. Flow accuracy: ±10%. Dual scale: 30 – 210°F (0 – 100°C). Gauge accuracy: ± 6°F. PEX crimp: ASTM F1807. PEX expansion: ASTM F1960. Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127145AFC ***	1/2" PEX crimp union	1.2	151.20
127143AFC ***	1/2" PEX expansion union	1.2	151.20
127155AFC ***	3/4" PEX crimp union	1.2	164.85
127153AFC ***	3/4" PEX expansion union	1.2	164.85
127165AFC ***	1" PEX crimp union	1.5	192.15
127163AFC ***	1" PEX expansion union	1.5	192.15



127 FlowCal+™ NPT

Compact automatic recirculation balancing valves. Patented anti-scale, low noise polymer. FlowCal™ cartridge. Inlet flow check valve. Max. working pressure: 230 psi. Temperature range: 32–212°F. Max. percentage of glycol: 50%. Flow rate range: 0.35 to 10 GPM. Flow accuracy: ±10%. Dual scale: 30 – 210°F (0 – 100°C). Gauge accuracy: ± 6°F. Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127140AFC ***	1/2" NPT male union	1.2	156.45
127150AFC ***	3/4" NPT male union	1.2	186.90
127160AFC ***	1" NPT male union	1.4	194.25



127 FlowCal+™ press

Compact automatic recirculation balancing valves. Patented anti-scale, low noise polymer. FlowCal™ cartridge. Inlet flow check valve. Max. working pressure: 230 psi. Temperature range: 32–212°F. Max. percentage of glycol: 50%. Flow rate range: 0.35 to 10 GPM. Flow accuracy: ±10%. Dual scale: 30 – 210°F (0 – 100°C). Gauge accuracy: ± 6°F. Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127147AFC ***	1/2" press union NEW	1.0	147.00
127157AFC ***	3/4" press union	1.2	182.70
127167AFC ***	1" press union	1.5	200.55

Flow rate selection

GPM	Last 3 digits ...	Differential Pressure Control Ranges (psid)
.35	G35	2–14
.5	G50	
.75	G75	
1	1G0	2–32
1.3	1G3	
1.5	1G5	
1.7	1G7	
2	2G0	
2.2	2G2	
2.5	2G5	
2.6	2G6	
3	3G0	
3.5	3G5	
4	4G0	4–34
4.5	4G5	
5	5G0	
6	6G0	
7	7G0	5–35
8	8G0	
9	9G0	
10	10G	

Complies with NSF/ANSI 372-2011, low lead laws, for use in accordance with the U.S. and Canadian plumbing codes. US Patent 7,246,635 B2.

DYNAMIC BALANCING VALVES FOR PLUMBING AND HYDRONICS



127 FlowCal+™ sweat

Compact automatic recirculation balancing valves. Patented anti-scale, low noise polymer. FlowCal™ cartridge. Inlet flow check valve. Max. working pressure: 230 psi. Temperature range: 32–212°F. Max. percentage of glycol: 50%. Flow rate range: 0.35 to 10 GPM. Flow accuracy: ±10%. Select desired flow rate on **page 70** to complete full part number.



127 FlowCal+™ PEX

Compact automatic recirculation balancing valves. Patented anti-scale, low noise polymer. FlowCal™ cartridge. Inlet flow check valve. Max. working pressure: 230 psi. Temperature range: 32–212°F. Max. percentage of glycol: 50%. Flow rate range: 0.35 to 10 GPM. Flow accuracy: ±10%. PEX crimp: ASTM F1807. PEX expansion: ASTM F1960. Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127149AFC ***	1/2" sweat union	0.8	115.50
127159AFC ***	3/4" sweat union	0.8	124.95
127169AFC ***	1" sweat union	1.0	154.35

Code	Description	Lbs	USD
127144AFC ***	1/2" PEX crimp union	1.0	115.00
127142AFC ***	1/2" PEX expansion union	1.0	115.50
127154AFC ***	3/4" PEX crimp union	1.0	124.95
127152AFC ***	3/4" PEX expansion union	1.0	124.95
127164AFC ***	1" PEX crimp union	1.3	154.35
127162AFC ***	1" PEX expansion union	1.3	154.35



127 FlowCal+™ NPT

Compact automatic recirculation balancing valves. Patented anti-scale, low noise polymer. FlowCal™ cartridge. Inlet flow check valve. Max. working pressure: 230 psi. Temperature range: 32–212°F. Max. percentage of glycol: 50%. Flow rate range: 0.35 to 10 GPM. Flow accuracy: ±10%. Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127141AFC ***	1/2" NPT male union	1.0	116.55
127151AFC ***	3/4" NPT male union	1.0	123.90
127161AFC ***	1" NPT male union	1.2	156.45




127 FlowCal+™ press

Compact automatic recirculation balancing valves. Patented anti-scale, low noise polymer. FlowCal™ cartridge. Inlet flow check valve. Max. working pressure: 230 psi. Temperature range: 32–212°F. Max. percentage of glycol: 50%. Flow rate range: 0.35 to 10 GPM. Flow accuracy: ±10%. Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
127146AFC ***	1/2" press union	0.9 NEW!	115.50
127156AFC ***	3/4" press union	1.0	142.80
127166AFC ***	1" press union	1.3	163.80

Construction details FlowCal+



Complies with NSF/ANSI 372-2011, low lead laws, for use in accordance with the U.S. and Canadian plumbing codes. US Patent 7,246,635 B2.

DYNAMIC BALANCING VALVES FOR PLUMBING AND HYDRONICS

2nd QTR



128 FlowCal+™ sweat

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Models with 2" diameter temperature gauge.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128448AFC***	1/2" sweat, PT ports, check	2.0	157.50
128458AFC***	3/4" sweat, PT ports, check	2.0	183.75
128468AFC***	1" sweat, PT ports, check	2.2	192.15

2nd QTR



128 FlowCal+™ NPT

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Models with 2" diameter temperature gauge.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128440AFC***	1/2" NPT male, PT ports, check	2.0	161.70
128450AFC***	3/4" NPT male, PT ports, check	1.8	187.95
128460AFC***	1" NPT male, PT ports, check	2.0	194.25

2nd QTR



128 FlowCal+™ press

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Models with 2" diameter temperature gauge.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128447AFC***	1/2" press, PT ports, check	2.0	178.50
128457AFC***	3/4" press, PT ports, check	2.0	200.55
128467AFC***	1" press, PT ports, check	2.2	208.95

2nd QTR




128 FlowCal+™ PEX

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 PEX crimp: ASTM F1807.
 PEX expansion: ASTM F1960.
 Models with 2" diameter temperature gauge.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128445AFC***	1/2" PEX crimp, PT ports, check	2.0	157.50
128455AFC***	3/4" PEX crimp, PT ports, check	2.0	183.75
128465AFC***	1" PEX crimp, PT ports, check	2.2	192.15
128443AFC***	1/2" PEX expansion, PT ports, check	2.0	157.50
128453AFC***	3/4" PEX expansion, PT ports, check	2.0	183.75
128463AFC***	1" PEX expansion, PT ports, check	2.2	192.15

Construction details

The y-body 128 Series FlowCal uses the same flow cartridges as the 127 Series FlowCal. Because the body can remain in the piping, the y-body simplifies serviceability and cartridge changeout. The 128 Series includes factory-installed PT ports.



DYNAMIC BALANCING VALVES FOR PLUMBING AND HYDRONICS

2nd QTR



128 FlowCal+™ sweat

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128449AFC***	1/2" sweat, PT ports, check	1.8	126.00
128459AFC***	3/4" sweat, PT ports, check	1.8	133.35
128469AFC***	1" sweat, PT ports, check	2.0	160.65

2nd QTR



128 FlowCal+™ PEX

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 PEX crimp: ASTM F1807.
 PEX expansion: ASTM F1960.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128444AFC***	1/2" PEX crimp, PT ports, check	1.8	126.00
128454AFC***	3/4" PEX crimp, PT ports, check	1.8	133.35
128464AFC***	1" PEX crimp, PT ports, check	2.0	160.65
128442AFC***	1/2" PEX expansion, PT ports, check	1.8	126.00
128452AFC***	3/4" PEX expansion, PT ports, check	1.8	133.35
128462AFC***	1" PEX expansion, PT ports, check	2.0	160.65

2nd QTR



128 FlowCal+™ NPT

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128441AFC***	1/2" NPT male, PT ports, check	1.8	127.05
128451AFC***	3/4" NPT male, PT ports, check	1.6	134.40
128461AFC***	1" NPT male, PT ports, check	1.8	161.70

2nd QTR




128 FlowCal+™ press

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128446AFC***	1/2" press, PT ports, check	1.8	136.50
128456AFC***	3/4" press, PT ports, check	1.8	150.15
128466AFC***	1" press, PT ports, check	2.0	168.00


Connecting Device

The body of the FlowCal+™ device is fitted with connections for the pressure ports, which is useful when checking operation in the working range. In addition, the cartridge plug contains a connection to be able to use a circuit drain valve.



Replaceable cartridge

The internal regulator is assembled in the form of a self contained cartridge so as to permit easy removal from the body for inspection or replacement. It is equipped with a special automatic fixing system with wire and an operating ring for fast and safe positioning without using tools.



DYNAMIC BALANCING VALVES FOR PLUMBING AND HYDRONICS

2nd QTR



128 FlowCal™ sweat

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128549AF***	1/2" sweat, PT ports	1.8	116.55
128559AF***	3/4" sweat, PT ports	2.0	121.80
128569AF***	1" sweat, PT ports	2.2	136.50

2nd QTR



128 FlowCal™ PEX

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 PEX crimp: ASTM F1807.
 PEX expansion: ASTM F1960.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128544AF***	1/2" PEX crimp, PT ports	2.0	116.55
128554AF***	3/4" PEX crimp, PT ports	2.1	121.80
128564AF***	1" PEX crimp, PT ports	2.2	136.50
128542AF***	1/2" PEX expansion, PT ports	2.0	116.55
128552AF***	3/4" PEX expansion, PT ports	2.1	121.80
128562AF***	1" PEX expansion, PT ports	2.2	136.50

2nd QTR



128 FlowCal™ NPT

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128541AF***	1/2" NPT male, PT ports	2.0	121.80
128551AF***	3/4" NPT male, PT ports	2.1	126.00
128561AF***	1" NPT male, PT ports	2.2	140.70

2nd QTR




128 FlowCal™ press

Y-body automatic balancing valves. Patented anti-scale, low noise polymer FlowCal™ cartridge.
 PT ports included.
 1/2" FNPT plugged blowdown port.
 Max. working pressure: 400 psi.
 Temperature range: 32-212° F.
 Max. percentage of glycol: 50%.
 Flow rate range: 0.35 to 10 GPM.
 Flow accuracy: +/- 10%.
 Select desired flow rate on **page 70** to complete full part number.

Code	Description	Lbs	USD
128546AF***	1/2" press, PT ports	2.0	132.30
128556AF***	3/4" press, PT ports	2.1	142.80
128566AF***	1" press, PT ports	2.2	170.10

Construction details

The Y-body 128 Series FlowCal uses the same flow cartridges as the 127 Series FlowCal. Because the body can remain in the piping, the Y-body simplifies serviceability and cartridge changeout. The 128 Series includes factory-installed PT ports. The FlowCal+ models come with a check valve in the inlet tailpiece, to prevent backward flow in DHW recirculation applications, and are available with or without outlet temperature gauge. The standard FlowCal models do not include a check.



STATIC BALANCING VALVES, FIXED ORIFICE, FOR PLUMBING AND HYDRONICS



130 Flo-Set™ Fixed Orifice Balancing Valve

Fixed orifice.
Multi-turn adjustment range.
Memory stop feature.
Max. working pressure: 232 psi
Working temperature range: -4 to 250°F
Number of adjustment turns: 6
DZR Low-lead brass body.
Stainless steel valve plug.
Teflon® stem guide bearing.
Meets requirements of ANSI/NSF 372-2011.
Certified to Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

Code	Description	Max Cv	Lbs	USD
130400A	½" NPT female	3.7	1.0	138.00
130500A	¾" NPT female	5.1	1.2	151.00
130600A	1" NPT female	8.8	1.5	180.00
130700A	1¼" NPT female	14.0	2.0	225.00
130800A	1½" NPT female	19.7	2.3	280.00
130900A	2" NPT female	30.5	2.5	373.00

Venturi flow rate measurement device

The 130 series valves are equipped with a flow rate measurement device based on the Venturi effect. The device is incorporated in the body of the valve upstream of the valve plug.




Insulation shell fits 130 series balancing valves.

Code	Description	Lbs	USD
CBN130400	fits ½" NPT	0.1	30.30
CBN130500	fits ¾" NPT	0.1	32.90
CBN130600	fits 1" NPT	0.1	39.50
CBN130700	fits 1¼" NPT	0.1	49.20
CBN130800	fits 1½" NPT	0.1	61.50
CBN130900	fits 2" NPT	0.1	81.90

Operating Principal

The 130 series balancing valve is a hydraulic device that controls the flow rate of a fluid. Turning the knob moves a plug within the fluid stream which varies the flow rate. The flow rate is determined according to the pressure drop value measured by a differential pressure meter connected to the pressure test ports.



STATIC BALANCING VALVES, VARIABLE ORIFICE, FOR PLUMBING AND HYDRONICS



142 Flo-Set™ Variable Orifice Balancing Valve

Memory stop feature.
Characterized plug for smooth adjustment.
Maximum working pressure: 232 psi.
Working temperature range: 14—250°F.
DZR low-lead brass body.
Meets requirements of ANSI/NSF 372-2011.
Certified to Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

Code	Description	Max Cv	Lbs	USD
142241A	½" NPT female	3.4	1.0	108.00
142251A	¾" NPT female	5.0	1.2	116.00
142261A	1" NPT female	7.5	1.5	156.00
142271A	1¼" NPT female	12.9	2.3	224.00
142281A	1½" NPT female	16.8	3.0	250.00
142291A	2" NPT female	22.0	3.5	320.00




Insulation shell fits 142 series balancing valves.

Code	Description	Lbs	USD
CBN142241A	fits ½" NPT	0.1	27.80
CBN142251A	fits ¾" NPT	0.1	29.50
CBN142261A	fits 1" NPT	0.1	40.20
CBN142271A	fits 1¼" NPT	0.1	57.40
CBN142281A	fits 1½" NPT	0.1	64.60

Operating Principal

The 142 series balancing valve is a hydraulic device that controls the flow rate of a fluid. Turning the knob moves a plug within the fluid stream which varies the flow rate. The flow rate is determined according to the pressure drop value measured by a differential pressure meter connected to the pressure test ports and the adjustment knob position.



THERMAL BALANCING VALVES FOR PLUMBING



**1161
ThermoSetter™**

Adjustable thermal balancing valve for domestic hot water recirculation circuits. Drywell for temperature gauge or probe. Max. working pressure: 230 psi. Adjustment temperature range: 95°F – 150°F for the 1" and 1-1/4" only. The 1/2" and 3/4" sizes have a top range of 140°F.

1/2" and 3/4" models:
Cv max: 2.1; Cv min: 0.23; Cv design: 0.52.

1" and 1 1/4" models:
Cv max: 4.4; Cv min: 1.0; Cv design: 1.9.



Code	Description	Lbs	USD
116140A	1/2" FNPT	1.6	237.00
116140AC	1/2" FNPT, check valve	1.8	289.00
116141A	1/2" FNPT, gauge	1.7	252.00
116141AC	1/2" FNPT, gauge, check valve	1.9	307.00
116150A	3/4" FNPT	1.5	254.00
116150AC	3/4" FNPT, check valve	1.7	315.00
116151A	3/4" FNPT, gauge	1.6	271.00
116151AC	3/4" FNPT, gauge, check valve	1.8	332.00
116160A	1" FNPT	2.1	333.00
116160AC	1" FNPT, check	2.3	462.00
116161A	1" FNPT, gauge	2.2	348.00
116161AC	1" FNPT, gauge, check	2.4	478.00
116170A	1 1/4" FNPT	2.0	358.00
116170AC	1 1/4" FNPT, check	2.2	500.00
116171A	1 1/4" FNPT, gauge	2.1	372.00
116171AC	1 1/4" FNPT, gauge, check	2.3	515.00



**1163
ThermoSetter™**

Adjustable thermal balancing valve for domestic hot water recirculation circuits. With by-pass valve for thermal disinfection. Purchase 656 actuator separately. Drywell includes temperature gauge. DZR low-lead brass body. Optional outlet check valve. Max. working pressure: 230 psi. Adjustment temperature range: 95°F – 150°F for the 1" and 1-1/4" only. The smaller ones have a top range of 140°F.


1/2" and 3/4" models:
Cv max: 2.1; Cv min: 0.23.
Cv disinfection: 1.2; Cv design: 0.52.

1" and 1 1/4" models:
Cv max: 4.4; Cv min: 1.0.
Cv disinfection: 2.3; Cv design: 1.9.



Code	Description	Lbs	USD
116340A	1/2" FNPT	1.8	298.00
116340AC	1/2" FNPT, check valve	2.0	343.00
116350A	3/4" FNPT	1.7	314.00
116350AC	3/4" FNPT, check valve	1.9	365.00
116360A	1" FNPT, gauge	2.3	414.00
116360AC	1" FNPT, gauge, check valve	2.5	543.00
116370A	1 1/4" FNPT, gauge	2.2	438.00
116370AC	1 1/4" FNPT, gauge, check valve	2.4	580.00

Construction details 116150AC



**1162, 1166
ThermoSetter™**

Adjustable thermal balancing valve for domestic hot water recirculation circuits. With thermal by-pass cartridge for thermal disinfection. Drywell includes temperature gauge. Max. working pressure: 230 psi. Adjustment temperature range: 95°F – 150°F for the 1" and 1-1/4" only. The smaller ones have a top range of 140°F.

1/2" and 3/4" models:
Cv max: 2.1; Cv min: 0.23.
Cv disinfection: 1.2; Cv design: 0.52.

1" and 1 1/4" models:
Cv max: 4.4; Cv min: 1.0.
Cv disinfection: 2.3; Cv design: 1.9.



Code	Description	Lbs	USD
116240A	1/2" FNPT, 160°F bypass	1.8	285.00
116240AC	1/2" FNPT, check valve, 160°F bypass	2.0	326.00
116250A	3/4" FNPT, 160°F bypass	1.7	299.00
116250AC	3/4" FNPT, check valve, 160°F bypass	1.9	350.00
116260A	1" FNPT, 160°F bypass	1.8	399.00
116260AC	1" FNPT check, 160°F bypass	2.0	527.00
116270A	1-1/4" FNPT, 160°F bypass	1.7	425.00
116270AC	1 1/4" FNPT, check, 160°F bypass	1.9	566.00
116640A	1/2" FNPT, 140°F bypass	1.8	285.00
116640AC	1/2" FNPT, check valve, 140°F bypass	2.0	326.00
116650A	3/4" FNPT, 140°F bypass	1.7	299.00
116650AC	3/4" FNPT, check valve, 140°F bypass	1.9	350.00
116660A	1" FNPT, 140°F bypass	2.3	399.00
116660AC	1" FNPT, check, 140°F bypass	2.5	527.00
116670A	1 1/4" FNPT, 140°F bypass	2.2	425.00
116670AC	1 1/4" FNPT, check, 140°F bypass	2.4	566.00

To order a ThermoSetter™ with isolation ball valves, add suffix "...001" to any of the 116 Series code numbers listed in these pages. See NA108 Series on page 93 for isolation valve details. **Contact Caleffi for 116...001 List Prices.**



Complies with NSF/ANSI 372-2011 low lead laws for use in accordance with the U.S. and Canadian plumbing codes, and with NSF/ANSI/CAN 61 (180F).

THERMAL BALANCING VALVES FOR PLUMBING



1164 ThermoSetter™

Compact adjustable thermal balancing valve for domestic hot water recirculation circuits. Drywell for temperature gauge or probe. DZR low-lead brass body. Optional outlet check valve. Max. working pressure: 230 psi. Adjustment temperature range: 105°F — 150°F. Cv max: 2.1; Cv min: 0.35. Cv design: 0.69. Certified to Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes. NSF/ANSI/CAN 61 to 180°F approval.

Code	Description	Lbs	USD
116440A	1/2" FNPT	1.6	197.00
116440AC	1/2" FNPT, check valve	1.8	240.00
116441A	1/2" FNPT, gauge	1.5	210.00
116441AC	1/2" FNPT, gauge, check valve	1.7	255.00
116450A	3/4" FNPT	1.6	212.00
116450AC	3/4" FNPT, check valve	1.8	263.00
116451A	3/4" FNPT, gauge	1.5	226.00
116451AC	3/4" FNPT, gauge, check valve	1.7	276.00



Actuator disinfection cartridge for use with 656 actuator.

Code	Description	Lbs	USD
116000	Replacement actuator bypass cartridge	0.1	66.00



Thermal disinfection bypass cartridges.

Code	Description	Lbs	USD
F0001286	140°F bypass cartridge	0.1	51.20
F0000580	160°F bypass cartridge	0.1	51.20



Temperature gauge fits 116 series. Working temperature range: 30°F — 180°F.

Code	Description	Lbs	USD
116010	1 1/2" dial temp. gauge	0.1	14.60



Check valve fits 116 ThermoSetter™. DZR low-lead brass. Max. working pressure: 150 psi. Max. working temperature: 250°F.

Code	Description	Lbs	USD
NA10469	1/2" FNPT x MNPT inline check valve	0.1	44.00
NA10467	3/4" FNPT x MNPT inline check valve	0.1	51.20
NA51361*	1" MNPT in, 1" FNPT out	1.1	127.00
NA51371*	1 1/4" MNPT in, 1 1/4" FNPT out	1.3	140.00

*Serviceable stainless steel check



NA108

NPT full port ball valves with extended operator handle for insulated or bare pipes. For use with hot or cold water piping in plumbing or hydronic applications. High strength forged low lead brass. Blowout-proof stem with dual o-ring seals. Pressure rating 600 WOG. Temperature rating -4°F to 366°F.

Code	Description	Lbs	USD
NA10824	1/2" FNPT ball valve low lead	0.4	37.30
NA10825	3/4" FNPT ball valve low lead	0.6	45.70
NA10826	1" FNPT ball valve low lead	1.0	59.30
NA10827	1 1/4" FNPT ball valve low lead	1.6	98.70
NA10828	1 1/2" FNPT ball valve low lead	1.9	125.00
NA10829	2" FNPT ball valve low lead	3	305.00



Low lead brass pipe nipples. For connecting NA108 ball valve to other FNPT valves such as 130, 132, 142, 116 series.

Code	Description	Lbs	USD
NA10834	1/2" NPT nipple	0.1	4.70
NA10835	3/4" NPT nipple	0.1	7.40
NA10836	1" NPT nipple	0.1	11.60
NA10837	1 1/4" NPT nipple	0.3	20.00
NA10838	1 1/2" NPT nipple	0.3	21.00
NA10839	2" NPT nipple	0.5	30.50



Replacement main balancing cartridge.

Code	Description	Lbs	USD
F0001516	1/2", 3/4" balancing cartridge	0.1	51.20



Insulation shell fits 116 series thermal balancing valve.

Code	Description	Lbs	USD
CBN116140*	Insulation shell for 1161, 1162, 1163	0.1	35.30
CBN116440*	Insulation shell for 1164	0.1	34.70
CBN116160**	Insulation shell for 1161, 1162, 1163	0.1	37.80


*Fits 1/2" and 3/4"
**Fits 1" and 1 1/4"

DYNAMIC BALANCING VALVES FOR HYDRONICS

**121
FlowCal™**

Automatic flow balancing valve with integral ball valve.
 Brass body.
 Patented anti-scale, low noise polymer FlowCal™ cartridge.
 Maximum working pressure: 400 psi (400 WOG).
 Working temperature range: 32–212°F (0 – 100°C).
 Max. percentage of glycol: 50%.
 Differential pressure control ranges: 2–14, 2–32, 4–34, 5–35 psid.
 Flow rate: fixed flow rate settings ranging from 0.35–21 GPM.
 Flow accuracy: ±10%.
 US Patent 7,246,635 B2.

Available with optional factory-installed pressure and temperature test ports (1213xxx series).



Select desired flow rate to complete full part number.

Code	Description	Lbs	USD
121141A ...	1/2" NPT female	2.7	138.00
121149A ...	1/2" sweat	2.7	132.00
121151A ...	3/4" NPT female	2.7	139.00
121159A ...	3/4" sweat	2.7	133.00
121161A ...	1" NPT female	5.0	285.00
121169A ...	1" sweat	5.0	272.00
121171A ...	1 1/4" NPT female	5.0	320.00
121179A ...	1 1/4" sweat	5.0	305.00
121341A ...	1/2" NPT female with PT test ports	3.2	149.00
121349A ...	1/2" sweat with PT test ports	3.2	141.00
121351A ...	3/4" NPT female with PT test ports	3.2	152.00
121359A ...	3/4" sweat with PT test ports	3.2	142.00
121361A ...	1" NPT female with PT test ports	5.5	295.00
121369A ...	1" sweat with PT test ports	5.5	282.00
121371A ...	1 1/4" NPT female with PT test ports	5.5	330.00
121379A ...	1 1/4" sweat with PT test ports	5.5	314.00

Size	GPM	Last 3 digits ...	Differential Pressure Control Ranges (psid)
1/2", 3/4"	0.35	G35	2 – 14
1/2", 3/4"	0.5	G50	
1/2", 3/4"	0.75	G75	
1/2", 3/4"	1	1G0	2 – 32
1/2", 3/4"	1.3	1G3	
1/2", 3/4"	1.5	1G5	
1/2", 3/4"	1.7	1G7	
1/2", 3/4"	2	2G0	
1/2", 3/4"	2.2	2G2	
1/2", 3/4"	2.5	2G5	
1/2", 3/4", 1"	2.6	2G6	
1/2", 3/4", 1"	3	3G0	
1/2", 3/4", 1"	3.5	3G5	
1/2", 3/4", 1", 1 1/4"	4	4G0	4 – 34
1/2", 3/4", 1", 1 1/4"	4.5	4G5	
1/2", 3/4", 1", 1 1/4"	5	5G0	
1/2", 3/4", 1", 1 1/4"	6	6G0	
1/2", 3/4", 1", 1 1/4"	7	7G0	
1/2", 3/4", 1", 1 1/4"	8	8G0	

Size	GPM	Last 3 digits ...	Differential Pressure Control Ranges (psid)
1/2", 3/4", 1", 1 1/4"	9	9G0	5 – 35
1/2", 3/4", 1", 1 1/4"	10	10G	
1", 1 1/4"	11	11G	3 – 32
1", 1 1/4"	12	12G	
1", 1 1/4"	13	13G	
1", 1 1/4"	14	14G	4 – 35
1", 1 1/4"	15	15G	
1", 1 1/4"	16	16G	
1", 1 1/4"	17	17G	
1", 1 1/4"	18	18G	
1", 1 1/4"	19	19G	
1", 1 1/4"	20	20G	
1", 1 1/4"	21	21G	


Size	Flow Rates
1/2"	.35 – 10 GPM
3/4"	.35 – 10 GPM
1"	2.5 – 21 GPM
1 1/4"	4 – 21 GPM

Replacement flow cartridge kits are available. Consult factory.

Y-STRAINER WITH BALL VALVE FOR HYDRONICS

120 Y-strainer

Y-strainer with integral ball valve. Brass body. Stainless steel strainer cartridge. Maximum working pressure: 400 psi (400 WOG). Working temperature range: 32–212°F. Max. percentage glycol: 50%. Strainer (20 mesh). Connections: —body: F NPT union x F NPT, sweat union x sweat. Pressure and temperature ports: ¼" NPT. Drain port connection: ¼" for ½" & ¾" or ½" for 1" & 1½".



DRAIN VALVES AND PT PORTS



Drain valves for field installation in blow-down-port connection of the 120 series Y-strainer. Brass body. With ¾" garden hose connection. Max. working pressure: 150 psi. Max. working temperature: 250°F.

Code	Description	Cv	Lbs	USD
120141A 000	½" NPT female	8.0	3.0	125.00
120149A 000	½" sweat	8.0	3.0	119.00
120151A 000	¾" NPT female	8.4	3.0	126.00
120159A 000	¾" sweat	8.4	3.0	120.00
120161A 000	1" NPT female	19	6.0	250.00
120169A 000	1" sweat	19	6.0	238.00
120171A 000	1¼" NPT female	20	6.0	285.00
120179A 000	1¼" sweat	20	6.0	272.00
120341A 000	½" NPT female with PT	8.0	3.5	135.00
120349A 000	½" sweat with PT	8.0	3.5	130.00
120351A 000	¾" NPT female with PT	8.4	3.5	137.00
120359A 000	¾" sweat with PT	8.4	3.5	131.00
120361A 000	1" NPT female with PT	19	6.5	261.00
120369A 000	1" sweat with PT	19	6.5	248.00
120371A 000	1¼" NPT female with PT	20	6.5	295.00
120379A 000	1¼" sweat with PT	20	6.5	282.00

Code	Description	Lbs	USD
538202 FD	¼" NPT fits ½"—¾" 120 series	0.3	14.80
538402 FD	½" NPT fits 1—1¼" 120 series	0.3	15.10



Fast-plug pressure/temperature test ports fits FlowCal™ automatic flow balancing valves and the 120 series Y-strainer. The double-sealing core insures long and trouble free service. Low Lead brass body. Nordel Core. Connections: ¼" NPT male. Cap thread: ⅜"-24 UNF. Working temperature range: 0–275°F. Max. working pressure: 435 psi. Pair (2 ports included).

Code	Description	Lbs	USD
100001A	Standard size, 1½" length (pair)	0.5	15.60


WORLD'S MOST RECOGNIZED PRESSURE REDUCING VALVES



The **PresCal™** is constructed of dezincification-resistant low lead brass and low friction moving parts that stand up to hard water and scale for maximum durability. The **fully-contained replaceable cartridge** has an integral stainless steel mesh filter which makes cleaning or rebuilding the PresCal **fast and easy**. Approvals include compliance with NSF/ANSI/CAN 61 (rated for commercial hot water 180°F), NSF/ANSI 372 low lead laws, ASSE 1003, CSA B356, and codes IPC, IRC, UPC and NPC for use in accordance with the U.S. and Canadian plumbing codes. **CALEFFI GUARANTEED.**



PRVS AND BACKFLOW PREVENTERS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions
[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

- Pressure reducing valves
- Backflow preventers, dual check
- Backflow preventers, RPZ type

PRESSURE REDUCING VALVES

535H PresCal™ sweat




Pressure reducing valve for residential and commercial applications.
 Max. working pressure: 300 psi.
 Max. working temperature: 180°F.
 Pressure setting range: 15 — 90 psi.
 Front and back set point indication for visibility in any mounting orientation.
 UV protective cover included.

Code	Description	Min GPM	Max GPM	Lbs	USD
535940HA	½" sweat union	1.2	7.3	1.9	117.00
535941HA*	½" sweat union	1.2	7.3	2.0	128.00
535950HA	¾" sweat union	2.1	12.5	2.2	128.00
535951HA*	¾" sweat union	2.1	12.5	2.3	140.00
535960HA	1" sweat union	3.2	19	2.9	168.00
535961HA*	1" sweat union	3.2	19	3.0	180.00
535970HA	1¼" sweat union	5.3	34	5.6	372.00
535971HA*	1¼" sweat union	5.3	34	5.7	383.00
535980HA	1½" sweat union	7.3	44	7.3	522.00
535981HA*	1½" sweat union	7.3	44	7.4	533.00
535990HA	2" sweat union	11.5	70	9.7	677.00
535991HA*	2" sweat union	11.5	70	9.8	689.00

GPM flowrate at 6 feet per second water velocity.
 *With gauge

Construction details 535H PresCal™



535H PresCal™ NPT



Pressure reducing valve for residential and commercial applications.
 Max. working pressure: 300 psi.
 Max. working temperature: 180°F.
 Pressure setting range: 15 — 90 psi.
 Front and back set point indication for visibility in any mounting orientation.
 UV protective cover included.

Code	Description	Min GPM	Max GPM	Lbs	USD
535340HA	½" NPT female union	1.2	7.3	2.0	128.00
535341HA*	½" NPT female union	1.2	7.3	2.1	140.00
535350HA	¾" NPT female union	2.1	12.5	2.3	137.00
535351HA*	¾" NPT female union	2.1	12.5	2.4	148.00
535360HA	1" NPT female union	3.2	19	3.0	179.00
535361HA*	1" NPT female union	3.2	19	3.1	190.00
535370HA	1¼" NPT female union	5.3	34	5.7	383.00
535371HA*	1¼" NPT female union	5.3	34	5.8	395.00
535380HA	1½" NPT female union	7.3	44	7.3	549.00
535381HA*	1½" NPT female union	7.3	44	7.4	560.00
535390HA	2" NPT female union	11.5	70	9.7	677.00
535391HA*	2" NPT female union	11.5	70	9.8	689.00

GPM flowrate at 6 feet per second water velocity.
 *With gauge

535H PresCal™ press



Pressure reducing valve for residential and commercial applications.
 Max. working pressure: 300 psi.
 Max. working temperature: 180°F.
 Pressure setting range: 15 — 90 psi.
 Front and back set point indication for visibility in any mounting orientation.
 UV protective cover included.

Code	Description	Min GPM	Max GPM	Lbs	USD
535650HA	¾" press union	2.1	12.5	2.3	144.00
535651HA*	¾" press union	2.1	12.5	2.4	155.00
535660HA	1" press union	3.2	19	3.0	195.00
535661HA*	1" press union	3.2	19	3.1	207.00
535670HA	1¼" press union	5.3	34	5.8	543.00
535671HA*	1¼" press union	5.3	34	5.8	554.00
535680HA	1½" press union	7.3	44	7.3	779.00
535681HA*	1½" press union	7.3	44	7.4	791.00
535690HA	2" press union	11.5	70	9.7	960.00
535691HA*	2" press union	11.5	70	9.8	971.00

GPM flowrate at 6 feet per second water velocity.
 *With gauge

Complies with: ASSE 1003, CSA B356, NSF/ANSI/CAN 61, NSF/ANSI 372, Low Lead Laws and listed by ICC-ES. Meets codes IPC, IRC & UPC for use in accordance with the U.S. and Canadian plumbing codes. Plenum rated: compliant with the requirements of standard UL 2043.

PRESSURE REDUCING VALVES



535H PresCal™ PEX

Pressure reducing valve for residential and commercial applications.
 Max. working pressure: 300 psi.
 Max. working temperature: 180°F.
 Pressure setting range: 15 — 90 psi.
 PEX crimp: ASTM F1807.
 PEX expansion: ASTM F1960.
 Front and back set point indication for visibility in any mounting orientation.
 UV protective cover included.



535H PresCal™ Body

Replacement valve body.
 DZR low lead "Ecobrass" body.
 Gauge port plug NA10438 included with body.
 See fitting selection table in Section 8.

Code	Description	Min GPM	Max GPM	Lbs	USD
535750HA	3/4" PEX crimp union	2.1	12.5	2.3	128.00
535751HA*	3/4" PEX crimp union	2.1	12.5	2.4	140.00
535550HA	3/4" PEX expansion union	3.2	19	2.3	128.00
535551HA*	3/4" PEX expansion union	3.2	19	2.4	140.00
535760HA	1" PEX crimp union	2.1	12.5	3.0	168.00
535761HA*	1" PEX crimp union	2.1	12.5	3.1	180.00
535560HA	1" PEX expansion union	3.2	19	3.0	168.00
535561HA*	1" PEX expansion union	3.2	19	3.1	180.00

GPM flowrate at 6 feet per second water velocity.
 *With gauge

Code	Description	Lbs	USD
NA535840HA	1/2" body	1.9	89.00
NA535841HA	1/2" body, gauge	2	101.00
NA535850HA	3/4" body	2.2	94.00
NA535851HA	3/4" body, gauge	2.3	105.00
NA535860HA	1" body	2.9	124.00
NA535861HA	1" body, gauge	3.0	136.00
NA535870HA	1 1/4" body	6.1	271.00
NA535871HA	1 1/4" body, gauge	6.2	283.00
NA535880HA	1 1/2" body	7.3	382.00
NA535881HA	1 1/2" body, gauge	7.4	394.00
NA535890HA	2" body	9.7	443.00
NA535891HA	2" body, gauge	9.8	456.00

Order body with custom fittings.



PVC jumper nipple with male union thread. The length of the jumper nipple matches the 535H series valve body face-to-face dimension (B'), allowing the piping to be completed prior to the installation of valve and permitting quick change out from the jumper to the valve.

Code	Description	Lbs	USD
NA11304	Jumper nipple for 535H 1/2"	0.1	15.40
NA11305	Jumper nipple for 535H 3/4"	0.1	17.00
NA11306	Jumper nipple for 535H 1"	0.2	18.20
NA11307	Jumper nipple for 535H 1 1/4"	0.3	19.50
NA11308	Jumper nipple for 535H 1 1/2"	0.3	21.30
NA11309	Jumper nipple for 535H 2"	0.5	61.40



Replacement cartridge for 535H series pressure reducer.

Code	Description	Lbs	USD
535006HA	Fits 535H 1/2", 3/4", 1"	0.3	65.70
535009HA	Fits 535H 1 1/4", 1 1/2", 2"	0.5	198.00

Complies with: ASSE 1003, CSA B356, NSF/ANSI/CAN 61, NSF/ANSI 372, Low Lead Laws and listed by ICC-ES. Meets codes IPC, IRC & UPC for use in accordance with the U.S. and Canadian plumbing codes. Plenum rated: compliant with the requirements of standard UL 2043.

PRESSURE REDUCING VALVES



533H PresCal™ Compact sweat

Compact pressure reducing valve for residential and light commercial applications. DZR low lead "Ecobrass" body with inlet union connection. Low friction anti-scale moving parts. High flow seat design. Adjustment screw for pressure set point. Tamper-resistant cap included. Max. working pressure: 250 psi. Max. working temperature: 180°F. Pressure setting range: 15-80 psi. Factory setting: 45 psi.



533H PresCal™ Compact press

Compact pressure reducing valve for residential and light commercial applications. DZR low lead "Ecobrass" body with inlet union connection. Low friction anti-scale moving parts. High flow seat design. Adjustment screw for pressure set point. Tamper-resistant cap included. Max. working pressure: 250 psi. Max. working temperature: 180°F. Pressure setting range: 15-80 psi. Factory setting: 45 psi.

Code	Description	Min GPM	Max GPM	Lbs	USD
533940HA*	1/2", sweat union in	0.9	5.6	2.0	88.00
533941HA**	1/2", sweat union in	0.9	5.6	2.1	101.00
533950HA*	3/4", sweat union in	1.5	10	2.3	64.00
533951HA**	3/4", sweat union in	1.5	10	2.4	75.00

*FNPT outlet
**FNPT outlet with gauge

Code	Description	Min GPM	Max GPM	Lbs	USD
533650HA*	3/4", press union in	1.5	10	2.3	64.00
533651HA**	3/4", press union in	1.5	10	2.4	75.00

*FNPT outlet
**FNPT outlet with gauge



533H PresCal™ Compact NPT

Compact pressure reducing valve for residential and light commercial applications. DZR low lead "Ecobrass" body with inlet union connection. Low friction anti-scale moving parts. High flow seat design. Adjustment screw for pressure set point. Tamper-resistant cap included. Max. working pressure: 250 psi. Max. working temperature: 180°F. Pressure setting range: 15-80 psi. Factory setting: 45 psi.



533H PresCal™ Compact PEX

Compact pressure reducing valve for residential and light commercial applications. DZR low lead "Ecobrass" body with inlet union connection. Low friction anti-scale moving parts. High flow seat design. Adjustment screw for pressure set point. Tamper-resistant cap included. Max. working pressure: 250 psi. Max. working temperature: 180°F. Pressure setting range: 15-80 psi. Factory setting: 45 psi.

Code	Description	Min GPM	Max GPM	Lbs	USD
533340HA*	1/2", NPT female union in	0.9	5.6	1.9	97.20
533341HA**	1/2", NPT female union in	0.9	5.6	2.0	110.00
533350HA*	3/4", NPT female union in	1.5	10	2.2	64.00
533351HA**	3/4", NPT female union in	1.5	10	2.3	75.00

*FNPT outlet
**FNPT outlet with gauge



Code	Description	Min GPM	Max GPM	Lbs	USD
533750HA*	3/4", PEX crimp union in	1.5	10	2.3	64.00
533751HA**	3/4", PEX crimp union in	1.5	10	2.4	75.00
533850HA*	3/4", PEX expan union in	1.5	10	2.3	64.00
533851HA**	3/4", PEX expan union in	1.5	10	2.3	75.00

*FNPT outlet
**FNPT outlet with gauge

Complies with: ASSE 1003, CSA B356, NSF/ANSI/CAN 61, NSF/ANSI 372, Low Lead Laws and listed by ICC-ES. Meets codes IPC, IRC & UPC for use in accordance with the U.S. and Canadian plumbing codes.

PRESSURE REDUCING VALVES

Construction details 533H PresCal™



Replacement cartridge for 533H series pressure reducer.

Code	Description	Lbs	USD
533000H	Fits 533H 1/2", 3/4"	0.2	47.70



533H PresCal™ Body

Replacement valve body. DZR low lead "Ecobrass" body. Gauge port plug NA10438 included with body. See fitting selection table in Section 8.

Code	Description	Lbs	USD
NA533449HA	1/2" body	0.7	79.20
NA533459HA	3/4" body	0.9	83.80



Pressure gauge fits 535H and 533H series pressure reducers. Dial size: 2". Pressure range: 0—100 psi /0-7 bar. Connection: 1/8" NPT.

Code	Description	Lbs	USD
NA10273	1/8" NPT male	0.1	14.20

PRESSURE REDUCING VALVES

2nd QTR



536A PresCal™ HP sweat High Range

High performance piston type pressure reducing valve for high rise buildings and other applications where high pressures are present and require staged pressure control. The 536A series carries out the first stage pressure reduction in a two valve series where the pressure ratio between the inlet and outlet would be too high for a single pressure reducing valve to control. Max. working pressure: 360 psi. Max. working temperature: 180°F. Pressure setting range: 90 – 150 psi. Factory setting: 115 psi

2nd QTR



536A PresCal™ HP NPT High Range

High performance piston type pressure reducing valve for high rise buildings and other applications where high pressures are present and require staged pressure control. The 536A series carries out the first stage pressure reduction in a two valve series where the pressure ratio between the inlet and outlet would be too high for a single pressure reducing valve to control. Max. working pressure: 360 psi. Max. working temperature: 180°F. Pressure setting range: 90 – 150 psi. Factory setting: 115 psi

Code	Description	Min GPM	Max GPM	Lbs	USD
536043A 109	½" sweat	1.2	7.3	3.3	312.00
536053A 109	¾" sweat	2.1	12.5	4.4	344.00
536063A 109	1" sweat	3.2	19	5	454.00
536073A 109	1¼" sweat	5.3	34	7.5	629.00
536083A 109	1½" sweat	7.3	44	8.8	770.00
536093A 109	2" sweat	11.5	70	11.2	990.00

Code	Description	Min GPM	Max GPM	Lbs	USD
536043A 103	1/2" NPT female	1.2	7.3	3.3	328.00
536053A 103	3/4" NPT female	2.1	12.5	4.4	361.00
536063A 103	1" NPT female	3.2	19	5.0	477.00
536073A 103	1-1/4" NPT female	5.3	34	7.5	660.00
536083A 103	1-1/2" NPT female	7.3	44	8.8	811.00
536093A 103	2" NPT female	11.5	70	11.2	1,042.00

2nd QTR



536A PresCal™ HP sweat Low Range

High performance piston type pressure reducing valve designed for demanding applications where water hammer and pressure spikes are present that would damage a diaphragm type PRV. Perfect for irrigation systems and outdoor locations in moderate non-freezing climates. Max working pressure: 300 psi. Max working temperature: 180°F. Pressure setting range 10 - 90 psi. Factory setting 45 psi

2nd QTR



536A PresCal™ HP NPT Low Range

High performance piston type pressure reducing valve designed for demanding applications where water hammer and pressure spikes are present that would damage a diaphragm type PRV. Perfect for irrigation systems and outdoor locations in moderate non-freezing climates. Max working pressure: 300 psi. Max working temperature: 180°F. Pressure setting range 10 - 90 psi. Factory setting 45 psi

Code	Description	Min GPM	Max GPM	Lbs	USD
536044A 109	½" sweat	1.2	7.3	3.3	312.00
536054A 109	¾" sweat	2.1	12.5	4.4	344.00
536064A 109	1" sweat	3.2	19	5	454.00
536074A 109	1¼" sweat	5.3	34	7.5	629.00
536084A 109	1½" sweat	7.3	44	8.8	770.00

Code	Description	Min GPM	Max GPM	Lbs	USD
536044A 103	1/2" NPT female	1.2	7.3	3.3	328.00
536054A 103	3/4" NPT female	2.1	12.5	4.4	361.00
536064A 103	1" NPT female	3.2	19	5.0	477.00
536074A 103	1-1/4" NPT female	5.3	34	7.5	660.00
536084A 103	1-1/2" NPT female	7.3	44	8.8	811.00

Complies with NSF/ANSI 372, Drinking Water System Components-Lead Content Reduction of Lead in Drinking Water Act, California Health and Safety Code 116875 S.3874, Reduction in Drinking Water Act, Vermont Act 193 - The Lead in Plumbing Supplies Law and Maryland's Lead Free Law HB.372, as certified by ICC-ES, file PMG-1360.

BACKFLOW PREVENTERS, RPZ TYPE

574 RPZ Backflow Preventer



Testable reduced pressure zone backflow preventer.
DZR low lead brass body.
Max. working pressure: 150 psi.
Max. working temperature: 150°F.


Code	Description	Lbs	USD
574004A	½" FNPT	5.0	350.00
574064A	½" press	5.1	371.00
59977*	Upstream check valve (½")	0.1	21.70
59978*	Discharge valve assembly (½")	0.2	39.00
59979*	Downstream check valve (½")	0.1	25.10
NA11604**	Checks, disch valve (½")	0.7	77.70
59980*	Discharge air gap (½")	0.1	52.50
F0001006*	Test port valve (½" - 1")	0.2	24.00

*Replacement
**Rebuild kit

Function

Caleffi 574 Series RPZ backflow preventers have dual unions for simple removal of the body for service or rebuilding. Access to the internal components from the top is also easy without removing the valve from the piping, if desired. Rebuild parts are available by ordering a single part number kit, for each size RPZ. The PT ports are located on top for easy access whether flow is right-to-left or left-to-right.

Construction details ½" RPZ Backflow Preventer



Complies with: ASSE 1013, CSA B64.4, NSF/ANSI 372, Low Lead Laws and listed by ICC-ES. Meets codes IPC, IRC & UPC for use in accordance with the U.S. and Canadian plumbing codes.

574 RPZ Backflow Preventer



Testable reduced pressure zone backflow preventer.
DZR low lead brass body.
Max. working pressure: 150 psi.
Max. working temperature: 150°F.


Code	Description	Lbs	USD
574050A	¾" FNPT	9.5	420.00
574056A	¾" press	9.6	457.00
59469*	Upstream check valve (¾")	0.2	55.90
59470*	Downstream check valve (¾")	0.2	59.40
59471*	Discharge valve assembly (¾")	0.3	118.00
59472*	Valve seat (¾")	0.1	41.90
NA11605**	Checks, disch valve, seat for (¾")	0.8	250.00
39623*	Discharge air gap (¾" to 2")	0.2	57.80
F0001006*	Test port valve (½" to 1")	0.2	24.00

*Replacement
**Rebuild kit

Function

The backflow preventer can be used in all systems where there is danger of the potable water supply system being contaminated. It prevents an accidental reduction in the pressure in the distribution system from causing backflow from contaminated water in user installations.

Construction details ¾ and 1" RPZ Backflow Preventer



BACKFLOW PREVENTERS, RPZ TYPE

NEW

574 RPZ Backflow Preventer




Testable reduced pressure zone backflow preventer.
DZR low lead brass body.
Max. working pressure: 150 psi.
Max. working temperature: 150°F.



Code	Description	Lbs	USD
574006A	1" FNPT	11	438.00
574066A	1" press	11	486.00
59471*	Discharge valve assembly (1")	0.3	118.00
59472*	Valve seat (1")	0.1	41.90
39623*	Discharge air gap (3/4" to 2")	0.2	57.80
F0001006*	Test port valve (1/2" to 1")	0.2	24.00

*Replacement
**Rebuild kit

Construction details 1¼" and 1½" RPZ Backflow Preventer



Maintenance

Since the backflow preventer valve is used to ensure the safety of domestic water supplies it must be inspected per local codes. The first sign that the equipment is not functioning properly, generally associated with the presence of sand or other impurities, is indicated by a permanent leakage through the discharge. This loss is just an initial warning sign and does not completely jeopardize the safety of the check mechanism but means that the unit should be dismantled and the equipment should be cleaned. In the event of dripping at the discharge it is recommended to create strong circulation flow for a few minutes by opening one or more taps. This is usually sufficient to flush out any sand or other impurities to restore normal operation.

Complies with: ASSE 1013, CSA B64.4, NSF/ANSI 372, Low Lead Laws and listed by ICC-ES. Meets codes IPC, IRC & UPC for use in accordance with the U.S. and Canadian plumbing codes.

574 RPZ Backflow Preventer





Testable reduced pressure zone backflow preventer.
DZR low lead brass body.
Max. working pressure: 150 psi.
Max. working temperature: 150°F.



Code	Description	Lbs	USD
574700A	1¼" FNPT	14	797.00
574706A	1¼" press	14	907.00
59455*	Upstream check valve (1¼")	0.3	91.40
59456*	Downstream check valve (1¼")	0.3	91.40
59457*	Discharge valve assembly (1¼")	0.6	129.00
59458*	Valve seat (1¼")	0.2	44.10
NA11607**	Incl. checks, disch valve, seat for (1¼")	1.4	356.00
39623*	Discharge air gap (3/4" to 2")	0.2	57.80

*Replacement
**Rebuild kit

Construction details 2" RPZ Backflow Preventer



BACKFLOW PREVENTERS, RPZ TYPE

NEW

**574
RPZ Backflow Preventer**



Testable reduced pressure zone backflow preventer.
DZR low lead brass body.
Max. working pressure: 150 psi.
Max. working temperature: 150°F.

NEW

**574
RPZ Backflow Preventer**



Testable reduced pressure zone backflow preventer.
DZR low lead brass body.
Max. working pressure: 150 psi.
Max. working temperature: 150°F.

Code	Description	Lbs	USD
574801A	1 1/2" FNPT	14	861.00
574806A	1 1/2" press	14	977.00
59455*	Upstream check valve (1 1/2")	0.3	91.40
59456*	Downstream check valve (1 1/2")	0.6	91.40
59457*	Discharge valve assembly (1 1/2")	0.6	129.00
59458*	Valve seat (1 1/2")	0.2	44.10
NA11608**	incl. checks, disch valve, seat for (1 1/2")	1.4	356.00
39623*	Discharge air gap (3/4" to 2")	0.2	57.80

*Replacement
**Rebuild kit

Complies with: ASSE 1013, CSA B64.4, NSF/ANSI 372, Low Lead Laws and listed by ICC-ES. Meets codes IPC, IRC & UPC for use in accordance with the U.S. and Canadian plumbing codes.

Code	Description	Lbs	USD
574900A	2" FNPT	20	1,355.00
574906A	2" press	20	1,559.00
59459*	Upstream check valve (2")	0.4	148.00
59460*	Downstream check valve (2")	0.4	131.00
59461*	Discharge valve assembly (2")	0.7	250.00
59462*	Valve seat (2")	0.3	50.40
NA11609**	incl. checks, disch valve, seat for (2")	1.8	688.00
39623*	Discharge air gap (3/4" to 2")	0.2	57.80

*Replacement
**Rebuild kit

BACKFLOW PREVENTERS, DUAL CHECK



**573
Dual Check Backflow Preventer**


Dual check continuous pressure backflow preventer with atmospheric vent.
DZR low Lead brass body.
Max. working pressure: 175 psi.
Working temperature range: 32–250°F.
Emergency backpressure temperature: 250°F.

Certified to: ASSE 1012, CSA B64.3, NSF/ANSI 372, Low Lead Laws and listed by ICC-ES. Meets codes IPC, IRC & UPC for use in accordance with the U.S. and Canadian plumbing codes.

Code	Description	Lbs	USD
573403A	1/2" NPT female unions	1.7	94.70
573406A	1/2" press unions	1.7	116.00
573409A	1/2" sweat unions	1.7	90.00
573493A	1/2" sweat union inlet, 1/2" FNPT union outlet	1.7	92.60
573503A	3/4" NPT female unions	1.7	99.40
573100A*	Replacement body w/washers	1.5	69.50

*See fitting selection table in Section 8

Construction details




PLUMBVENT™ AUTOMATIC AIR VENT



The compact low lead **PLUMBVENT™** meets plumbing codes for the U.S. and Canada and is designed to remove unwanted air from **plumbing systems**. The hygroscopic vent cap is a safety feature that prevents potential leakage. **CALEFFI GUARANTEED.**



PLUMBING MISCELLANEOUS COMPONENTS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions
View List Prices

PRODUCTS INCLUDED IN SECTION

- Union y-strainer for plumbing and hydronics
- NPT y-strainer for plumbing and hydronics
- Isolation ball valves
- Automatic air vent for plumbing
- Serviceable low lead check valves

UNION Y-STRAINERS FOR PLUMBING AND HYDRONICS

2nd QTR



**128
Y-strainer sweat**

Y-strainer with union connections.
1" ISO 228 unions threads
PT ports included.
1/2" FNPT plugged blowdown port.
Max. working pressure: 400 psi.
Temperature range: 32-212°F.
Max. percentage of glycol: 50%

Code	Description	Lbs	USD
128749000	Union strainer 1/2" sweat, PT ports	1.3	129.00
128759000	Union strainer 3/4" sweat, PT ports	1.5	132.00
128769000	Union strainer 1" sweat, PT ports	1.7	137.00

2nd QTR



**128
Y-strainer PEX**

Y-strainer with union connections.
1" ISO 228 union threads
PT ports included.
1/2" FNPT plugged blowdown port.
Max. working pressure: 400 psi.
Temperature range: 32-212°F.
Max. percentage of glycol: 50%

Code	Description	Lbs	USD
128744000	Union strainer 1/2" PEX crimp, PT ports	1.5	133.00
128754000	Union strainer 3/4" PEX crimp, PT ports	1.5	137.00
128764000	Union strainer 1" PEX crimp, PT ports	1.7	139.00
128742000	Union strainer 1/2" PEX expan., PT ports	1.5	133.00
128752000	Union strainer 3/4" PEX expan., PT ports	1.5	137.00
128762000	Union strainer 1" PEX expan., PT ports	1.7	139.00

2nd QTR



**128
Y-strainer NPT**

Y-strainer with union connections.
1" ISO 228 union threads
PT ports included.
1/2" FNPT plugged blowdown port.
Max. working pressure: 400 psi.
Temperature range: 32-212°F.
Max. percentage of glycol: 50%

Code	Description	Lbs	USD
128741000	Union strainer 1/2" NPT male, PT ports	1.5	140.00
128751000	Union strainer 3/4" NPT male, PT ports	1.5	143.00
128761000	Union strainer 1" NPT male, PT ports	1.7	145.00

2nd QTR




**128
Y-strainer press**

Y-strainer with union connections.
1" ISO 228 union threads
PT ports included.
1/2" FNPT plugged blowdown port.
Max. working pressure: 400 psi.
Temperature range: 32-212°F.
Max. percentage of glycol: 50%

Code	Description	Lbs	USD
128746000	Union strainer 1/2" press, PT ports	1.5	149.00
128756000	Union strainer 3/4" press, PT ports	1.5	152.00
128766000	Union strainer 1" press, PT ports	1.7	161.00


Construction details

The 128 Series Y-strainer uses the same brass body as the 128 Series FlowCal balancing valve, with dual unions and PT ports included. The 20 mesh stainless steel screen can be easily removed for cleaning without removing the body from the piping or a 1/2" purge valve can replace the plug for easy dirt blowdown.



NPT Y-STRAINERS FOR PLUMBING AND HYDRONICS


2nd QTR



**NA109
Y-strainer**

Designed for residential and commercial plumbing and hydronic applications to protect equipment from premature failure due to damaging debris.
Lead free bronze y-strainers.
Pressure rating 400 WOG.
Temperature range 32 - 212°F.
Max glycol percentage 50%.
20 mesh 304 stainless steel screen.
EPDM gasket.
Threaded cap with tap for blowdown valve.

Code	Description	Lbs	USD
NA10904	1/2" FNPT y-strainer low lead	0.5	65.10
NA10905	3/4" FNPT y-strainer low lead	0.9	105.00
NA10906	1" FNPT y-strainer low lead	1.4	130.00
NA10907	1 1/4" FNPT y-strainer low lead	1.9	218.00
NA10908	1 1/2" FNPT y-strainer low lead	2.4	286.00
NA10909	2" FNPT y-strainer low lead	3.0	492.00



ISOLATION BALL VALVES

NEW



Isolation ball valve.
Low lead MxF union fits between valve body and tailpiece.

Code	Description	Lbs	USD
290030	1" M x 1" F union ball valve	1.0	46.20
NA10815	Stem extension for 290030	0.2	26.30



NEW



NA108

NPT full port ball valves with extended operator handle for insulated or bare pipes.
For use with hot or cold water piping in plumbing or hydronic applications.
High strength forged low lead brass.
Blowout-proof stem with dual o-ring seals.
Pressure rating 600 WOG.
Temperature rating -4°F to 366°F.

Code	Description	Lbs	USD
NA10824	1/2" FNPT ball valve low lead	0.4	37.30
NA10825	3/4" FNPT ball valve low lead	0.6	45.70
NA10826	1" FNPT ball valve low lead	1.0	59.30
NA10827	1 1/4" FNPT ball valve low lead	1.6	98.70
NA10828	1 1/2" FNPT ball valve low lead	1.9	125.00
NA10829	2" FNPT ball valve low lead	3	305.00

NEW



Low lead brass pipe nipples.
For connecting NA108 ball valve to other FNPT valves such as 130, 132, 142, 116 series.

Code	Description	Lbs	USD
NA10834	1/2" NPT nipple	0.1	4.70
NA10835	3/4" NPT nipple	0.1	7.40
NA10836	1" NPT nipple	0.1	11.60
NA10837	1 1/4" NPT nipple	0.3	20.00
NA10838	1 1/2" NPT nipple	0.3	21.00
NA10839	2" NPT nipple	0.5	30.50

AUTOMATIC AIR VENT FOR PLUMBING



**NA5026
PLUMBVENT™**

Automatic air vent.
Compatible with plumbing systems.
Hygroscopic cap (anti-drip).
Lead free automatic air vent.
Max. working pressure: 150 psi.
Max. discharge pressure: 90 psi.
Max. discharge rate: 1.75 SCFM.
Max working temperature: 240°F.
Approval: NSF/ANSI 372 low lead.

Code	Description	Lbs	USD
NA502640A	½" MNPT	0.6	48.50

Complies with NSF/ANSI 372, Drinking Water System Components-Lead Content Reduction of Lead in Drinking Water Act, California Health and Safety Code 116875 S.3874, Reduction in Drinking Water Act, Vermont Act 193 - The Lead in Plumbing Supplies Law and Maryland's Lead Free Law HB.372, as certified by ICC-ES, file PMG-1360.

Function


Float type automatic air vent designed to vent air from water at high points in plumbing system piping. Example applications include risers, domestic hot water storage tanks and recirculation system pump inlets. The automatic air vent is installed in the vertical position in parts of the system where air has possibility accumulated. It is supplied complete with a safety hygroscopic cap that automatically closes the air discharge in case of contact with water.

Operating mechanism


The function of this device is guaranteed by an operating mechanism specially designed to vent when system pressure is high.

Antivibration and antirotation system on the float


This guarantees that in the rest position the air relief valve will not be affected by any movement of the float.



Construction details



Air Flow



SERVICEABLE LOW LEAD CHECK VALVES

NA51 sweat



Serviceable low lead check valves.
 Max. working pressure: 150 psi (10 bar).
 Operating temperature range: 32 to 150°F (0 to 65°C).
 Max. temperature: for one hour: 190°F (88°C).
 Opening pressure differential: 0.25 psi (½" through 1¼"); 0.50 psi (1½", 2").

Code	Description	Cv	Lbs	USD
NA51249	½" sweat	17	0.4	76.70
NA51259	¾" sweat	17	0.4	84.20
NA51369	1" sweat	30	0.9	119.00
NA51379	1¼" sweat	30	1.1	134.00
NA51489	1½" sweat	75	2.4	334.00
NA51499	2" sweat	75	2.4	355.00

NA51 MNPT



Serviceable low lead check valves.
 Max. working pressure: 150 psi (10 bar).
 Operating temperature range: 32 to 150°F (0 to 65°C).
 Max. temperature: for one hour: 190°F (88°C).
 Opening pressure differential: 0.25 psi (½" through 1¼"); 0.50 psi (1½", 2").

Code	Description	Cv	Lbs	USD
NA51240	½" MNPT	17	0.4	91.60
NA51250	¾" MNPT	17	0.6	96.60
NA51360	1" MNPT	30	1.1	126.00
NA51370	1¼" MNPT	30	1.3	139.00
NA51480	1½" MNPT	75	2.6	355.00
NA51490	2" MNPT	75	2.6	377.00

NA51 FNPT



Serviceable low lead check valves.
 Max. working pressure: 150 psi (10 bar).
 Operating temperature range: 32 to 150°F (0 to 65°C).
 Max. temperature: for one hour: 190°F (88°C).
 Opening pressure differential: 0.25 psi (½" through 1¼"); 0.50 psi (1½", 2").

Code	Description	Cv	Lbs	USD
NA51243	½" FNPT	17	0.4	104.00
NA51253	¾" FNPT	17	0.6	111.00
NA51363	1" FNPT	30	1.1	134.00
NA51373	1¼" FNPT	30	1.3	146.00
NA51493	2" FNPT	75	2.6	391.00

NA51 press



Serviceable low lead check valves.
 Max. working pressure: 150 psi (10 bar).
 Operating temperature range: 32 to 150°F (0 to 65°C).
 Max. temperature: for one hour: 190°F (88°C).
 Opening pressure differential: 0.25 psi (½" through 1¼"); 0.50 psi (1½", 2").

Code	Description	Cv	Lbs	USD
NA51246	½" press	17	0.4	111.00
NA51256	¾" press	17	0.6	119.00
NA51366	1" press	30	1.1	173.00
NA51376	1-1/4" press	30	1.3	203.00
NA51486	1½" press	75	2.6	438.00
NA51496	2" press	75	2.6	481.00

NA51 PEX



Serviceable low lead check valves.
 Max. working pressure: 150 psi (10 bar).
 Operating temperature range: 32 to 150°F (0 to 65°C).
 Max. temperature: for one hour: 190°F (88°C).
 Opening pressure differential: 0.25 psi (½" through 1¼"); 0.50 psi (1½", 2").
 PEX crimp: ASTM F1807
 PEX expansion: ASTM F1960

Code	Description	Cv	Lbs	USD
NA51247	½" PEX crimp	17	0.4	84.20
NA51257	¾" PEX crimp	17	0.6	91.60
NA51248	½" PEX expansion	17	0.4	84.20
NA51258	¾" PEX expansion	17	0.6	91.60

NA51 body



Serviceable low lead check valves.
 Max. working pressure: 150 psi (10 bar).
 Operating temperature range: 32 to 150°F (0 to 65°C).
 Max. temperature: for one hour: 190°F (88°C).
 Opening pressure differential: 0.25 psi (½" through 1¼"); 0.50 psi (1½", 2").

Code	Description	Cv	Lbs	USD
NA51200	body, small, w/o fittings	17	0.2	54.40
NA51300	body, medium, w/o fittings	30	0.5	69.30
NA51400	body, large, w/o fittings	75	1.8	181.00

Replacement checks.



Code	Description	Cv	Lbs	USD
NA10117	Fits ½", ¾" (small body)	17	0.1	10.00
NA10370	Fits 1", 1¼" (medium body)	30	0.1	10.00
NA10371	Fits 1½", 2" (large body)	75	0.2	17.30


FAST FILL ACCURATE PRESSURE CONTROL



The highly regarded and widely used **AutoFill™** is known among contractors as THE set-it-and-forget-it hydronic system pressure control valve solution. The **fast-fill function** makes filling the system quicker and simpler by automatically opening fully until fill pressure is reached. System pressure is automatically and accurately maintained per the simple set point dial or the integral shutoff valve can be closed for system isolation from the make-up supply. For flexibility in meeting regional code variations, the AutoFill Combo is available either with an ASSE 1012 dual check type or an ASSE 1013 RPZ type backflow preventer. **CALEFFI GUARANTEED.**



FILLING UNITS AND BOILER TRIM KITS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions
[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

- Water treatment filling units
- Fill and Flush cart
- Automatic filling units
- Boiler trim kits

WATER TREATMENT FILLING UNITS



NA573

Replenishment water treatment filling unit, demineralizes site water through a color changing (indicates when to change) demineralizing cartridge.
 Max. inlet pressure: 125 psi.
 Max. working temperature: 100°F.
 Max. flow: 1 gpm.
 TDS of water after treatment: < 30 ppm.


Code	Description	Lbs	USD
NA573022*	1/2" FNPT	7.4	405.00
NA573100**	Replacement filter housing assembly	3.4	184.00
NA573102	Replacement color-changing filter	1.0	94.00

*Complete including back flow preventer, isolation valves, filter housing with resin cartridge and AutoFill™.
 **Filter housing only. Includes color changing demineralizing cartridge.

Function

The replenishment water treatment filling unit is an assembly consisting of a backflow preventer, isolation valves, filter housing unit with replaceable resin cartridge and AutoFill™ pre-adjustable fill valve. This unit is installed on the water inlet piping in sealed hydronic heating or cooling systems. Three important functions are provided in this single filling unit assembly: maintaining the pressure of the system stable at a set value and automatically filling up with water as required; protecting drinking water systems from return flow, caused by back-siphoning or back pressure of contaminated fluids; and producing from site-sourced water, demineralized water of an ideal grade for use in closed hydronic heating and cooling systems. Minerals causing hardness are almost entirely eliminated. This prevents premature equipment malfunction including reduced efficiency or component failure due to lime scale formation – a common affliction of heat exchangers. Demineralized water is low in electrical conductivity to minimize corrosion due to galvanic attack. Demineralized water eliminates the variability of mineral content found in untreated site water which provides more reliable dosing when chemical additives are used – such as glycol.

Construction detail




Installation

The replacement water treatment filling unit must be horizontally installed following the direction of flow as indicated by the arrow on the AutoFill™ or 573 backflow preventer body. The replacement water treatment filling unit is factory pre-assembled. Fittings may have loosened during shipping and handle. Check the fittings and tighten accordingly.



Cartridge change

1. Close the isolation ball valves. 2. Turn the cartridge with white plastic wrench included with unit. 3. Remove the used cartridge and discard them. 4. Insert the new cartridge. 5. Turn the cartridge and tighten in place with the white plastic wrench. 6. Re-open the isolation ball valves to return to normal operation.



NA570 HYDROFILL™ replacement twist-on lid.

Code	Description	Lbs	USD
NA57094	Replacement twist-on lid	3.0	666.00

NA570 HYDROFILL™ replacement parts.



Code	Description	Lbs	USD
NA57092	Replacement internal inlet/outlet screens	1.5	60.90
NA57093	Replacement o-ring seal kit	0.1	98.10

Resin bags for NA570 HYDROFILL™ in reusable plastic pail.

Code	Description	Lbs	USD
NA570971	Two resin bags for NA570912	22	489.00
NA570974	Four resin bags for NA570924	43	979.00

FILL AND FLUSH CART

**NA255
HYDROFLUSH™**

The fill and flush pump cart is portable, leak-tested for a safe, quick and clean way to fill and flush solar, geo thermal and hydronic systems.

Medium: water, glycol and cleaning fluids.
Tank: 10 gallon with dirt filter.

Max. tank medium temperature: 140°F.

Pump delivery flow: 1–15 gpm.

Pump feet of head: 125 psi.

Max. pump pressure: 55 psi.

Pump power: ½ HP (120 V AC).


Isolating ball valves: ¾" garden hose thread.

Transfer hoses: 8' with ¾" GHT (2 ea).

Dimensions: 48"H x 20"W x 18"D.

Code	Description	Lbs	USD
NA25510	Clean, fill and flush cart	60	3,387.00
NA11338	Replacement hose, 3/4" ID, FxF GHT	3.0	63.10

Dimensions:





Code	A	B	C	D	Weight	Capacity
NA25510	19 ½"	20 "	14"	46 ¼"	85 lbs.	10 gallon

Function

The fill and flush pump cart is portable and leak-tested for a safe, quick and clean way to fill and flush solar, geothermal and hydronic systems.

Connect the fill/purge valves to the fill and flush system, allow fluid to circulate and remove air and dirt in system.



AUTOMATIC FILLING UNITS



553 AutoFill™

Pre-adjustable automatic filling valve, anti-scale, visual system pressure indicator. Complete with manual shut-off valve, strainer and check valve. Brass body.
 Max. inlet pressure: 230 psi.
 Max. working temperature: 150°F.
 Setting pressure range: 3–60 psi.
 Preset outlet pressure: 15 psi.
 Pressure gauge scale: 0–60 psi / 0–4 bar.

Code	Description	Lbs	USD
553549A	½" sweat union in, ½" FNPT out	1.7	116.00
553649A	½" sweat union in, ½" FNPT out	1.7	130.00
553542A	½" NPT male union in, ½" FNPT out	1.7	123.00
553642A	½" NPT male union in, ½" FNPT out	1.7	138.00

*With pressure gauge.



573 AutoFill™ Combo

Pre-adjustable automatic filling valve with backflow preventer. Brass body.
 Max. inlet pressure: 175 psi.
 Max. working temperature: 150°F.
 Setting pressure range: 3–60 psi.
 Preset outlet pressure: 15 psi.
 Pressure gauge scale: 0–60 psi / 0–4 bar.

Code	Description	Lbs	USD
573002A	½" NPT female union in, ½" FNPT out	5.0	208.00
573012A*	½" NPT female union in, ½" FNPT out	5.0	224.00
573006A	½" press union in, ½" press out	5.0	232.00
573016A*	½" press union in, ½" press out	5.0	250.00
573007A	½" press union in, ½" FNPT out	5.0	221.00
573017A*	½" press union in, ½" FNPT out	5.0	238.00
573009A	½" sweat union in, ½" FNPT out	5.0	198.00
573019A*	½" sweat union in, ½" FNPT out	5.0	215.00

*With pressure gauge.



574 AutoFill™ Combo

Pre-adjustable automatic filling valve with testable reduced pressure zone backflow preventer. Brass body.
 Max. working pressure: 150 psi.
 Max. working temperature: 150°F.
 Setting pressure range: 3–60 psi.
 Preset outlet pressure: 15 psi.
 Pressure gauge scale: 0–60 psi / 0–4 bar.

Code	Description	Lbs	USD
574002A	½" FNPT	9.4	460.00
574012A	½" FNPT, gauge	9.4	473.00
574206A	½" press	9.4	481.00
574216A	½" press, gauge	9.4	470.00
574207A	½" press in x FNPT out	9.4	447.00
574217A	½" press in x FNPT out, gauge	9.4	484.00



Code	Description	Lbs	USD
NA10363	0-60 psi/0-4 bar, ¼" NPT	0.1	15.10




Code	Description	Lbs	USD
F59650	553 AutoFill™ replacement cartridge	0.2	34.40




Code	Description	Lbs	USD
NA10197	AutoFill™ clear plastic disc cover	0.1	1.60

Application Diagram



Construction



COMMERCIAL AUTOMATIC FILLING UNITS



5350 AutoFill™

Automatic filling valve. Complete with integral downstream pressure gauge and pressure setting adjustment knob. Max. working pressure: 365 psi. Max. working temperature: 140°F. Pressure gauge scale: 0–100 psi /0–7 bar. Pressure setting range: 6–90 psi. Preset outlet pressure: 15 psi.

Code	Description	Lbs	USD
535059A	¾" sweat union	2.3	149.00
535069A	1" sweat union	2.4	159.00
535051A	¾" NPT male union	2.3	152.00
535061A	1" NPT male union	2.4	160.00
535056A	¾" press union	2.3	155.00
535066A	1" press union	2.4	168.00
535057A	¾" PEX crimp union	2.3	149.00
535067A	1" PEX crimp union	2.4	161.00
535058A	¾" PEX expansion union	2.3	149.00
535068A	1" PEX expansion union	2.4	161.00



5350 AutoFill™ Body

Automatic filling valve. Brass body. Complete with integral downstream pressure gauge and pressure setting adjustment knob. See fitting selection table in Section 8.

Code	Description	Lbs	USD
535951A	AutoFill™ body, no fittings	2.0	109.00



574 AutoFill™ Combo

Pre-adjustable automatic filling valve with testable reduced pressure zone backflow preventer. Max. working pressure: 150 psi. Max. working temperature: 140°F. Pressure gauge scale: 0–100 psi /0–7 bar. Pressure setting range: 6–90 psi. Preset outlet pressure: 15 psi.

Code	Description	Lbs	USD
574151A	¾" FNPT in, ¾" NPT male union out	9.4	561.00
574161A	1" FNPT in, 1" NPT male union out	9.4	562.00
574156A	¾" press	9.4	596.00
574166A	1" press	9.4	615.00
574157A	¾" press in, ¾" NPT male union out	9.4	579.00
574167A	1" press in, 1" NPT male union out	9.4	608.00



NA102

Pressure gauge fits 5350 series AutoFill™. Dial size: 2". Pressure range: 0–100 psi /0–7 bar. Connection: 1/8" NPT.

Code	Description	Lbs	USD
NA10273	0-100 psi/0-7 bar, 1/8" MNPT	0.2	14.20



Replacement cartridge for 5350 series AutoFill™.

Code	Description	Lbs	USD
535004	AutoFill™ 5350 series replacement cartridge	0.2	54.80

BOILER TRIM KITS



NA553

Boiler Trim Kits. 6 configurations combining 8 boiler installation components in one box. This kit includes:

- (1) Caleffi DISCAL® air separator
- (1) Backflow preventer: ½" NPT, sweat or press union
- (1) AutoFill™
- (1) Expansion tank check valve
- (2) Brass nipples: 3"
- (1) NPT brass tee
- (1) Expansion tank

Code	Description	Tank size (gal)	Lbs	USD
NA553369	1" sweat	4.4	15	596.00
NA553379	1¼" sweat	4.4	16	692.00
NA553362	1" FNPT	4.4	15	609.00
NA553372	1¼" FNPT	4.4	16	706.00
NA553366	1" press	4.4	15	653.00
NA553376	1¼" press	4.4	16	785.00



NA553

Boiler Trim Kits. 6 configurations combining 8 boiler installation components in one box. This kit includes:

- (1) Caleffi DISCAL® air separator
- (1) RPZ backflow preventer
- (1) AutoFill™
- (1) Expansion tank check valve
- (2) Brass nipples: 3"
- (1) NPT brass tee
- (1) Expansion tank

Code	Description	Tank size (gal)	Lbs	USD
NA553369R	1" sweat	4.4	19	959.00
NA553379R	1¼" sweat	4.4	20	1,053.00
NA553362R	1" FNPT	4.4	19	969.00
NA553372R	1¼" FNPT	4.4	20	1,068.00
NA553366R	1" press	4.4	19	1,015.00
NA553376R	1¼" press	4.4	20	1,148.00


FAST CONNECTIONS AVAILABLE ON ALL OF OUR MOST POPULAR PRODUCTS



Fast, leak-proof and no-flame press and PEX connections are fast becoming the preferred standard by many professionals. Caleffi offers these connections on our most popular products. Our dual union valve bodies even allow for **mix/match inlet/outlet fitting choices** to save transition adapters. **CALEFFI GUARANTEED.**



FITTINGS AND MISCELLANEOUS COMPONENTS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions

[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

- Fittings configuration table
- Small mixing valves, zone valves, others with 1" union fittings
- PresCal™ pressure reducing valve fittings
- Press fitting kits
- Mixing valve fittings
- AutoFill™ and backflow preventer fittings
- Hydro separator fittings
- Fittings with threads
- Differential pressure bypass
- Miscellaneous components
- Uni-Switch™ Universal flow switch

FITTING CONFIGURATION TABLE

Product series	Code	Description	Nut code	Tailpiece code	Washer code	USD
535H PresCal™ (½")	NA20543	½" FNPT, ¾" nut, washer	incl. w/tail	F49644	incl. w/tail	20.30
533H PresCal™ (½")	NA20540	½" MNPT, ¾" nut, washer	F41186	F31868	R0001458	16.80
553 AutoFill™	NA20549	½" sweat, ¾" nut, washer	incl. w/tail	F49655	incl. w/tail	14.70
127 FlowCal [†]	NA20643	½" FNPT, 1" nut, washer	F0000698	NA10569	R20011	20.30
	NA20640	½" MNPT, 1" nut, washer	F61008	R31981	R20011	17.50
	NA20640C	½" MNPT, 1" nut, washer, check	F61008	59893A	R20011	27.30
	NA20649	½" sweat, 1" nut, washer	F61008	NA10002	R20011	14.50
	NA20649C	½" sweat, 1" nut, washer, check	F61008	NA10164	R20011	24.40
127 FlowCal+™	NA20646	½" press, 1" nut, washer	F61008	NA10403	R20011	17.80
132 QuickSetter+™	NA20647	½" PEX crimp, 1" nut, washer	F61008	F0000492	R20011	14.50
	NA20647C	½" PEX crimp, 1" nut, washer, check	F61008	NA10484	R20011	24.40
520 TankMixer™	NA20648	½" PEX expansion, 1" nut, washer	F61008	F0001007	R20011	14.50
520 AngleMix™	NA20648C	½" PEX expansion, 1" nut, washer, check	F61008	NA10634	R20011	24.40
521 MixCal™	NA20653	¾" FNPT, 1" nut, washer	incl. w/tail	F49645	incl. w/tail	23.10
	NA20650	¾" MNPT, 1" nut, washer	F61008	31901A	R20011	20.30
5213 TMV (req. inlet port check)	NA20650C	¾" MNPT, 1" nut, washer, check	F61008	59840A	R20011	34.90
5350 AutoFill™	NA20659	¾" sweat, 1" nut, washer	F61008	NA10003	R20011	17.40
	NA20659C	¾" sweat, 1" nut, washer, check	F61008	NA10165	R20011	31.90
533H PresCal™ (¾")	NA20656	¾" press, 1" nut, washer	incl. w/tail	NA16265	R20011	20.40
535H PresCal™ (¾")	NA20656C	¾" press, 1" nut, washer, check	incl. w/tail	NA16265LC	R20011	45.30
	NA20657	¾" PEX crimp, 1" nut, washer	F61008	F0000520	R20011	17.40
5517 DISCAL®	NA20657C	¾" PEX crimp, 1" nut, washer, check	F61008	NA10485	R20011	31.90
6000 LEGIOMIX (3/4")	NA20658	3/4" PEX expansion, 1" nut, washer	F61008	F00001008	R20011	17.40
	NA20658C	3/4" PEX expansion, 1" nut, washer, check	F61008	NA10635	R20011	31.90
644 Ball Valve	NA20660	1" MNPT, 1" nut, washer	incl. w/tail	59817A	R20011	33.60
676 Zone Valve	NA20660C	1" MNPT, 1" nut, washer, check	incl. w/tail	59894A	R20011	48.20
Z2, Z3 Zone Valve	NA20669	1" sweat, 1" nut, washer	incl. w/tail	59834A	R20011	30.30
	NA20669C	1" sweat, 1" nut, washer, check	incl. w/tail	59906A	R20011	44.90
NA512xx Serviceable check	NA20666	1" press, 1" nut, washer	incl. w/tail	NA16266	R20011	35.30
V40 flow meter	NA20666C	1" press, 1" nut, washer, check	incl. w/tail	NA16266LC	R20011	69.30
	NA20667	1" PEX crimp, 1" nut, washer	F61008	F0000521	R20011	30.30
	NA20667C	1" PEX crimp, 1" nut, washer, check	F61008	NA10486	R20011	44.90
	NA20668	1" PEX expansion, 1" nut, washer	F000698	F0001009	R20011	30.30
	NA20668C	1" PEX expansion, 1" nut, washer, check	F000698	NA10636	R20011	44.90
535H PresCal™ (1")	NA20760	1" MNPT, 1¼" nut, washer	R31495	NA10116	R0001454	29.40
	NA20763	1" FNPT, 1¼" nut, washer	incl. w/tail	F49646	incl. w/tail	32.30
	NA20767	1" PEX crimp, 1¼" nut, washer	R31495	NA10496	R0001454	31.00
	NA20768	1" PEX expansion, 1¼" nut, washer	R31495	NA10556	R0001454	30.30
	NA20766	1" press, 1¼" nut, washer	incl. w/tail	NA10497	R0001454	39.00
5206 AngleMix (1")	NA20769	1" sweat, 1¼" nut, washer	incl. w/tail	F49657	incl. w/tail	23.90
535H PresCal™ (1¼")	NA20873	1¼" FNPT, 1½" nut, washer	incl. w/tail	F49647	incl. w/tail	58.80
	NA20879	1¼" sweat, 1½" nut, washer	R31589	41787 CST	R0001457	53.00
NA513xx Serviceable check	NA20876	1¼" press, 1½" nut, washer	R11221	NA10707	R0001457	77.70
535H PresCal™ (1½")	NA20983	1½" FNPT, 2" nut, washer	incl. w/tail	F0000493	incl. w/tail	89.30
	NA20989	1½" sweat, 2" nut, washer	incl. w/tail	F0000494	incl. w/tail	74.30
	NA20986	1½" press, 2" nut, washer	incl. w/tail	NA10715	R0001459	162.00

FITTING CONFIGURATION TABLE

Product series	Code	Description	Nut code	Tailpiece code	Washer code	USD
535H PresCal™ (2")	NA21193	2" FNPT, 2½" nut, washer	incl. w/tail	F0000495	R0001460	124.00
	NA21199	2" sweat, 2½" nut, washer	incl. w/tail	F0000496	incl. w/tail	135.00
NA514xx Serviceable check	NA21196	2" press, 2½" nut, washer	incl. w/tail	NA10709	R0001460	226.00
548, 5495 Seps (1")	NA20863	1" FNPT, 1½" nut, washer	R31589	31553 FD	R50005	36.20
	NA20869	1" sweat, 1½" nut, washer	R31589	31554 FD	R50005	36.60
	NA20866	1" press 1½" nut, washer	R31589	NA10706	R50005	60.10
548, 5495 Seps (1¼")	NA20973	1¼" FNPT, 2" nut, washer	R53003	31401 FD	R50008	77.10
	NA20979	1¼" sweat, 2" nut, washer	R53003	31403 FD	R50008	103.00
	NA20976	1¼" press 2" nut, washer	R53003	NA10407	R50008	106.00
548, 5495 Seps (1½")	NA21083	1½" FNPT, 2¼" nut, washer	R53004	R41441	R50047	84.00
	NA21089	1½" sweat, 2¼" nut, washer	R53004	41882A	R50047	107.00
5461 DISCALDIRTMAG™ (1½")	NA21086	1½" press 2¼" nut, washer	R53004	NA10408	R50047	141.00
548, 5495 Seps (2")	NA21293	2" FNPT, 2¾" nut, washer	R53005	31426 FD	R50048	129.00
	NA21299	2" sweat, 2¾" nut, washer	R53005	31428 FD	R50048	152.00
5461 DISCALDIRTMAG™ (2")	NA21296	2" press 2¾" nut, washer	R53005	NA10409	R50048	208.00
5231 MixCal+™ (1") 6000 LEGIOMIX® (1")	NA20860	1" MNPT 1½" nut, washer	R31589	NA10009	R0001457	40.30
	NA20869	1" sweat, 1½" nut, washer	R31589	31554 FD	R0001457	36.60
	NA20866	1" press, 1-1/2" nut, washer	R31589	NA10706	R0001457	60.10
5231 MixCal+™ (1¼") 6000 LEGIOMIX® (1¼")	NA20870	1¼" MNPT 1½" nut, washer	R31589	R41660	R0001457	70.80
	NA20879	1¼" sweat, 1½" nut, washer	R31589	41787 CST	R0001457	53.00
	NA20876	1-1/4" press, 1-1/2" nut, washer	R11221	NA10707	R0001457	77.70
5231 MixCal+™ (1½") 6000 LEGIOMIX® (1½")	NA21180	1½" MNPT 2½" nut, washer	R51838	41371A	R0001460	119.00
	NA21189	1½" sweat 2½" nut, washer	R51838	41788 CST	R0001460	104.00
	NA21186	1½" press, 2-1/2" nut, washer	R51838	NA10708	R0001460	156.00
5231 MixCal+™ (2") 6000 LEGIOMIX® (2")	NA21190	2" MNPT 2½" nut, washer	R51838	41372A	R0001460	149.00
	NA21199	2" sweat 2½" nut, washer	R51838	41789 CST	R0001460	135.00
	NA21196	2" press, 2-1/2" nut, washer	incl. w/tail	NA10709	R0001460	226.00

SMALL MIXING VALVES, ZONE VALVES, OTHERS WITH 1" UNION FITTINGS



Tail piece with check valve.
Low lead brass.

Code	Description	Lbs	USD
59893A	½" NPT male fits 1" nut	0.2	21.20
59840A	¾" NPT male fits 1" nut	0.3	28.90



Tail piece without check valve.
Low lead brass.

Code	Description	Lbs	USD
R31981	½" NPT male fits 1" nut	0.3	11.30
31901A	¾" NPT male fits 1" nut	0.4	14.70



Tail piece.
Low lead brass. Requires sealing washer R20011, not included.

Code	Description	Lbs	USD
59817A	1" NPT male with 1" nut	0.4	31.90
59894A	1" NPT male with 1" nut w/check valve	0.5	46.40



Tail piece with check valve.
Low lead brass.

Code	Description	Lbs	USD
59904A	½" sweat fits 1" nut	0.2	18.40
59905A	¾" sweat for 1" nut	0.3	25.80



Copper press tail piece with 1" brass union nut. Low lead. Requires sealing washer, not included.

Code	Description	Lbs	USD
NA16264	½" press with 1" union nut	0.3	17.10
NA16265	¾" press with 1" union nut	0.4	18.80
NA16266	1" press with 1" union nut	0.5	33.50



Long copper press tail piece with 1" brass union slip nut. Low lead. Requires sealing washer, not included.

Code	Description	Lbs	USD
NA16265L	¾" long press with 1" union slip nut	0.3	43.10
NA16265LC	¾" long press with 1" union nut/check valve	0.3	54.60
NA16266L	1" long press with 1" union slip nut	0.3	64.40
NA16266LC	1" long press with 1" union nut/check valve	0.3	66.90



Washer fits 1" union thread.

Code	Description	Lbs	USD
R20011	1" union washer	0.1	1.60



Tail piece.
Low lead brass.

Code	Description	Lbs	USD
NA10002	½" sweat fits 1" nut	0.2	8.20
NA10003	¾" sweat fits 1" nut	0.3	11.30



Tail piece.
Low lead brass. Requires sealing washer R20011, not included.

Code	Description	Lbs	USD
59834A	1" sweat with 1" nut	0.4	28.80
59906A	1" sweat with 1" nut w/check valve	0.5	43.40



Tail piece with high temperature check valve.
Low lead brass.

Code	Description	Lbs	USD
NA10164	½" sweat fits 1" nut	0.2	25.50
NA10165	¾" sweat fits 1" nut	0.3	29.80



Tail piece with high temperature check valve.
Low lead brass. Requires sealing washer R20011, not included.

Code	Description	Lbs	USD
NA10166	1" sweat with 1" nut w/check valve	0.4	48.80



Copper press low lead tail piece with check valve, requires F0000698 1" slip nut.

Code	Description	Lbs	USD
NA10419C	¾" press long fits 1" slip nut w/check	0.3	43.70



Copper press low lead tail piece, requires F0000698 1" slip nut.

Code	Description	Lbs	USD
NA10403	½" press fits 1" nut	0.1	22.20
NA10419	¾" press long fits 1" slip nut F0000698	0.3	37.30
NA10404	1" press fits 1" slip nut F0000698	0.4	33.60
NA10786	1" press long fits 1" slip nut F0000698	0.5	56.70



Washer fits 1" union thread.
High temperature silicone rubber.
Working temperature: -40—350°F.

Code	Description	Lbs	USD
NA10302	1" union washer high temp silicone	0.1	2.40

SMALL MIXING VALVES, ZONE VALVES, OTHERS WITH 1" UNION FITTINGS



Union nut fits 1" union thread.

Code	Description	Lbs	USD
F61008	1" brass nut	0.2	4.50
F0000698	1" brass slip nut	0.2	6.20



PEX crimp (ASTM F1807) tailpiece for 1" union nut, requires sealing washer and nut, not included.

Code	Description	Lbs	USD
F0000492	1/2" PEX for 1" union nut	0.1	8.20
F0000520	3/4" PEX for 1" union nut	0.1	11.30
F0000521	1" PEX for 1" union nut	0.1	24.20



PEX crimp (ASTM F1807) tailpiece for 1" union nut with check valve, requires sealing washer and nut, not included.

Code	Description	Lbs	USD
NA10484	1/2" PEX for 1" union nut	0.1	18.40
NA10485	3/4" PEX for 1" union nut	0.1	25.80
NA10486	1" PEX for 1" union nut	0.1	38.70



Union nut fits 1" union thread.

Code	Description	Lbs	USD
F61008/C	1" chrome-plated nut	0.2	5.40



Compression fitting.

Code	Description	Lbs	USD
F0000718	3/8" compression tailpiece for 1" nut	0.1	16.60



PEX expansion (ASTM F1960) tailpiece for 1" union nut, requires sealing washer and nut, not included.

Code	Description	Lbs	USD
F0001007	1/2" PEX for 1" union nut	0.1	8.20
F0001008	3/4" PEX for 1" union nut	0.1	11.30
F0001009	1" PEX for 1" union nut	0.1	24.20



PEX expansion (ASTM F1960) tailpiece for 1" union nut with check valve, requires sealing washer and nut, not included.

Code	Description	Lbs	USD
NA10634	1/2" PEX for 1" union nut	0.1	18.40
NA10635	3/4" PEX for 1" union nut	0.1	25.80
NA10636	1" PEX for 1" union nut	0.1	38.70

5231 AND 6000 SERIES MIXING VALVE FITTINGS



Tail piece.
Low lead brass.

Code	Description	Lbs	USD
NA10009	1" NPT male	0.3	44.50
R41660	1 1/4" NPT male	0.3	50.90
41371A	1 1/2" NPT male	0.4	57.40
41372A	2" NPT male	0.5	74.30



Tail piece.
Low lead brass.

Code	Description	Lbs	USD
31554 FD	1" sweat	0.3	35.40
41787 CST	1 1/4" sweat	0.3	34.80
41788 CST	1 1/2" sweat	0.4	55.10
41789 CST	2" sweat	0.5	71.70



Large press tail piece.
Low lead brass.

Code	Description	Lbs	USD
NA10706	1" press tailpiece assy	0.4	44.50
NA10707	1 1/4" press tailpiece assy	0.4	81.70
NA10708	1 1/2" press tailpiece assy	0.5	117.00
NA10709	2" press tailpiece assy	0.5	208.00



Union nut.

Code	Description	Lbs	USD
F61008*	1" brass nut	0.2	4.50
F0000698*	1" brass slip nut	0.2	6.20
R31589**	1 1/2" union nut	0.2	15.10
R11221	1 1/2" slip union nut for 1-1/4" press	0.2	14.80
R51838***	2 1/2" union nut	0.3	37.00

* Fits 3/4" valves
** Fits 1" and 1 1/4" valves
*** Fits 1 1/2" and 2" valves



Washer.

Code	Description	Lbs	USD
R0001462*	1" union washer	0.1	1.60
R0001457**	1 1/2" union washer	0.1	3.50
R0001460***	2 1/2" union washer	0.1	16.50

* Fits 3/4" valves
** Fits 1" and 1-1/4" valves
*** Fits 1-1/2" and 2" valves

PRESCAL™ PRESSURE REDUCING VALVE FITTINGS



NPT female tailpieces with union nut and washer.

Code	Description	Lbs	USD
F49644	1/2" NPT female tailpiece with 3/4" union nut	0.4	19.70
F49645	3/4" NPT female tailpiece with 1" union nut	0.5	22.30
F49646	1" NPT female tailpiece with 1 1/4" union nut	0.6	29.70
F49647	1 1/4" NPT female tailpiece with 1 1/2" union nut	0.7	49.50
F0000493	1 1/2" NPT female tailpiece with 2" union nut	0.9	89.00
F0000495	2" NPT female tailpiece with 2 1/2" union nut	1.0	106.00



PEX expansion tailpieces (ASTM F1960) for union nut.

Code	Description	Lbs	USD
F0001008	3/4" PEX expansion tailpiece for 1" union nut	0.1	11.30
NA10556	1" PEX expansion tailpiece for 1 1/4" union nut	0.2	14.80



NPT male tailpieces for union nut.

Code	Description	Lbs	USD
F31868	1/2" NPT male tailpiece for 3/4" union nut	0.1	11.80
31901A	3/4" NPT male tailpiece for 1" union nut	0.1	14.70



PEX crimp tailpieces (ASTM F1807) for union nut.

Code	Description	Lbs	USD
F0000520	3/4" PEX crimp tailpiece for 1" union nut	0.1	11.30
NA10496	1" PEX crimp tailpiece for 1 1/4" union nut	0.2	26.30



Sweat tailpieces.

Code	Description	Lbs	USD
NA10001	1/2" sweat tailpiece for 3/4" union nut	0.1	9.90
NA10003	3/4" sweat tailpiece for 1" union nut	0.2	11.30
F49657*	1" sweat tailpiece with 1 1/4" nut	0.4	19.70
41787 CST	1 1/4" sweat tailpiece for 1 1/2" union nut	0.3	34.80
F0000494*	1 1/2" sweat tailpiece with 2" union nut	0.7	66.90
F0000496*	2" sweat tailpiece with 2 1/2" union nut	0.8	91.60

*With washer



Union nut.

Code	Description	Lbs	USD
F41186	3/4" union nut for 1/2" 535H	0.1	3.70
F61008	1" union nut for 3/4" 535H	0.2	4.50
R0000915	1" slip union nut for 3/4" 535H	0.2	4.50
R31495	1-1/4" union nut for 1" 535H	0.3	7.40
R11222	1-1/4" slip nut for 1" 535H	0.3	7.40
R31589	1-1/2" union nut for 1-1/4" 535H	0.4	15.10
R53003	2" union nut for 1-1/2" 535H	0.4	30.10
R51838	2-1/2" union nut for 2" 535H	0.5	37.00



Press tailpieces.

Code	Description	Lbs	USD
NA16265	3/4" press tailpiece with 1" nut	0.2	18.80
NA10497	1" press tailpiece with 1 1/4" union nut	0.4	37.10
NA10707	1 1/4" press tailpiece for 1 1/2" union nut	0.6	81.70
NA10715	1 1/2" press tailpiece with 2" union nut	0.8	162.00
NA10709	2" press tailpiece with 2 1/2" union nut	0.9	208.00



Union washers.

Code	Description	Lbs	USD
R0001458	3/4" union washer for 1/2" 535H	0.1	1.50
R20011	1" union washer for 3/4" 535H	0.1	1.60
R0001454	1-1/4" union washer 1" 535H	0.1	2.40
R0001457	1 1/2" union washer for 1 1/4" 535H	0.1	3.50
R0001459	2" union washer for 1 1/2" 535H	0.1	6.70
R0001460	2 1/2" union washer for 2" 535H	0.1	16.50

AUTOFILL™ FITTINGS



AutoFill™ union nut.

Code	Description	Lbs	USD
F41186	¾" union nut	0.1	3.00



AutoFill™ tail piece.

Code	Description	Lbs	USD
NA10001	½" sweat	0.3	9.40



AutoFill™ tail piece.

Code	Description	Lbs	USD
F31868	½" NPT male	0.1	11.80



AutoFill™ washer.

Code	Description	Lbs	USD
R0001458	¾" union washer	0.1	1.40

BACKFLOW PREVENTER FITTINGS



Tail piece with screen fits 573 backflow preventer.

Code	Description	Lbs	USD
R0000892	½" NPT female	0.1	14.80



Tail piece with screen fits 573 backflow preventer.

Code	Description	Lbs	USD
41380A	½" sweat	0.1	14.10



Washer union fits 573 backflow preventer.

Code	Description	Lbs	USD
R0001622	Union washer	0.1	3.40

SEPARATOR FITTINGS



Tail piece for steel 548, 5495, 5461.

Code	Description	Lbs	USD
31553 FD	1" NPT female, fits 54...6A	0.3	17.60
31401 FD	1¼" NPT female, fits 54...7A	0.3	38.10
R41441	1½" NPT female, fits 54...8A	0.3	38.40
31426 FD	2" NPT female, fits 54...9A	0.4	75.20



Tail piece for steel 548, 5495, 5461.

Code	Description	Lbs	USD
31554 FD	1" sweat, fits 54...6A	0.3	35.40
31403 FD	1¼" sweat, fits 54...7A	0.3	65.80
41882A	1½" sweat, fits 54...8A	0.3	62.30
31428 FD	2" sweat, fits 54...9A	0.4	102.00



Press tail piece for steel 548, 5495, 5461.

Code	Description	Lbs	USD
NA10406	1" press, fits 54...6A	0.6	45.70
NA10407	1¼" press, fits 54...7A	0.7	68.10
NA10408	1½" press, fits 54...8A	0.9	96.20
NA10409	2" press, fits 54...9A	1.0	158.00



Union nut for steel 548, 5495, 5461.

Code	Description	Lbs	USD
R31589	fits 54...6A	0.4	15.10
R53003	fits 54...7A	0.4	30.10
R53004	fits 54...8A	0.4	30.10
R53005	fits 54...9A	0.4	34.50



Union washer for steel 548, 5495, 5461.

Code	Description	Lbs	USD
R50005	fits 54...6A	0.2	3.50
R50008	fits 54...7A	0.2	7.00
R50047	fits 54...8A	0.2	14.10
R50048	fits 54...9A	0.2	17.10

FITTINGS WITH 3/4" THREADS



Double nipple.

Code	Description	Lbs	USD
NA12172	3/4" NPT x 3/4" NPT	0.3	21.40



Union nut.

Code	Description	Lbs	USD
F41186	3/4" union nut	0.1	3.70

FITTINGS WITH 1" THREADS



Double nipple.

Code	Description	Lbs	USD
NA12173	1" NPT x 1" NPT	0.4	26.60



Bushing.

Code	Description	Lbs	USD
NA10060	3/4" NPT female w/ 1" male thread	0.3	21.40



Sweat adapter.

Code	Description	Lbs	USD
NA10061	3/4" sweat adaptor w/ 1" male thread	0.2	22.30



Sweat adapter.

Code	Description	Lbs	USD
NA10062	1" sweat adaptor w/ 1" male thd.	0.1	23.10



Union nut fits 1" union thread.

Code	Description	Lbs	USD
F61008	1" brass nut	0.2	4.50
F000698	1" brass slip nut	0.2	6.20

FITTINGS WITH 1" THREADS



Nipple.

Code	Description	Lbs	USD
NA12162	3/4" male w/ O-ring x 1" male thread	0.2	24.60



Bushing.

Code	Description	Lbs	USD
NA10089	3/4" female thread x 1" male thread	0.1	17.70



Disk.

Code	Description	Lbs	USD
NA10104	1" female disk	0.1	3.70



High temperature silicone flat 1" washer.

Code	Description	Lbs	USD
NA10302	1" flat silicone gasket	0.1	2.40



Nipple.

Code	Description	Lbs	USD
NA10064	1" NPT w/ 1" male thread	0.2	24.00

FITTINGS WITH 1 1/4" THREADS



Sweat adapter.

Code	Description	Lbs	USD
NA10119	1" sweat adapter x 1 1/4" union thread	0.4	29.30



Bushing.

Code	Description	Lbs	USD
NA10087	1" female x 1 1/4" male thread bushing	0.4	21.50



Bushing.

Code	Description	Lbs	USD
61215A	1" NPT F x 1 1/4" M thread bushing	0.8	21.40



Nipple.

Code	Description	Lbs	USD
R31706	1" male x 1 1/4" male nipple	0.3	26.60



Union nut.

Code	Description	Lbs	USD
R31495	1 1/4" union nut	0.1	7.40



Washer.

Code	Description	Lbs	USD
R0001454	1 1/4" washer	0.1	2.40



Disk.

Code	Description	Lbs	USD
R11059	1 1/4" female disk	0.1	4.50

DIFFERENTIAL PRESSURE BYPASS




519

Differential pressure by-pass valve.
Adjustable from 2 to 10 psid.
Brass body.
Max. working pressure: 150 psi.
Working temperature range: 32 – 230°F.
¾" flow up to 9 gpm.
1" flow up to 40 gpm.
1¼" flow up to 45 gpm.

Construction Details

When the spring (1) compression is adjusted using the control knob (2), the force balance acting on the valve plug (3) changes, modifying the threshold pressure value of the valve. The valve plug opens, activating the by-pass circuit, only when it is subjected to a differential pressure sufficient to generate a thrust greater than the thrust exerted by the spring. This allows the flow discharge through the outlet (4), limiting the difference in pressure between the two points in the system where the valve is installed. Set screw (5) can be used to lock the adjustment knob in position.



Code	Description	Lbs	USD
519502A	¾" NPT female union	1.0	130.00
519566A	¾" press union	1.0	148.00
519599A	¾" sweat union	1.0	129.00
519600A	1" FNPT in, 1" NPT male union out	1.4	204.00
519609A	1" FNPT in, 1" sweat union out	1.4	204.00
519700A	1¼" FNPT in, 1¼" NPT male union out	1.5	245.00
519709A	1¼" FNPT in, 1¼" sweat union out	1.5	245.00

MISCELLANEOUS COMPONENTS



NA101

Ball valve. Brass body.
Max. working pressure: 600 psi.
Max. working temperature: 365°F.



NA510

NBR, POM check valve.
Max. percentage of glycol: 50%.
Max. working pressure: 150 psi.
Temperature range: 32-150°F (190°F for max. 1 hour).
Opening pressure differential: 0.25 psi (½" through 1¼"); 0.50 psi (1½", 2").

Code	Description	Lbs	USD
NA10167	½" sweat x ½" sweat	0.5	10.00

Code	Description	Cv	Lbs	USD
NA51059	¾" sweat union	12	0.7	58.20
NA51069	1" sweat union	17	1.0	74.30



538

Drain valve. Brass body.
¾" garden hose thread with cap.
Max. working pressure: 150 psi.
Max. working temperature: 250°F.



NA503

Tridicator dual pressure / temperature gauge for boilers. Dial size: 3 1/8".
Pressure range: 0–75 PSI.
Temperature range: 60–320°F.
¼" NPT rear probe.
For direct fluid stream submersion.

Code	Description	Lbs	USD
538202 FD	¼" NPT male x ¾" GHT	0.3	14.80
538402 FD	½" NPT male x ¾" GHT	0.3	15.10

Code	Description	Lbs	USD
NA503040	¼" NPT male center back	0.2	37.00

UNIVERSAL FLOW SWITCH

626 Uni-Switch™

Universal flow switch.
 Suitable for 1" to 8" pipe size.
 Working pressure: 150 psi.
 Working temperature range: -20 – 250°F.
 Minimum flow: 5.7 gpm.
 Switch contacts: NO or NC.
 Switch rating: 15 A.
 CE, cUL, NEMA Type 5, IP 54.



Code	Description	Lbs	USD
626600A	1" NPT male thread	2.3	255.00
626009	Replacement paddle assembly*	0.1	23.90

* stainless steel

Operating principle



The flow switch is composed of a paddle (blade) (1) integral with a control rod (2) connected, at the top, to an adjustable counter spring (3). The assembly, by turning around a pin under the action of the water flow, operates a microswitch contained in a protective casing (4). At rest, the counter spring keeps the microswitch contact open. When the increasing flow rate of the medium within the piping becomes equal or greater than the trip flow rate, the thrust (5) on the blade applied (1) by the flow overcomes the opposing force applied by the adjustable spring (3) thus making the microswitch contact close. With a decreasing flow rate, on reaching the trip flow rate values, the flow thrust on the blade is not enough to overcome the opposing force applied by the adjustable spring, so the blade returns to the rest position and the microswitch contact opens.

The trip values for closing (increasing flow) and opening (decreasing flow) the microswitch contact can be modified with the adjusting screw (6).

Construction Details

The unit is equipped with a set of paddles (blades) (A), to be used for different pipe diameters, particularly sized to allow easy installation and minimal head losses.

For diameters equal to or greater than 3" (DN 80), it is necessary to add to the preassembled blades in increasing order on the long blade (B) (supplied in the package), just by cutting it to the size corresponding to the desired diameter. Replacement paddle or blade assemblies are available, order part number 626009.




EASY-ACCESS INSTALLATION TIP VIDEOS



Whether you're a contractor in the mechanical room looking for installation pointers or a wholesaler explaining a component at the counter, **Caleffi's Installation Tip videos** just made your job easier! Simply scan the QR code, easily identified with a bright-yellow label placed on our product boxes, to **access educational YouTube videos. CALEFFI GUARANTEED.**

RENEWABLES, SOLAR AND BIOMASS DEVICES



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions
View List Prices

PRODUCTS INCLUDED IN SECTION

- Pump stations and fittings
- Solar mixing valves
- Air vents, air separator, and safety relief valves
- Boiler protection valve accessories
- Boiler protection high-flow thermostatic mixing valve
- Boiler protection recirculation and distribution unit

SOLAR PUMP STATIONS

278 & 279



Solar pump stations are pre-assembled and leak-tested. Safety relief valve. Ball valves with built-in flow checks in return (and flow for dual-line models). Temperature gauges in return (and flow for dual-line models). Pressure gauge. Manual air vent (dual-line models only). Expansion tank connection. Connections for flushing and filling. Foam insulation. Balance/flow meter: 1 – 8 gpm scale. Pump: three speed. Pump performance: 19 ft head/8 gpm. Safety relief valve: 90 psi. Max. working pressure: 145 psi. Max. working temp: 350°F. Connections: 3/4" female thread.

(Select adaptors to the right)



Code	Description	Lbs	USD
279051A	Dual-line solar pump station	17	1,027.00
279051	Dual-line solar station w/o pump	12	821.00
278751A	Single-line solar pump station	14	896.00
278751	Single-line solar station w/o pump	10	690.00
278011	Controller housing	0.5	50.00



Replacement pump fit current solar pump stations 278 & 279, plus discontinued 255 & 256 stations. 3 speed 115 V. 1" male union thread. Agency approval: cULus. (install in-line with NA122 union fittings on page 84)

Code	Description	Lbs	USD
NA10481	Grundfos 15-58U, 21' head / 18 gpm	5.0	265.00

DRAINBACK PUMP STATION

278



Drainback solar pump station designed with a high head and steep pump curve which are pre-assembled and leak-tested. Safety relief valve, ball valve, temperature gauge, pressure gauge, air fill valve. Connections for flushing and filling with foam insulation. Balance/flow meter: 2—8 gpm scale. Pump: Grundfos UP15-100. Performance: 36 feet head / 8 gpm. Safety relief valve: 90 psi. Max. working pressure: 145 psi. Max. working temp: 350°F. Connections: 3/4" female thread. (Select adaptors to the left)

Code	Description	Lbs	USD
278951A	Drainback solar pump station	14	956.00

NA121



Replacement single speed 120 V, 1" male union thread. Flow 36 feet head / 8 gpm. Agency approval: cULus. (install in-line with NA122 union fittings on page 94)

Code	Description	Lbs	USD
NA12171	Grundfos Solar 15-100	6.0	330.00

HIGH TEMPERATURE PREMIX GLYCOL

NA101 SolarHD™



Pre-mixed 50% high temperature non toxic glycol, FDA reference: 21 CFR 182.1666, Gosselin TOXICITY INDEX 1, Generally recognized as safe for use as direct food additives. NSF listed, Category Code: HT1, HT2, NSF Registration No. 144912. Compatible with other propylene glycols.



Code	Description	Lbs	USD
NA10103	5 gallon bucket	45	315.00

PUMP STATION FITTINGS



3/4" sweat fittings to top or bottom.
2 each.

Code	Description	Lbs	USD
NA26659	3/4" male thread x 3/4" sweat fitting	0.6	84.50



3/4" sweat fittings to top and bottom. 4 each.

Code	Description	Lbs	USD
NA26759	3/4" male thread x 3/4" sweat fitting	1.0	169.00



1" sweat fittings to top or bottom.
2 each.

Code	Description	Lbs	USD
NA26669	3/4" male thread x 1" sweat fitting	0.6	92.60



1" sweat fittings to top and bottom. 4 each.

Code	Description	Lbs	USD
NA26769	3/4" male thread x 1" sweat fitting	1.0	185.00

BOILER PROTECTION ACCESSORIES



F296

Replacement thermostatic sensor cartridges. Sensor cartridge accuracy: ±4°F. By-pass from boiler complete closing temperature: Tset +18°F (130°+18°=148°F).

Fits 280 and 281 series boiler protection valves. Easy replacement to change the 280 valve set temperature without removing the valve body from the piping.

Code	Description	Lbs	USD
F29633	115°F Tset	0.2	31.30
F29634	130°F Tset	0.2	31.30
F29635	140°F Tset	0.2	31.30
F29636	160°F Tset	0.2	31.30

Selection note: thermostatic sensor cartridge will completely close at Tset value +18°F. Example: (130°F Tset +18°F=148°F completely closed) ±4°F.



F295

Dual scale temperature gauge 280 and 281 series boiler protection valves.

Code	Description	Lbs	USD
F29571	32—250°F	0.2	26.50

BOILER PROTECTION HIGH-FLOW THERMOSTATIC MIXING VALVES

280 ThermoProtect™



Boiler protection high-flow thermostatic mixing valve. Changeable thermostatic sensor cartridge. Brass body and lower plug. Max. working pressure: 150 psi. Working temperature range: 40—212°F. Thermostatic sensor cartridge: 130°F & 140°F Tset standard selections, see below. 115°F, 160°F Tset optional (field replaceable). Sensor cartridge accuracy: ±4°F. By-pass from boiler complete closing temperature: Tset +18°F (ex. 130°+18°=148°F).

Code	Description	Lbs	USD
280965A	1" sweat unions 130°F Tset	11	310.00
280165A	1" NPT female unions 130°F Tset	11	331.00
280966A	1" sweat unions 140°F Tset	11	310.00
280166A	1" NPT female unions 140°F Tset	11	331.00
280975A	1 1/4" sweat unions 130°F Tset	11	364.00
280175A	1 1/4" NPT female unions 130°F Tset	11	380.00
280976A	1 1/4" sweat unions 140°F Tset	11	364.00
280176A	1 1/4" NPT female unions 140°F Tset	11	380.00

BOILER PROTECTION RECIRCULATION AND DISTRIBUTION UNITS

281 ThermoBloc™



ThermoBloc™ boiler protection recirculation and distribution unit. Suitable fluids: water, up to 50% glycol solutions. Max. working pressure: 150 psi. Working temperature range: 40—210°F. Maximum pumping capacity: 10 gpm. Temperature gauge scale: 30—250°F. Thermostatic sensor: 130°F & 140°F Tset standard selections, see below. 115°F, 160°F Tset optional models*. Sensor cartridge accuracy: ±4°F. By-pass from boiler complete closing temperature: Tset +18°F (ex. 130°+18°=148°F). * Consult factory

Code	Description	Lbs	USD
281965A	1" sweat unions 130°F Tset	11	949.00
281165A	1" NPT female unions 130°F Tset	11	1,016.00
281966A	1" sweat unions 140°F Tset	11	949.00
281166A	1" NPT female unions 140°F Tset	11	1,016.00
281975A	1 1/4" sweat unions 130°F Tset	11	1,118.00
281175A	1 1/4" NPT female unions 130°F Tset	11	1,169.00
281976A	1 1/4" sweat unions 140°F Tset	11	1,118.00
281176A	1 1/4" NPT female unions 140°F Tset	11	1,169.00
F19379	Replacement Pump	5	404.00

SOLAR LOW LEAD MIXING VALVES




2521

Adjustable thermostatic three-way mixing valve for solar systems with built-in inlet check valves.
 Setting range: 80—150°F.
 Max. working pressure: 200 psi.
 Max. inlet temperature: 210°F.
 Connection: ½", ¾", 1" sweat.
 Certified to ASSE 1017, CSA B125.3, UPC, IPC, Low Lead Laws and listed by ICC-ES for use in accordance with the U.S. and Canadian plumbing codes.

Operating principle

The controlling element of the solar thermostatic mixing valve is a temperature sensor that is fully immersed in the mixed water outlet passage. As it expands or contracts, the sensor continuously establishes the correct proportion of hot and cold water entering the valve. The flow is regulated by a piston sliding in a cylinder between the hot and cold water passages. Even when there are pressure drops due to the drawing off of hot or cold water for other uses or variations in the incoming temperature, the mixer automatically regulates the water flow to obtain the required temperature.

Code	Description	Lbs	USD
252149A	½" sweat unions	1.2	197.00
252158A	¾" sweat unions with gauge	1.2	256.00
252159A	¾" sweat unions	1.2	208.00
252168A	1" sweat unions with gauge	1.2	291.00
252169A	1" sweat unions	1.2	242.00



Check valve for use in 2521 mixing valve.
 Max. inlet temperature: 210°F.

Code	Description	Lbs	USD
R29326	Check valve insert	0.1	7.40

AIR SEPARATOR AND SAFETY RELIEF VALVES



251 DISCAL®

Air separator for solar heating systems.
 Working temperature range: -20—320°F.
 Max. working pressure: 150 psi.
 Max. discharge pressure: 150 psi.
 Connections: Main, ¾" NPT, female.
 Bottom, ½" NPT, female.



253

Safety relief valves for solar systems.
 Working temperature range: -20—360°F.
 Normal pressure: 150 psi.
 Opening over pressure: 10%.
 Closing differential: 20%.
 Discharge capacity: 171,000 Btu.
 Connections: Inlet, ½" female.
 Discharge, ¾" female.
 TÜV certified to TRD-721-SV100 7.7.
 Meets ANSI Z21.22 standard.

TÜV Rheinland is an approved U.S. Nationally Recognized Testing Laboratory (NRTL) Certification Body for Pressure Equipment. Meets ANSI Z21.22 "Relief Valves for Hot Water Supply Systems."



Code	Description	Lbs	USD
251003A	¾" FNPT female	2.0	183.00

Code	Description	Lbs	USD
253042	Factory set to 35 psi	0.3	61.20
253043	Factory set to 45 psi	0.3	61.20
253044	Factory set to 60 psi	0.3	61.20
253046	Factory set to 90 psi	0.3	61.20
253048	Factory set to 120 psi	0.3	61.20
253040	Factory set to 150 psi	0.3	61.20

AUTOMATIC AIR VENTS



250

Automatic air vent for solar systems.
Working temperature range: -20—360°F.
Max. working pressure: 150 psi.
Max. discharge pressure: 75 psi.



251 DISCALAIR®

High-performance automatic air vent for solar heating systems.
Working temperature range: -20—320°F.
Max. working pressure: 150 psi.
Max. discharge pressure: 150 psi.


Code	Description	Lbs	USD
250041A	1/2" MNPT	0.3	64.60

Code	Description	Lbs	USD
251004A	1/2" FNPT and 3/4" MNPT	0.8	138.00

Function

Automatic air vents are used in the closed circuits of solar heating systems. They allow air contained in the fluid to be released automatically during the filling process, through a valve operated by a float in contact with fluid in the system.


The shut-off valves are used in combination with the automatic air vents to isolate them after filling the circuit of solar heating systems. These series of products have been specially made to work at high temperatures with a glycol medium.



Function

DISCALAIR® solar devices are used in hydronic systems or in the filling and start-up phase of solar heating systems to discharge evenly discharge large quantities of air that have formed in the circuits. This function is performed even when there is considerable pressure due to the special geometry of the discharge mechanism, which is identical to the mechanism on DISCAL® Solar 251 series air separators.

This particular series of automatic air vent valves have been specifically designed to work at high temperature with a glycol medium, which is typical of solar heating systems.



NA292



Shut-off fits automatic air vent.
Working temperature range: -20—360°F.
Max. working pressure: 150 psi.

Code	Description	Lbs	USD
NA29284	1/2" FNPT x 1/2" MNPT	0.2	50.10



NA102

Vent cap adapter to connect discharge tube. Fits all air vents and air separators except 5026 and 5027 series.

Code	Description	Lbs	USD
NA10204	1/4" MNPT	0.1	21.40


MEASURE DISPLAY AND TOTALIZE



CONTECA™ direct heat meter precisely measures and records instantaneous and totalized thermal energy usage for both heating and cooling. Included are two pulse inputs for a domestic hot and domestic water meters, and two universal pulse inputs for added metering for example gas or electric. All data can be accessed at the local user interface or remotely via Modbus, via a Datalogger which can handle up to 250 heat meters, or a Modbus-to-BACnet gateway for BAS systems. Available from .25 to 1000 GPM in an array of fittings, it complies with ASTM E3137/ E3137M – 17 Standard Specification for Heat Meter Instrumentation. **CALEFFI GUARANTEED.**



ENERGY METERS



This diagram is for illustration purposes only



CALEFFI
Hydronic Solutions
[View List Prices](#)

PRODUCTS INCLUDED IN SECTION

Energy meters

Energy meters accessories

ENERGY METERS



7504
CONTECA™ Energy meter

CONTECA™ is a direct heat meter designed to measure instantaneous and recorded history of thermal energy usage in residential and commercial buildings.

Micro processor:

Power supply: 24 VAC, 50/60 Hz, 1W.
Data transmission: 2-wire RS-485; selectable Modbus or M-bus (for use with Datalogger).
Ambient temperature: 40 – 113°F (4 – 45°C).
Environmental rating: NEMA 3S (IP 54).
Pulse inputs: Class 1B per EN 1434-2.

Temperature sensors:

Cable length: 26¼ feet (8 m).
Sensor type: 100 kohm NTC matched.
Temperature sensitivity: < 0.1°F.

Flow meters:

Body material: Brass.
Body threads: ISO 228 male straight.
Piping connections: Dual unions, tailpieces NPT, sweat, flanged, press.
Max. working pressure: 150 psi (10 bar)




Function

The CONTECA™ meter features an 8-digit liquid crystal display that enables easy reading of BTU consumed as well as a range of technical data indicating equipment operating status and data logging.

Each CONTECA™ includes an electronic calculator/user interface, two temperature sensors, fittings included. The flow meter comes with the CONTECA™ meter kit. In addition to the two temperature inputs and flow meter input, 4 additional pulse inputs, for optional equipment monitoring and data logging. The CONTECA™ is easy to install and commission, and complies with ASTM E3137 specification for heat metering instrumentation and European directive 2014/32/UE EN 1434 (MI 004). Approved by Measurement Canada for use in heat metering applications in Canada.


The meter has integral RS-485 Modbus protocol 2-wire communication (default) for remote access and configuration when BAS is MODBUS-RT. The RS-485 protocol must be changed to M-bus when using the Datalogger. Up to 250 CONTECA meters can connect to one CONTECA® data logger.

Lead seals (included with each kit) to prevent tampering



Code	Description	Lbs	USD
750449A	Energy Meter, 0.25 to 10 GPM, ½" sweat	6.2	1,013.00
750440A	Energy Meter, 0.25 to 10 GPM, ½ MNPT	6.2	1,052.00
750446A	Energy Meter, 0.25 to 10 GPM, ½" press	6.2	1,104.00
750459A	Energy Meter, 0.25 to 10 GPM, ¾" sweat	7.1	1,025.00
750450A	Energy Meter, 0.25 to 10 GPM, ¾" MNPT	7.1	1,065.00
750456A	Energy Meter, 0.25 to 10 GPM, ¾" press	7.1	1,116.00
750469A	Energy Meter, 0.25 to 10 GPM, 1" sweat	7.9	1,077.00
750460A	Energy Meter, 0.25 to 10 GPM, 1" MNPT	7.9	1,116.00
750466A	Energy Meter, 0.25 to 10 GPM, 1" press	7.9	1,168.00
750463A	Energy Meter, 0.3 to 15 GPM, 1" FNPT	12	1,502.00
750473A	Energy Meter, 0.5 to 25 GPM, 1¼" FNPT	13	1,604.00
750483A	Energy Meter, 1 to 45 GPM, 1½" FNPT	19	1,860.00
750410A	Energy Meter 11 - 110 GPM, 2½" flanges	27	2,831.00
750411A	Energy Meter 14 - 140 GPM, 3" flanges	29	3,572.00
750412A	Energy Meter 22 - 220 GPM, 4" flanges	44	4,689.00
750413A	Energy Meter 35 - 350 GPM, 5" flanges	51	5,353.00
750414A	Energy Meter 88 - 880 GPM, 6" flanges	88	6,371.00
750415A	Energy Meter 100 - 1000 GPM, 8" flanges	110	7,137.00

Standard installation



ENERGY METERS

7504 CONTECA™ Datalogger



Power supply: 24 V (DC) ±10%, 24 V (AC) - 3 W.
 2 Ethernet ports: ETH1 (PoE), ETH2.
 Ambient temperature range: 32—122°F.
 Mounting: on a 35 mm DIN rail (EN 60715).
 Network addresses: up to 250 Conteca heat meters.
 Daily data logging: 10 years.
 Reports: In XLS or CSV format.



Code	Description	Lbs	USD
750450	Conteca Datalogger	2.0	2,365.00



MODBUS-RT-to-BACnet gateway.
 Converts CONTECA™ controller MODBUS-RT (RS-485 serial) output communication to BACnet IP or MSTP communication.
 Network capacity: up to 1500 registers (approx. 50 CONTECA heat meters).

Code	Description	Lbs	USD
755052	MODBUS-RT-to-BACnet gateway	1.0	1,949.00



Wall transformer.
 Input voltage: 120 V AC.
 Output voltage: 24 V AC.
 Power output: 20 VA.
 Agency approval: cULus.

Code	Description	Lbs	USD
NA10759	24 V AC wall transformer, 20 VA	1.0	39.40

V40 Replacement



Replacement flow meter (body only)
 Single jet rotary pulse flow meter measures liquid flow for energy heat metering production or consumption. Accurate to International Standards OIML R75, EN1434 and MID.
 Brass body.
 Sweat connections included.
 Working temperature range: -40—210°F.
 Max. fluid temperature: 265°F.
 Max. working pressure: 235 psi.
 Maximum glycol: 50%.

Code	Description	Lbs	USD
R79701	0.25 to 10 GPM	3.0	464.00


V40 Replacement



Replacement flow meter (body only)
 Multi-jet rotary pulse flow meter measures liquid flow for energy heat metering production or consumption. Accurate to International Standards OIML R75, EN1434 and MID.
 Brass body.
 Sweat connections included.
 Working temperature range: -40—210°F.
 Max. fluid temperature: 265°F.
 Max. working pressure: 235 psi.
 Maximum glycol: 50%.

Code	Description	Lbs	USD
R79702	0.3 to 15 GPM	5.0	827.00
R79703	0.5 to 25 GPM	8.0	979.00
R79704	1 to 45 GPM	14	1,162.00

Application Diagram



CALEFFI BIM LIBRARY THE HEART OF YOUR DESIGNS



Caleffi is BIM ready and we are eager to share our design know-how. The whole library is natively modeled in REVIT so files are of the highest quality, delivered in a user-friendly file size. Each family contains the parametric variants to allow calculation functions within AUTODESK® REVIT®. Choose Caleffi as part of your standard of excellence in design. **CALEFFI GUARANTEED.**

Download the free library

<http://bit.ly/nacaleffbim>

For more information

woody.dickinson@caleffi.com

LIMITED WARRANTY

COVERAGE: Caleffi North America Inc. ("WARRANTOR") warrants that each Caleffi PRODUCT will be free from defects in material and workmanship for a period of two years* from the date of shipment/delivery of the PRODUCT (that can be identified by the "Caleffi" trademark, trade name, or logo affixed to them). The Limited Warranty is referred to herein as "the Limited warranty." The PURCHASER's sole and exclusive remedy under this Limited Warranty for defects in the PRODUCT shall be the repair, replacement or refund of the purchase price, in WARRANTOR's sole discretion, of the defective PRODUCT, or components thereof.

***PRODUCT warranty exceptions:**

Switching Zone Relays	3 years
Switching zone relays + valves (Z-one valves and Z-one relays installed together)	5 years

NOT COVERED: This Limited Warranty also does not apply to, and WARRANTOR shall have no liability or responsibility in respect of, damages or expenses relating to:

- The failure to properly store, transport, install or use the PRODUCT as, for example, specified in any manuals or other literature supplied by WARRANTOR, on WARRANTOR's website, or in accordance with any applicable laws, codes, regulators or standards;
- Any PRODUCT purchased from any entity other than WARRANTOR;
- Alteration, change or modification of the PRODUCT, including its subcomponents, parts or assemblies;
- WARRANTOR also makes no warranty that a PRODUCT manufactured does not infringe the intellectual property or other proprietary rights of any third party;
- Accidents, misuse, abuse, abnormal use, improper use, negligent use, wilful misconduct, or use exceeding the recommended and permitted limits of the PRODUCT, and/or normal wear or deterioration;
- Any defect or non-conformity that has not been timely and promptly communicated in writing to WARRANTOR as set forth herein.
- Any damage, cost or expense caused by Act of God; or
- Loss of time, loss of use, inconvenience, loss of profits, lost business, lost business opportunities, damage to reputation, goodwill and any incidental or consequential damages arising out of or relating to the PRODUCT, or other matters not specifically covered hereunder.

PROCEDURE: Upon delivery, PURCHASER shall, within one (3) business day, inspect the PRODUCT for conformity and visible defects. PURCHASER shall give WARRANTOR immediate written, specific and detailed notice of any non-conformities or defects regarding the PRODUCT. Upon receipt of the written notice of claim, WARRANTOR shall have the right to inspect the PRODUCT. In the event of a defect covered by this Limited Warranty, WARRANTOR will, at WARRANTOR's discretion, repair or replace the PRODUCT or any component of the PRODUCT or refund the purchase price for that particular PRODUCT. In the event that PURCHASER submits a warranty claim that, in the sole reasonable discretion of the WARRANTOR, is unfounded, the PURCHASER shall reimburse the WARRANTOR all reasonable costs incurred by the WARRANTOR in evaluating the warranty claim (i.e. travel, lodging, expert evaluations, etc.). WARRANTOR must approve, in advance and in writing, all repairs or replacements covered under or performed pursuant to this Limited Warranty. Any warranty repairs or service must be performed exclusively by WARRANTOR or other authorized representative of WARRANTOR or by another servicing facility pre-approved in writing by WARRANTOR. Acceptance of any Limited Warranty claim is not an admission that any PRODUCT or any of its component parts are defective. The PURCHASER forfeits any rights it may have under this Limited Warranty if the PURCHASER does not follow the procedure described herein.

All requests and notices under this Limited Warranty shall be directed to:

Caleffi North America Inc.
3883 West Milwaukee Road
Milwaukee, WI 53208
E-Mail: returns.us@caleffi.com
Phone (414) 238-2360
Fax: (414) 238-2366

LIMITATION OF DAMAGES: Except as expressly provided by this Limited Warranty, **WARRANTOR SHALL NOT BE RESPONSIBLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES ASSOCIATED WITH THE USE OR NON-USE OF THE PRODUCT OR A CLAIM UNDER THIS LIMITED WARRANTY, WHETHER THE CLAIM IS BASED ON CONTRACT, TORT OR OTHERWISE.** The foregoing statements of warranty are exclusive and in lieu of all other remedies or damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, so only in this case this limitation or exclusion may not apply to you. This Limited Warranty shall be the sole and exclusive remedy available to the PURCHASER with respect to this PRODUCT. In the event of any alleged breach of any warranty or any legal action brought by the PURCHASER, based on breach of warranty, alleged negligence or other tortious conduct by WARRANTOR, the PURCHASER's sole and exclusive remedy will be the repair or replacement of any defective PRODUCT as stated herein. In no event shall the liability of the WARRANTOR exceed the purchase price of the PRODUCT.

DISCLAIMER: ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ALL IMPLIED WARRANTIES ARISING FROM A COURSE OF DEALING, USAGE OF TRADE, BY STATUTE OR OTHERWISE, IS HEREBY STRICTLY LIMITED TO THE TERM OF THIS WRITTEN WARRANTY. This Limited Warranty shall be the sole and exclusive remedy available to the PURCHASER with respect to this PRODUCT. In the event of any alleged breach of any warranty or any legal action brought by the PURCHASER based on alleged negligence or other tortious conduct by WARRANTOR, the PURCHASER'S sole and exclusive remedy will be repair or replacement of defective materials or refund of the purchase price, as stated herein.

TRANSFER OF LIMITED WARRANTY: This warranty is made by WARRANTOR with only first PURCHASER of the PRODUCT and does not extend to any subsequent PURCHASER or any third parties. The unexpired portion of this Limited Warranty may not be transferred to any entity.

APPLICABLE LAW: The parties expressly acknowledge and irrevocably agree that any and all claims or disputes arising out of or otherwise relating to this Limited Warranty shall be decided by a binding arbitration administered by the American Arbitration Association pursuant to Commercial Industry Rules in effect as of the date of this Limited Warranty, to the exclusion of any courts of any place, except as necessary for the enforcement of arbitration rights. The place for any such arbitration shall be The State of Wisconsin. PURCHASER expressly waives any provision of law in the jurisdiction in which PURCHASER is located or any other potentially applicable law which conflicts with any provision of this Limited Warranty at any time.

OTHER RIGHTS: Your acceptance of delivery of The PRODUCT constitutes your acceptance of the terms of this Limited Warranty. This Limited Warranty gives you specific legal rights, and you may also have other rights which vary from state to state. If any term or provision of this Limited Warranty is invalid or unenforceable under any local, state, or federal law, statute, judicial decision, regulation, ordinance, executive order or other rule of law, such term shall be deemed reformed or deleted, but only to the extent necessary to comply with such statute, regulation, ordinance, order or rule and the remaining provisions of this Limited Warranty shall remain in full force and effect.

ENTIRE AGREEMENT: This document alone contains the entire Limited Warranty given by WARRANTOR in respect of the PRODUCT. Nothing in WARRANTOR's product literature, marketing materials, advertisements and technical specifications expand or enlarge the scope of this Limited Warranty. There are no terms, promises, conditions or warranties regarding the PRODUCT other than those expressly contained herein. WARRANTOR specifically does not authorize any person, including but not limited to any dealer or other agent or employee of WARRANTOR, to extend the time, scope, terms or conditions of this Limited Warranty or to create or assume for WARRANTOR any other obligation or liability with respect to the PRODUCT or other products designed, manufactured or sold by WARRANTOR. All terms of this Limited Warranty are contractual and not mere recitals, and constitute material terms of this Limited Warranty. It is agreed and acknowledged that the provisions of this Limited Warranty allocate the risks between WARRANTOR and PURCHASER, that WARRANTOR's pricing reflects this allocation of risk, and but for this allocation and limitation of liability, WARRANTOR would not have entered into this Limited Warranty. The agents, employees, and dealers of Caleffi Products are not authorized to make modifications to this limited warranty or make additional warranties binding on Caleffi.

THIS DOCUMENT AND ALL PROVISIONS CONTAINED HAS BEEN SPECIFICALLY AGREED BETWEEN THE PARTIES.



HAVE A QUESTION? WANT TO LEARN MORE?

We are committed to your success and are here to help. Check out our website CALEFFI.US to explore an expansive collection of product information, training webinars, BIM objects, and our expansive library of educational idronics™ journals.



CALEFFI NORTH AMERICA INC.

INQUIRIES:

SALES:

sales@caleffi.com

TECHNICAL SUPPORT:

techsupport.us@caleffi.com

MARKETING/PR:

marketing.us@caleffi.com

SEARCHING FOR A REPRESENTATIVE

www.caleffi.info/dealerlocator/



Suggested List Price

Effective August 1, 2022

Canceling All Prior Issues

specifications and prices are subject to change without notice

Caleffi North America, Inc..

3883 W. Milwaukee Road · Milwaukee, WI 53208

Tel: 414.238.2360 · Fax: 414.238.2366

sales@caleffi.com | www.caleffi.com

© 2022 Copyright Caleffi



SKU: 22-01-V2